View NSN Online: https://aerobasegroup.gr/nsn/6830-01-371-0501

## DDRV STOCK MAINTENANCE DIV/DDRV-M/ -- 1301 -- 6830-01-371-0501

Product ID:1301 MSDS Date:10/03/1995 FSC:6830 NIIN:01-371-0501 MSDS Number: BXWQL === Responsible Party === Company Name: DDRV STOCK MAINTENANCE DIV/DDRV-M/ Address:8000 JEFFERSON-DAVIS HIGHWAY City:RICHMOND State:VA ZIP:23297 Country:US Info Phone Num:804-279-3125 Emergency Phone Num:800-851-8061 Prep arer's Name:DGSC-VBA/HMIS CAGE:02LX8 === Contractor Identification === Company Name: DDRV STOCK MAINTENANCE DIV/DDRV-H Address:8000 JEFFERSON-DAVIS HIGHWAY Box:City:RICHMOND State:VA ZIP:23297 Country:US Phone:804-279-3125 CAGE:02LX8 

Ingred Name:TRIFLUOROBROMOMETHANE (HALON 1301) (SARA 313) (CERCLA) CAS:75-63-8 RTECS #:PA5425000 Fraction by Wt: 100% Other REC Limits:NONE RECOMMENDED OSHA PEL:1000 PPM ACGIH TLV:1000 PPM; 9495 LD50 LC50 Mixture: TLV 1000 PPM

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:TARGET ORGANS:CNS, EYES, SKIN, LUNGS.

ACUTE- EYE:CONTACT WITH LIQUID CAN CAUSE "FREEZER" BURNS.

SKIN:LIQUID CAN CAUSE FROSTBITE. ORAL:NOT LIKELY. INHALE:TOXIC BY INHALATION. MAY CAUSE IRREGULARITIES IN THE CENTRAL NER

VOUS SYSTEM

AND CARDIAC MUSCLES. CHRONIC- UNKNOWN.

Explanation of Carcinogenicity:NONE

Effects of Overexposure: FROSTBITE, EYE BURNS, HEADACHE, DIZZINESS, CONFUSION, INCOORDINATION, UNCONSCIOUSNESS, IRREGULAR PULSE, CONVULSION

Medical Cond Aggravated by Exposure:ANEMIA, ASTHMA, DERMAL SENSITIVITY AND LOW BLOOD PRESSURE

First Aid:CALL A DOCTOR IF SYMPTOMS PERSIST. EYE:IMMEDIATELY FLUSH WITH WATER FOR 15 MINU

TES, HOLDING EYELIDS OPEN. SKIN:REMOVE

CONTAMINATED CLOTHING AND WASH EXPOSED SKIN WITH LARGE AMOUNT OF WATER. INHALED:RE MOVE TO FRESH AIR. PROVIDE CPR/OXYGEN IF NEEDED. ORAL:NOT A POTENTIAL ROUTE OF EXPOSURE.

Flash Point:NONE

Extinguishing Media:NON-FLAMMABLE. COOL FIRE EXPOSED CONTAINERS WITH WATER WELL AFTER FIRE IS OUT TO PREVENT POSSIBLE EXPLOSIONS Fire Fighting Procedures:WEAR PROTECTIVE CLOTHING AND NI OSH-APPROVED

SELF-CONTAINED BREATHING APPARATUS. SEE 1990 EMERGENCY RESPONSE GUIDEBOOK, DOT P 5800.5, GUIDE NO 12.

Unusual Fire/Explosion Hazard: IRRITATING AND/OR TOXIC GASES DUE TO DECOMPOSITION OF THE PRODUCT MAY BE GENERATED DURING A FIRE. CONTAINERS MAY EXPLODE DUE TO FIRE.

Spill Release Procedures:WEAR PROTECTIVE EQUIPMENTS. VENTIALTE AREA. CONTAIN SPILL. COLLECT SPILL WITH ABSORBENT MATERIAL AND PLAC E INTO A DRUM APPROVED FOR WASTE DISPOSAL. Neutralizing Agent:NOT RELEVANT

| ======================================   |
|--|
| <ul> <li>Handling and Storage Precautions:STORE IN A COOL, WELL-VENTILATED AREA<br/>AWAY FROM HEAT, FLAMES, HOT SURFACES AND INCOMPATIBLE MATERIALS. DO<br/>NOT SMOKE WHILE WORKING WITH THIS PRODUCT.</li> <li>Other Precautions:AVOID EYE AND SKIN CONTACT. DO NOT INHALE VAPORS.<br/>KEEP OUT OF REACH OF CHILDREN. WASH THOROUGHLY AFTER HANDLING AND<br/>BEFORE EATING OR DR<br/>INKING</li> </ul>  |
| ======================================   |
| Respiratory Protection: IF ENGINEERING CONTROLS DO NOT MAINTAIN AIRBORNE<br>CONCENTRATIONS TO AN ACCEPTABLE LEVEL, A NIOSH-APPROVED<br>SELF-CONTAINED BREATHING APPARATUS MUST BE WORN.<br>Ventilation: PROVIDE SUFFICIENT MECHANICAL (GENERAL AND/OR LOCAL<br>EXHAUST) VENTILATION TO MAINTAIN EXPOSURE TO A MINIMUM LEVLE.<br>Protective Gloves: NITRILE OR NATURAL RUBBER<br>Eye Protection: SPLASH PROOF GOGGLES WITH SIDE SHIELDS<br>Other Prot<br>ective Equipment: EYE WASH STATION, EMERGENCY SHOWER,<br>IMPERVIOUS BODY COVERING AND BOOTS WHERE SPILLS OR SPLASHING OCCUR<br>Work Hygienic Practices: OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND<br>RECOMMENDED PROCEDURES.<br>Supplemental Safety and Health<br>THIS MSDS WAS PREPARED BY THE PROFESSIONALS OF DGSC-VBA/HMIS WITHOUT<br>ANY WARRANTY. IT IS THE USER'S RESPONSIBILITY TO GATHER INFORMATION<br>AND USE THE MATERIAL PROPERLY TO PROTECT EMPLOYEES AND ENVIRONM<br>ENT. |
| ======================================   |
| HCC:G3<br>NRC/State Lic Num:NOT RELEVANT<br>Boiling Pt:B.P. Text:-72F,-58C<br>Melt/Freeze Pt:M.P/F.P Text:-270F,-168C<br>Decomp Temp:Decomp Text:850F,454C<br>Vapor Density:5.14<br>Spec Gravity:1.54<br>Viscosity:NOT RELEVANT<br>Evaporation Rate & amp; Reference:LIQUEFIED GAS<br>Solubility in Water:NEGLIGIBLE<br>Appearance and Odor:CLEAR LIQUEFIED GAS WITH SLIGHT ETHEREAL ODOR<br>Percent Volatiles by Volume:100   |
| Stability and Reactivity Data  |

Stability I

ndicator/Materials to Avoid:YES ALKALINE EARTH METALS, ALKALI, POWDERED ALUMINUM, ZINC, BERYLLIUM Stability Condition to Avoid:EXPOSURE TO FLAMES OR HOT SURFACES ABOVE 850F (454C)

Hazardous Decomposition Products:HYDROBROMIC AND HYDROFLUORIC ACIDS, POSSIBLY FREE HALIDES AND CARBONYL HALIDES

Waste Disposal Methods:RECOVERED MATERIAL CAN BE INCINERATED IN A FURNACE WHERE PERMITTED. OBSERVE ALL LOCAL, STATE AND FEDERA

L

REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their

particular situation.