View NSN Online: https://aerobasegroup.gr/nsn/3439-01-397-5992

HOBART TAFA TECHNOLOGIES INC -- CHROME CARBIDE 15 NICKEL CHROMIUM,1372 V -- 3439-01-397-5992

Product ID:CHROME CARBIDE 15 NICKEL CHROMIUM, 1372 V MSDS Date:07/15/1994 FSC:3439 NIIN:01-397-5992 MSDS Number: BYCGY === Responsible Party === Company Name: HOBART TAFA TECHNOLOGIES INC Address:146 PEMBROKE RD City:CONCORD State:NH ZIP:03301 Country:US Info Phone Num:603-224-9585 Emergency Phone Num:603-224-9585 CAGE:FO895 === Contractor Identification === Company Name: HOBART TAFA TECHNOLOGIES INC Address:146 PEMBROKE RD City:CONCORD State:NH ZIP:03301-5000 Country:US Phone:603-224-9585 CAGE:FO895 Company Name:STARGHILL TECHNOLOGIES CORP Address:3850 OAKMAN BLVD Box:City:DETROIT State:MI ZIP:48204-1119 Country:US Phone:313-933-4141 CAGE:0VYG8 **Company Name: TAFA INC** Address:146 PEMBROKE RD Box:City:CONCORD State:NH ZIP:03301 Country:US Phone:603-224-9585 CAGE:2605

Ingred Name:CHROMIUM (SARA 313) (CERCLA) CAS:7440-47-3 RTECS #:GB4200000 Fraction by Wt: 3% Other REC Limits:NONE RECOMMENDED OSHA PEL:1 MG/M3 ACGIH TLV:0.5 MG/M3; 9495 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

7

Ingred Name:NICKEL (SARA 313) (CERCLA) CAS:7440-02-0 RTECS #:QR5950000 Fraction by Wt: 12% Other REC Limits:NONE RECOMMENDED OSHA PEL:1 MG/M3 ACGIH TLV:1 MG/M3; 9495

Ingred Name:CHROMIUM CARBIDE CAS:12012-35-0 Fraction by Wt: 85% Other REC Limits:NONE RECOMMENDED OSHA PEL:0.5 MG CR/M3 ACGIH TLV:0.05 MG CR/M3

LD50 LC50 Mixture:LD50 (ORAL RAT) IS NOT RELEVANT.
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO
Health Hazards Acute and Chronic:TARGET ORGANS:EYE, SKIN, RESPIRATORY
TRACT. ACUTE- ARC RAYS CAN INJURE EYES & BURNS SKIN. INHALATION OF
FUMES MAY DAMAGE LUNGS. SWALLOWI
NG CHROMIUM SALTS CAN CAUSE SEVERE
INJURY/DEATH. DUST ON SKIN CA N FORM ULCERS & ON EYES CAUSES BURNS.
ALLERGIC REACTION MAY OCCUR. CHRONIC- ULCERATION, LUNG FIBROSIS, BRONCHIAL ASTHMA.
Explanation of Carcinogenicity:CONTAINS NICKEL AND CHROMIUM.
Effects of Overexposure:IRRITATION, SKIN DERMATITIS OR ECZEMA, COUGH, WHEEZING AND SHORTNESS OF BREATH, DECREASED PULMONARY FUNCTION, HEADACHE, NAUSEA, VOMITING, WEAKNESS, CONVULSIONS, RESPIRATORY AND

SKIN SENSITIZATION, BUR NS,

METALLIC TASTE, METAL FUME FEVER Medical Cond Aggravated by Exposure:INDIVIDUALS WITH PRE-EXISTING DISEASES OF THE EYE, SKIN, RESPIRATORY TRACT MAY HAVE INCREASED SUSCEPTIBILITY TO THE TOXICITY OF EXCESSIVE EXPOSURES.

First Aid:OBTAIN MEDICAL ATTENTION IF NEEDED. EYES:FLUSH WITH WATER FOR 10 MINUTES. KEEP EYELIDS OPEN. SKIN:WASH WITH SOAP & WATER. INHALATION:MOVE TO FRESH AIR. PROVIDE CPR/OXYGEN IF NEEDED.

INGESTION:DRINK LA RGE AMOUNT OF WATER & INDUCE VOMITING. CALL PHYSICIAN.

Flash Point:NONE

Extinguishing Media:COVER BURNING POWDER WITH DRY SAND OR LIMESTONE TO SMOTHER FLAMES. IF FIRE OCCURS IN DRUMS, SEAL DRUM WITH LID.
Fire Fighting Procedures:WEAR PROTECTIVE CLOTHING AND NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS.
Unusual Fire/Explosion Hazard:FINE METAL DUSTS MAY PRESENT FIRE OR EXPLOSION HAZARD

IN CONFINED AREAS. THIS IS NOT EXPECTED UNDER NORMAL HANDLING PROCEDURES.

Spill Release Procedures:WEAR PROTECTIVE EQUIPMENTS. VENTILATE AREA. VACUUM LOOSE POWDER ONLY WITH VACUUMS EQUIPPED WITH HEPA FILTERATION. WIPE AREA CLEAN. DO NOT USE WATER FOR CLEAN UP OPERATION. DO NOT SWEEP. PLACE IN A BAG AND HOLD FOR WASTE DISPOSAL. AVOID RAISING DUST. Neutralizing Agent:NOT RELEVANT

====== Hand

Handling and Storage Precautions:STORE IN A DRY, VENTILATED PLACE AWAY FROM INCOMPATIBLES. KEEP CONTAINER TIGHTLY CLOSED. KEEP OUT OF REACH OF CHILDREN.

Other Precautions: AVOID INGESTION, INHALATION AND EXCESSIVE SKIN CONTACT. AVOID BREATHING OF FUMES OR DUST. USE WITH ADEQUATE VENTILATION. WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING AND DRINKING. REMOVE CONTAMINA TED CLOTHING. LAUNDER BEFORE REUSE.

======== Exposure Contr

ols/Personal Protection ========

Respiratory Protection: A NIOSH-APPROVED RESPIRATOR WITH FILTER CARTRIDGES APPROVED FOR DUST/FUMES/MISTS SHOULD BE WORN AT ALL TIMES DURING THE THERMAL SPRAY PROCESS. RESPIRATORS MAY ALSO BE WORN WHEN PRODUCT HANDLING GENERA TES DUST.
Ventilation: USE ENOUGH VENTILATION TO KEEP THE DUSTS, FUMES AND GASES BELOW THE PELS OR TLVS IN THE WORKER'S BREATHING ZONE.
Protective Gloves: WELDER'S GLOVE WHEN WELDING
Eye Protection: USE # 5 SHADE SAFETY GLA
SSES IF WELDING.
Other Protective Equipment: EYE WASH STATION, SAFETY SHOWER, HEAD, HAND & BODY PROTECTION TO PREVENT INJURY FROM RADIATION, SPARKS & ELECTRIC SHOCK.
Work Hygienic Practices: OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES.

Supplemental Safety and Health

## HCC:T6

NRC/State Lic Num:NOT RELEVANT Melt/Freeze Pt:M.P/F.P Text:2372F,1300C Viscosity:NOT RELEVANT Evaporation Rate & amp; Refer ence:NOT RELEVANT Solubility in Water:INSOLUBLE Appearance and Odor:GREY POWDER - NO ODOR

Stability Indicator/Materials to Avoid:YES ACIDS Stability Condition to Avoid:PRODUCTION OF FINE POWDER Hazardous Decomposition Products:WELDING FUMES (OXIDES OF METAL BEING WELD) & GASES SUCH AS OZONE, CARBON MONOXIDE, CARBON DIOXIDE, NITROGEN OXIDES

Waste Disp

osal Methods:PRIOR TO DISPOSAL, CONSIDER IF MATERIAL HAS RECOVERY VALUE. EMPTY PRODUCT CONTAINERS, PROUCT WASTE AND CLEANING MEDIA SHOULD BE DISPOSED OF IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS. PREVENT WASTE FROM CONTAMINATING ENVIRONMENT.

The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.