View NSN Online: https://aerobasegroup.com/nsn/8010-01-266-6576

Product ID:COMP B, LOW DENSITY, LOW IH PRIMER

MSDS Date:06/10/1993

FSC:8010

NIIN:01-266-6576

Kit Part:Y

MSDS Number: BYCPR === Responsible Party === Company Name: DEFT, INC.

Address:17451 VON KARMAN AVENUE

City:IRVINE, State:CA ZIP:92714 Country:US

Info Phone Num:714-474-0400

Emergency Phone Num

:714-474-0400 CAGE:DO188

=== Contractor Identification === Company Name: DEFT, INC.

Address:17451 VON KARMAN AVE

City:IRVINE State:CA ZIP:92614

Country:US Phone:949-474-0400

CAGE:33461

Company Name: DEFT, INC.

Address:17451 VON KARMAN AVE

City:IRVINE State:CA ZIP:92714

Phone:800-424-9300

CAGE:DO188

======= Composition/Information on Ingredients ========

Ingred Name: NITROETHANE

CAS:79-24-3

RTECS #:KI5600000 Fraction by Wt: 30%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:100 PPM

ACGIH

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: VAPORS ARE IRRITATING TO EYES, NOSE & THROAT. INHALATION MAY CAUSE HEADACHES, DIFFICULT BREATHING & LOSS OF CONSCIOUSNESS. CHRONIC: PROLONGED CONTACT WILL CAUSE DRYING & CRACKING OF THE SKIN, D UE TO DEFATTING ACTION. SKIN SENSITIZATION, ASTHMA OR ALL

ERGIC REACTION MAY DEVELOP.

Explanation of Carcinogenicity: DOSE NOT CONTAIN A CARCINOGEN.

Effects of Overexposure:INHALATION-HEADACHE, DIZZINESS, STAGGERING GAIT, CONFUNSION, UNCONSCIOUSNESS OR COMA. SKIN & EYE-MAY BE SWELLING, REDNESS, RASH. TEARING, REDNESS & SWELLING ACCOMPANIED BY STINGING SENSATION. INGESTIO N-VOMITING MAY CAUSE ASPIRATION OF THE SOLVENT RESULTING IN CHEMICAL PNEUMONITIS.

Medical Cond Aggravated by Exposure: ASTHMA AND ANY OTHER RESPIRATORY DISORDER. SKIN

ALLERGIES, ECZEMA, AND DERMATITIS.

First Aid:INHALE:MOVE TO AN AREA FREE FROM RISK OF FUTHER EXPOSURE. RESTORE BREATHING. OBTAIN MEDICAL ATTN. SKIN:REMOVE CONTAMINATED CLOTHING. WASH AFFECTED AREAS THOROUGHLY WITH SOAP & WATER. EYES:FLUSH WITH C LEAN, LUKEWARM WATER FOR 15 MIN, OCCASIONALLY LIFTING EYELIDS. OBTAIN MEDICAL ATTENTION. INGEST:DO NOT INDUCE VOMITING. DO NOT GIVE ANYTHING BY MOUTH TO AN UNCONS CIOUS PERSON.

OBTAIN MEDICAL ATTENTION

============= Fire Fighting Measures ========================

Flash Point Method:TCC Flash Point:=30.6C, 87.F

Lower Limits:1 Upper Limits:8

Extinguishing Media:FOAM, ALCOHOL FOAM, CARBON DIOXIDE, DRY CHEMICAL, WATER FOG. WATER MAY BE USED TO COOL CLOSED CONTAINERS.

Fire Fighting Procedures: FULL FIRE FIGHTING EQUIPMENT WITH SELF-CONTAINED BREATHING APPARATUS & FULL PROTECTIVE CLOTHING SHOULD BE WARN BY FIRE FIGHTERS.

Unusual Fire/Ex



======== Accidental Release Measures ===========

Spill Release Procedures:EVACUATE ALL NONESSENTIAL PERSONNEL. REMOVE ALL SOURCES OF IGNITION (FLAME, HOT SURFACES, SPARK SOURCES) VENTILATE AREA. CONTAIN AND REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS.

Handling and Storage Precautions:STORE IN BUILDING DESIGNED TO COMPLY WITH OSHA 1910.106. AVOID STORING NEAR HIGH TEMPERATURES, FIRE, OPEN FLAMES & SPARK SOURCES.

Other Precautions:STORE IN WELL VENTILATED AREAS. STORE IN TIGHTLY CLOSED CONTAINERS. KEEP CONTAINERS TIGHT & UPRIGHT TO PREVENT LEAKAGE. PREVENT PROLONGED OR REPEATED BREATHING OF VAPORS OR SPRAY MIST.

===== Exposure Controls/Personal Protection ========

Res

piratory Protection: A RESPIRATOR THAT IS RECOMMENDED OR APPROVED FOR USE IN AN ORGANIC VAPOR ENVIROMENT (AIR PURIFYING OR FRESH AIR SUPPLIED) IS NECESSARY. OBSERVE OSHA REGULATIONS FOR RESPIRATOR USE.

Ventilation: EXHAUST VENTILATION SUFFICIENT TO KEEP THE AIRBORNE CONCENTRATIONS OF THE SOLVENT VAPORS OR MIST BELOW THEIR TLV'S.

Protective Gloves: COTTON, NEOPRENE, RUBBER, POLYETHYLENE.

Eye Protection: SAFETY EYEWARE W/SPLASH GUARDS.

Other Protective Equipment: USE LONG SLEEVE AND LON

G LEG CLOTHING.

REMOVE AND WASH CONTAMINATED CLOTHING BEFORE REUSE.

Work Hygienic Practices: WASH HANDS BEFORE EATING, SMOKING OR USING WASHROOM. SMOKE IN SMOKING AREAS ONLY.

Supplemental Safety and Health

OTHER PRECAUTIONS: PROLONGED OVEREXPOSURE CAN CAUSE AN ALLERGIC REACTION. AVOID CONTACT WITH SKIN & EYES. DO NOT TAKE INTERNALLY. DO NOT HANDLE UNTIL MANUFACTURES SAFETY PRECAUTIONS HAVE BEEN READ AND UNDERSTOOD. WASH HANDS BEFORE EATING, SMOKING OR USING WASHROOM. SMOK

E IN SMOKING AREAS ONLY.**ITEM IS A TWO PART KIT**
========== Physical/Chemical Properties =============
HCC:F3
Boiling Pt:=113.9C, 237.F
Vapor Density:>AIR Spec Gravity:1.12845
Viscosity:VARIES
Evaporation Rate & Reference:1.27 X N-BUTYL ACETATE Solubility in Water:INSOLUBLE
Appearance and Odor:AMBER LIQUID WITH SOLVENT ODOR.
Percent Volatiles by Volume:32.3
======================================
Clasmy and Measurity Data
Stability Indicator/Materials to Avoid:YES STRO
NG OXIDIZING AGENTS AND STRONG LEWIS OR MINERAL ACIDS.
Stability Condition to Avoid:HIGH TEMPERATURES, SPARKS, OR OPEN FLAMES. AVOID UNCONTROLLED REACTIONS WITH AMINES.
Hazardous Decomposition Products:BY HIGH HEAT AND FIRE: CARBON DIOXIDE,
CARBON MONOXIDE, OXIDES OF NITROGEN. ALDEHYDES & ACIDS MAY BE FORMED.
========== Disposal Considerations ================
Waste Disposal Methods:WASTE MUST BE DISPOSED OF IN ACCORDANCE WITH FEDERAL, STATE AND LCOAL ENVIRONMEN
TAL CONTROL REGULATIONS. EMPTY
CONTAINERS MUST BE HANDLED WITHCARE DUE TO PRODUCT RESIDUE AND FLAMMABLE VAPOR. DO NOT IN CINERATE CLOSED CONTAINERS.
Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever.

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.