

ALLIED ENTERPRISES, INC. -- FORMULA 1309 WATER-BASED STAINLESS STEEL CLEANER & POLISH -- 7930-01-398-1010

===== Product Identification =====

Product ID:FORMULA 1309 WATER-BASED STAINLESS STEEL CLEANER & POLISH

MSDS Date:04/28/1994

FSC:7930

NIIN:01-398-1010

MSDS Number: BYCXV

=== Responsible Party ===

Company Name:ALLIED ENTERPRISES, INC.

Address:814 W. 45TH STREET

Box:6159

City:NORFOLK

State:VA

ZI

P:23508-2008

Country:US

Info Phone Num:804-489-8282

Emergency Phone Num:800-535-5053

CAGE:58396

=== Contractor Identification ===

Company Name:ALLIED ENTERPRISES, INC.

Address:814 W. 45TH STREET

Box:6159

City:NORFOLK

State:VA

ZIP:23508-2008

Country:US

Phone:757-489-8282

CAGE:58396

===== Composition/Information on Ingredients =====

Ingred Name:PROPANE

CAS:74-98-6

RTECS #:TX2275000

Fraction by Wt: 5-20%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:1000 PPM

ACGIH TLV:1000 PPM

Ing

red Name: BUTANE  
CAS: 106-97-8  
RTECS #: EJ4200000  
Fraction by Wt: 5-20%  
Other REC Limits: NONE RECOMMENDED  
OSHA PEL: 800 PPM  
ACGIH TLV: 800 PPM

Ingred Name: PETROLEUM DISTILLATES  
CAS: 64742-48-9  
Fraction by Wt: 1-5%  
Other REC Limits: NONE RECOMMENDED  
OSHA PEL: 100 PPM  
ACGIH TLV: 100 PPM

=====  
Hazards Identification  
=====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:EYES: MAY CA  
USE TRANSIENT PAIN.

=====  
First Aid Measures  
=====

First Aid: QUICKLY FOLLOW DIRECTIONS BELOW: GET QUICK MEDICAL ATTN. IF  
ANY ILL AFFECTS CONTINUE OR DEVELOP LATER. EYES: FLUSH W/PLENTY  
WATER. REMOVE CONTACT LENSES. THEN HOLD EYES OPEN & CONTINUE  
FLUSHING THOROUGHLY.

=====  
Fire Fighting Measures  
=====

Flash Point: 47.0F, 8.3C  
Lower Limits: 1.0  
Upper Limits: 7.0  
Extinguishing Media: FOAM, DRY CHEMICAL, CO2.  
Fire Fighting Procedures: KEEP CONTAINERS COOL. USE SHIELDING TO PROTECT  
PERSONNEL AGAINST BURSTING, RUPTURING OR VENTING CONTAINERS.  
Unusual Fire/Explosion Hazard: AT ELEVATED TEMPERATURES (OVER 120F)  
CONTAINERS MAY VENT, RUPTURE OR BURST.

=====  
Accidental Release Measures  
=====

Spill Release Procedures: REMOVE SOURCES OF FLAME, SPARK OR HEAT.  
PROVIDE ADEQUATE VENTILATION. WIPE SPILLS THEN WASH W/CLEANER TO  
REMOVE FINAL TRACES. FLOORS MAY BE SLIPPERY. USE CAUTION

TION TO AVOID  
FALLS.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:CAUTION: CONTENTS UNDER PRESSURE. KEEP  
OUT OF REACH OF CHILDREN. DO NOT STORE WHERE TEMPERATURES MAY  
EXCEED 120F.

Other Precautions:READ ENTIRE LABEL BEFORE USING.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:NONE REQUIRED.

Ventilation:ADEQUATE MECHANICAL (GENERAL)

Protective Gloves:NONE REQUIRED

Eye Protection:SAF

ETY GLASSES

Other Protective Equipment:NONE

Work Hygienic Practices:ALWAYS FOLLOW SAFE WORK PRACTICES.

Supplemental Safety and Health

NK

=====  
Physical/Chemical Properties  
=====

Boiling Pt:B.P. Text:212F,100C

Vapor Pres:18

Vapor Density: