

METALLURGICAL TECHNOLOGIES,INC -- METEC 4060C -- 3439-01-392-7054

=====
Product Identification
=====

Product ID:METEC 4060C
MSDS Date:03/09/1990
FSC:3439
NIIN:01-392-7054
MSDS Number: BYHCW
=== Responsible Party ===
Company Name:METALLURGICAL TECHNOLOGIES,INC
Address:14435 MAX ROAD
City:PEARLAND
State:TX
ZIP:77581
Country:US
Info Phone Num:713-485-7765
Emergency Phone Num:713-485-7765
CAGE:63726

=
== Contractor Identification ===
Company Name:METALLURGICAL TECHNOLOGIES,INC
Address:14435 MAX ROAD
Box:City:PEARLAND
State:TX
ZIP:77581
Country:US
Phone:713-485-7765
CAGE:63726

=====
Composition/Information on Ingredients
=====

Ingred Name:COBALT
CAS:7440-48-4
RTECS #:GF8750000
Fraction by Wt: 53.5%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:0.1 MG/M3
ACGIH TLV:0.1 MG/M3

Ingred Name:CHROMIUM
CAS:7440-47-3
RTECS #:GB4200000
Fraction by Wt: 25%
Other REC Limits:NONE RECOMMEND

ED
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:NICKEL
CAS:7440-02-0
RTECS #:QR5950000
Fraction by Wt: 11%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:1 MG/M3
ACGIH TLV:1 MG/M3

Ingred Name:TUNGSTEN
CAS:7440-33-7
RTECS #:YO7175000
Fraction by Wt: 7.5%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:5 MG/M3
ACGIH TLV:5 MG/M3

Ingred Name:IRON
CAS:7439-89-6
RTECS #:NO4565500
Fraction by Wt: 2%
Other REC Limits:NONE RECOMMENDED

Ingred Name:MANGANESE
CAS:7439-96-5
RTECS #:OO9275000
Fraction by Wt: 1%
O
ther REC Limits:NONE RECOMMENDED

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:YES OSHA:NO
Health Hazards Acute and Chronic:INHALATION: ACUTE-BRONCHITIS.
CHRONIC-SIDEROSIS. EYE CONTACT: ACUTE-MECHANICAL IRRITATION.
CHRONIC-CONJUNCTIVITIS.
Explanation of Carcinogenicity:METALLIC CO. METALLIC CR.

=====
===== First Aid Measures =====

Fi

rst Aid:EYE CONTACT-FLUSH EYES WITH LARGE AMOUNTS OF WATER.

=====
Fire Fighting Measures
=====

Extinguishing Media:DRY CHEMICAL, DRY SAND OR GRAPHITE TO SMOTHER FIRE.
USE WATER ONLY IN MIST/FOG APPLICATION TO AVOID SPREADING POWDER.

Fire Fighting Procedures:FIREFIGHTERS SHOULD USE SELF-PROTECTIVE
CLOTHING AND EQUIPMENT.

Unusual Fire/Explosion Hazard:NOT CONSIDERED FLAMMABLE UNDER MOST
CONDITIONS. AVOID AIRBORN DISPERSION OF ANY FINE DIVIDED POWDER
ON

AN ENCLOSED INDUSTRIAL AREA TO REDUCE POTENTIAL FOR IGNIT

=====
Accidental Release Measures
=====

Spill Release Procedures:USE WET METHODS OR VACUUM CLEANING INSTEAD OF
DRY SWEEPING TO AVOID GENERATION OF AIRBORNE DUST.

Neutralizing Agent:NA

=====
Handling and Storage
=====

Handling and Storage Precautions:SYORE IN CLOSED CONTAINERS.

Other Precautions:DO NOT STORE ADJACENT TO STRONG OXIDIZERS.

=====
Exposure
Controls/Personal Protection
=====

Respiratory Protection:NIOSH APPROVED DUST RESPIRATOR.

Ventilation:LOCAL EXHAUST-REQUIRED IF OSHA STANDARD IS EXCEEDED.

Protective Gloves:WORK GLOVES.

Eye Protection:SAFETY GLASSES.

Other Protective Equipment:NONE.

Work Hygienic Practices:GOOD HOUSEKEEPING HABITS.

Supplemental Safety and Health

NONE

=====
Physical/Chemical Properties
=====

HCC:N1

Solubility in Water:INSOLUBLE.

Appearance and Odor:GREY COLOR FINE POWDER, N

O ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

REACTS WITH MINERAL ACIDS TO LIBERATE HYDROGEN.

Stability Condition to Avoid: GENERATION OF AIRBORNE DUST.

Hazardous Decomposition Products: EVOLVED HYDROGEN MAY BECOME EXPLOSIVE.

===== Disposal Considerations =====

Waste Disposal Methods: PROCEDURES COMPLYING WITH FEDERAL, STATE AND LOCAL WASTE ORDINANCES.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.