

METALCRETE MANUFACTURING CO -- SC-4-OZ INSTAROK CABLE,SEALING CEMENT --
8030-01-084-9759

===== Product Identification =====

Product ID:SC-4-OZ INSTAROK CABLE,SEALING CEMENT

MSDS Date:03/01/1992

FSC:8030

NIIN:01-084-9759

MSDS Number: BYPBG

=== Responsible Party ===

Company Name:METALCRETE MANUFACTURING CO

Address:10330 BRECKSVILLE RD

City:CLEVELAND

State:OH

ZIP:44141-5000

Country:US

Info Phone Num

:216-526-5600

Emergency Phone Num:216-526-5600

CAGE:MCRET

=== Contractor Identification ===

Company Name:METALCRETE MANUFACTURING CO

Address:10330 BRECKSVILLE RD

City:CLEVELAND

State:OH

ZIP:44141

Country:US

Phone:216-526-5600;800-424-9300(CHEMTREC)

CAGE:MCRET

===== Composition/Information on Ingredients =====

Ingred Name:PLASTER OF PARIS; CALCIUM SULFATE HEMIHYDRATE

CAS:10034-76-1

RTECS #:EW4150000

Fraction by Wt: 55%

ACGIH TLV:10 MG/CUM

Ingred Name:SILICA ACID, CALCIUM SALT

95-4
CAS:1344-95-2
RTECS #:VV9150000
Fraction by Wt: 44%
OSHA PEL:0.05 MG/CUM (CD)
ACGIH TLV:10 MG/CUM

Ingred Name:FLOW CONTROL AGENTS
Fraction by Wt: 1%

=====
Hazards Identification
=====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYES/SKIN: MAY CAUSE IRRITATION.
INHALATION: DUST IS CONSIDERED A NUISANCE DUST. THIS PRODUCT
HARDENS WHEN WETTED & IF
INGESTED MAY RESULT IN OBSTRUCTION.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:IRRITATION

=====
First Aid Measures
=====

First Aid:EYES: IMMEDIATELY FLOOD W/WATER FOR 15 MINS. SKIN: REMOVE BY
WASHING. OBTAIN MEDICAL ATTENTION IN ALL CASES.

=====
Fire Fighting Measures
=====

Flash Point:NONCOMBUSTIBLE
Extinguishing Media:USE MEDIA APPROPRIATE TO THE SURROUNDING AREA.

=====
Accidental Release Measures
=====

Spill Release Procedures:SWEEP UP & PLACE IN SUITABLE CONTAINERS. AVOID
CREATING EXCESSIVE DUST. DON'T WASH SLURRY DOWN DRAINS SINCE THIS
MAY CAUSE PLUGGING.

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE IN DRY LOCATION AWAY FROM
WATER/HIGH HUMIDITY CONDITONS TO AVOID PREMATURE HARDENING.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:USE NI

OSH APPROVED NUISANCE DUST RESPIRATOR IF

>TLV.

Ventilation:GENERAL MECHANICAL EXHAUST

Protective Gloves:REQUIRED

Eye Protection:SAFETY GLASSES

Other Protective Equipment:NONE

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Spec Gravity:2.7

pH:9

Solubility in Water:2%

Appearance and Odor:GRAY, ODORLESS POWDER

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

WATER

=====

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF AS SOLID WASTE IN LANDFILL IN
ACCORDANCE W/LOCAL, STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any pers

on utilizing this

document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.