

DU PONT E I DE NEMOURS & CO INC -- FREON 114 (DU001061) -- 6830-00-782-6512

===== Product Identification =====

Product ID:FREON 114 (DU001061)

MSDS Date:10/07/1991

FSC:6830

NIIN:00-782-6512

MSDS Number: BYXTV

=== Responsible Party ===

Company Name:DU PONT E I DE NEMOURS & CO INC

Address:1007 MARKET STREET

Box:1635

City:WILMINGTON

State:DE

ZIP:19898

Country:US

Info Phone Num:800-441-9442

Emergency

Phone Num:800-441-3637(MEDICAL) OR CHEMTREC

Preparer's Name:W. J. BROCK

CAGE:18873

=== Contractor Identification ===

Company Name:E.I. DUPONT DE NEMOURS & CO

Address:1007 MARKET STREET

Box:City:WILMINGTON

State:DE

ZIP:19898

Country:US

Phone:800-441-7515;800-441-9442

CAGE:18873

===== Composition/Information on Ingredients =====

Ingred Name:ETHANE, 1,2-DICHLOROTETRAFLUORO-("FREON" 114) (SARA 313)

CAS:76-14-2

RTECS #:KI1101000

Fraction by Wt: 100%

Other REC Limits:NONE RECOMMEND

ED
OSHA PEL:1000 PPM, 8 HR TWA
ACGIH TLV:1000 PPM, 8 HR TWA
Ozone Depleting Chemical:1

===== Hazards Identification =====

LD50 LC50 Mixture:SEE SUPPLEMENTAL DATA.
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:UNKNOWN IARC:UNKNOWN OSHA:NO
Health Hazards Acute and Chronic:SKIN: POS IRRIT/RASH/FROSTBITE. EYES:
IRRITATION/TEARING/BLURRY VISION. INHAL: POS NONSPECIFIC DISCOMFORT
(NAUSEA/HEADACHE/WEAKNESS; TEMPORARY ALTERATION HEART ELECTRICAL
ACTIVITY W/IRREG PULSE/PALPITATIONS/INADEQUATE CIRCULATION.) DEATH
POS W/GROSS OVEREXPOS. INTENTIONAL MISUSE/DELIBERATE INHAL MAY
CAUSE DEATH W/O*
Explanation of Carcinogenicity:CONTAINS 2-A [53-96-3]
WHICH IS LISTED BY NTP AND IARC AND REGULATED BY OSHA AS A
CARCINOGEN.
Effects of Overexposure:NK *WARNING. VAPOR REDUCES OXYGEN AVAILABLE
FOR BREATHING & IS HEAVIER THAN AIR.
Medical Condition Aggravated by Exposure:INDIVIDUALS W/PREEXISTING
DISEASES
OF CNS, CARDIOVASCULAR SYSTEM MAY HAVE INCREASED SUSCEPTIBILITY TO
TOXICITY OF EXCESSIVE EXPOSURES.

===== First Aid Measures =====

First Aid:INHAL: GET FRESH AIR IMMEDIATELY. KEEP CALM. IF NOT BREATHING GIVE
ARTIFICIAL RESPIRATION. IF BREATHING DIFFICULT, GIVE OXYGEN. CALL DR. SKIN:
FLUSH W/WATER 15 MIN. IF FROST BITE, WARM AFFECTED AREAS. GET MEDICAL
AID IF IRRITATION PRESENT. EYES: FLUSH IMMEDIATELY W/LOTS H2O 15 MIN. CALL
DR. NOTE TO DR.: BECAUSE POS
CARDIAC RHYTHM DISTURBANCE,
CATECHOLAMINE DRUGS (EPINEPHRINE) SHOULD BE USED W/SPECIAL CAUTION
IN EMERGENCY LIFE SUPPORT.

===== Fire Fighting Measures =====

Flash Point Method:TOC
Extinguishing Media:AS APPROPRIATE FOR COMBUSTIBLES IN AREA.
Fire Fighting Procedures:SCBA REQUIRED IF CYLINDERS RUPTURE/RELEASE
UNDER FIRE CONDITIONS.
Unusual Fire/Explosion Hazard:USE WATER SPRAY/FOG TO COOL CONTAINERS.
CYLINDERS ARE EQUIPPED W/TEMP & PRESSURE RELIEF DEVICES.

VICES BUT MAY
STILL RUPTURE UNDER FIRE CONDITIONS. DECOMP POSSIBLE.

===== Accidental Release Measures =====

Spill Release Procedures:REVIEW FIRE EXPLN HAZ/SAFETY PRECAUTIONS
BEFORE CLEAN UP. USE APPROPRIATE PERSONAL PROTECTIVE EQUIP.
VENTILATE AREA, ESPEC LOW PLACES WHERE VAPORS MIGHT COLLECT. USE
SCBA FOR LARGE SPILLS. REMOVE OPEN FLAMES. COMPLY W/APPLIC LAWS ON
REPORTING RELEASE

===== Handling and Storage =====
==

Handling and Storage Precautions:STORE CONTAINERS IN COOL, CLEAN DRY
AREA. DO NOT ALLOW TEMP TO RISE ABOVE 125F.
Other Precautions:AVOID BREATHING VAPORS. AVOID LIQUID CONTACT
W/SKIN/EYES. USE SUFFICIENT VENTILATION TO KEEP EMPLOYEE EXPOSURE
BELOW RECOMMENDED LIMITS. AQUATIC TOXICITY: 96 HR LC50, KILLIFISH =
45 PPM.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT REQUIRED UNDER NORMAL MFG CONDITIONS. SCBA
REQUIRED IF SPILL
OCCURS.
Ventilation:NORMAL FOR STANDARD MFG ADEQUATE. LOCAL EXHAUST WHEN LG
AMTS RELEASED. MECHANCL VENT SHOULD BE USED IN LOW PLACES.
Protective Gloves:RUBBER,PLASTIC
Eye Protection:CHEMICAL SPLASH GOGGLES
Other Protective Equipment:USE GLOVES & FACE SHIELD WHEN HANDLING
LIQUID
Supplemental Safety and Health
INHALATION 4-HR ALC = 383,000 PPM RATS. ORAL ALD RATS = >1500 MG/KG.

===== Physical/Chemical Properties =====

HCC:G3
Boiling Pt:B.P. Text:39.0F,3.9C
Va

por Pres:31PSIA@77F
Vapor Density:6.2 @ 77F
Evaporation Rate & Reference: