

DEL PAINT CORP. -- TT-E-2784 -- 8010-01-333-9822

===== Product Identification =====

Product ID:TT-E-2784

MSDS Date:08/01/1995

FSC:8010

NIIN:01-333-9822

MSDS Number: BYYLL

=== Responsible Party ===

Company Name:DEL PAINT CORP.

Address:3105 E. RENO

City:OKLAHOMA CITY

State:OK

ZIP:73117

Country:US

Info Phone Num:405-672-1431/FAX 405-672-0804

Emergency Phone Num:800-424-9300 24 HRS

Preparer's Name:ONEY FLEMING

CAGE:JO954

=== Contractor Identification ===

Company N

ame:DEL PAINT CORP.

Address:3105 E. RENO

City:OKLAHOMA CITY

State:OK

ZIP:73117

Country:US

Phone:405-672-1431/FAX 405-672-0804

CAGE:JO954

Company Name:DEL PAINT MFG

Address:3105 EAST RENO

Box:City:OKLAHOMA CITY

State:OK

ZIP:73117

Country:US

Phone:405-672-1431

CAGE:39934

===== Composition/Information on Ingredients =====

Ingred Name:PROPYLENE GLYCOL

CAS:57-55-6

RTECS #:TY2000000

Fraction by Wt: 3.72%

Other REC Limits:NONE RECOMMENDED

Ingred Name:2,2,4-TRIMETHYL-1-3-PENTANEDIOL

MONOISOBUTYRATE  
CAS:25265-77-4  
RTECS #:UF6000000  
Fraction by Wt: 3.43%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:DIMETHYLAMINOETHANOL LOW VOC  
CAS:108-01-0  
RTECS #:KK6125000  
Fraction by Wt: 0.22%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:2-N-OCTYL-4-ISOTHIAZOLIN-3-ONE  
CAS:26530-20-1  
Fraction by Wt: 0.18%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:NON HAZARDOUS INGREDIENTS  
Fraction by Wt: 92.45%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:NOT RELEVANT  
ACGIH TLV:NOT RELEVANT

=====

===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:CAN CAUSE IRRITATION OF RESPIRATORY  
PASSAGES.  
Effects of Overexposure:INHALATION OF VAPOR/MIST CAN CAUSE HEADACHES,  
NAUSEA, IRRITATION OF NOSE/THROAT/LUNGS. EYES: CAN CAUSE SLIGHT  
IRRITATION. CHRONIC SKIN CONTACT CAN CAUSE SLIGHT IRRITATION.  
Medical Cond Aggravated by Exposure:PREEXISTING LUNG DISEASE MAY BE  
AGGRAVATED BY EXPOSURE.

===== First Aid Measures =====

First Aid:EYES: FLUSH W/LARGE AMTS WATER 15 MINUTES. CONSULT DR. IF  
IRRITATION PERSISTS. SKIN: WASH AFFECTED AREA THOROUGHLY W/SOAP &  
WATER. INGESTION: GIVE 2 GLASSES WATER. CONSULT DR.

===== Fire Fighting Measures =====

Flash Point Method:SCC  
Flash Point:>212F,>100C  
Lower Limits:NA  
Upper Limits:NA  
Extinguishing Media:FOAM, ALCOHOL

L FOAM, CO2, DRY CHEMICAL, WATER FOG.

Fire Fighting Procedures:WEAR SCBA (PRESSURE DEMAND MSHA/NIOSH APPROVED OR EQUIVALENT) & FULL PROTECTIVE GEAR.

Unusual Fire/Explosion Hazard:MATERIAL CAN SPLATTER ABOVE 212F/100C.  
POLYMER FILM CAN BURN.

===== Accidental Release Measures =====

Spill Release Procedures:KEEP SPECTATORS AWAY. FLOOR MAY BE SLIPPERY.  
USE CARE TO AVOID FALLING. CONTAIN W/INERT MAT'L (SAND/EARTH).  
TRANSFER LIQ/SOLID DIKING MAT'L TO SEPAR  
ATE SUITABLE CONTAINERS FOR  
RECOVERY/DISPOSAL.

Neutralizing Agent:NONE

===== Handling and Storage =====

Handling and Storage Precautions:KEEP FROM FREEZING. DO NOT TAKE  
INTERNALLY. KEEP AWAY FROM CHILDREN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:APPROVED MECHANICAL FILTER RESPIRATOR TO REMOVE  
SOLID AIRBORNE PARTICLES OF OVER-SPRAY DURING SPRAY APPLICATION.

Ventilation:NORMAL, SUCH AS FAN.

Protec

tive Gloves:RUBBER

Eye Protection:SAFETY GLASSES OR GOGGLES.

Other Protective Equipment:EYEWASH STATION.

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:212 TO 644F

Melt/Freeze Pt:M.P/F.P Text:32.0F,0.0C

Decomp Temp:Decomp Text:350F,177C

Vapor Pres:NONE

Vapor Density:>AIR

Spec Gravity:1.14

VOC Pounds/Gallon:191

pH:9 MAX

VOC Grams/Liter:1.59

Viscosity:77-95 KU

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubilit

y in Water:SLIGHT  
Appearance and Odor:BLUE LIQUID, SLIGHT ODOR  
Percent Volatiles by Volume:60.6

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
NONE KNOWN  
Stability Condition to Avoid:NONE  
Hazardous Decomposition Products:ACRYLIC MONOMERS

===== Disposal Considerations =====

Waste Disposal Methods:KEEP SPILLS/CLEANING RUN-OFF OUT OF SEWERS &  
OPEN BODIES OF WATER. CONSULT FEDERAL/STATE/LOCAL AUTH  
ORITIES FOR  
PROPER DISPOSAL PROCEDURES CONCERNING HEALTH & ENVIRONMENT.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume respon  
sibility for the suitability of this information to their  
particular situation.