

POLYMERIC SYSTEMS, INC. -- PSI-690 PRIMER, 2 OF 2 -- 8040-00-902-3871

=====
Product Identification
=====

Product ID:PSI-690 PRIMER, 2 OF 2

MSDS Date:02/21/1995

FSC:8040

NIIN:00-902-3871

Kit Part:Y

MSDS Number: BZLHX

=== Responsible Party ===

Company Name:POLYMERIC SYSTEMS, INC.

Address:723 WHEATLAND ST.

City:PHOENIXVILLE

State:PA

ZIP:19460

Country:US

Info Phone Num:215-935-1170

Emergency Phone Nu

m:215-935-1170

Preparer's Name:ED CLUFF

CAGE:0KND3

=== Contractor Identification ===

Company Name:POLYMERIC SYSTEMS, INC.

Address:723 WHEATLAND STREET

Box:City:PHOENIXVILLE

State:PA

ZIP:19460

Country:US

Phone:610-935-1170

CAGE:0KND3

=====
Composition/Information on Ingredients
=====

Ingred Name:METHYL ISOBUTYL CARBINOL

CAS:108-11-2

RTECS #:SA7350000

Fraction by Wt: 93%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:S,25 PPM

ACGIH TLV:S,25 PPM/40STEL;9394

Ingred Name:ETHYL SILICA

TE
CAS:68412-37-3
Fraction by Wt: 5%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:100 PPM
ACGIH TLV:10 PPM; 9394

Ingred Name:POLY(BUTYLTITANATE)
CAS:9022-96-2
Fraction by Wt: 1%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:100 PPM
ACGIH TLV:S: 50 PPM CEILING

Ingred Name:VOC = 6.5 LBS/GL 780 G/L
RTECS #:9999999VO
Fraction by Wt: NA
Other REC Limits:NONE RECOMMENDED
OSHA PEL:NA
ACGIH TLV:NA

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:Y
ES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: IRRITATION AND ANESTHESIA.
CHRONIC: NONE.
Explanation of Carcinogenicity:EXPLANATION: NO.
Effects of Overexposure:IRRITATION OF EYES, SKIN AND UPPER RESPIRATORY
TRACT.
Medical Cond Aggravated by Exposure:EYE, SKIN AND RESPIRATORY DISORDERS
MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT.

=====
===== First Aid Measures =====

First Aid:EYES-FLUSH
H WITH WATER FOR 15 MINUTES. SKIN- WASH WITH SOAP
AND WATER. INHALATION-REMOVE TO FRESH AIR. GIVE OXYGEN IF BREATHING
DIFFICULT. INGESTION-WASH OUT MOUTH WITH WATER. CALL A PHYSICIAN.

=====
===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:103F,39C
Lower Limits:1
Upper Limits:5.5
Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL POWDER, ALCOHOL FOAM.
Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND
PROTECTIVE CLOTHI

NG TO PREVENT CONTACT WITH SKIN AND EYES.

Unusual Fire/Explosion Hazard:VAPOR MAY TRAVEL CONSIDERABLE DISTANCE TO IGNITION SOURCE AND FLASH BACK.

===== Accidental Release Measures =====

Spill Release Procedures:TAKE UP WITH ABSORBENT MATERIAL. STORE IN APPROPRIATE CONTAINER. AVOID PROLONGED INHALATION OF VAPOR OR CONTACT WITH LIQUID. WASH RESIDUE WITH LARGE AMOUNTS OF WATER.
Neutralizing Agent:WATER.

===== Handling and Storage =====
=====

Handling and Storage Precautions:AVOID IGNITION SOURCES: FLAME, SPARKS, EXTREME HEAT. KEEP CONTAINER TIGHTLY CLOSED.

Other Precautions:CONTAINS 1 (N-BUTYL ACETATE=1)

Solubility in Water:98%

Appearance and Odor:COLORLESS LIQUID. PLESANT, SWEET ODOR.

Percent Volatiles by Volume:96

Corrosion Rate:NIF

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
ACID CHLORIDES AND OXIDIZING AGENTS.

Stability Condition to Avoid:OPE
N FLAMES, SPARKS AND EXTREME HEAT.

Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE, SILICA AND TITANIA FROM COMBUSTION.

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.