View NSN Online: https://aerobasegroup.gr/nsn/6750-01-354-7466

EASTMAN KODAK COMPANY -- 173 3013 RAPID FIXER, WORKING SOLUTION (PAPER)

6750-01-354-7466

Product ID:173 3013 RAPID FIXER, WORKING SOLUTION (PAPER)

MSDS Date:11/08/1995

FSC:6750

NIIN:01-354-7466

Kit Part:Y

MSDS Number: BZPMT === Responsible Party ===

Company Name: EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY ZIP:14650 Country:US Info Ph

one Num:716-477-3194 MSDS:800-242-2424

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name: BADGER GRAPHIC SALES INC

Address:1225 DELANGLADE ST

Box:46

City:KAUKAUNA

State:WI

ZIP:54130-0046

Country:US

Phone:414-766-9332

CAGE:0E4P0

Company Name: EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

Company Name: EASTMAN KODAK CO US CUSTOMER SERVICE/G

OVERNMENT SALES Address:800 LEE RD Box:City:ROCHESTER

State:NY

ZIP:14650-3129 Country:US

Phone:800-828-6203

CAGE:5K871

======= Composition/Information on Ingredients ========

Ingred Name:WATER

CAS:7732-18-5

RTECS #:ZC0110000 Fraction by Wt: 90-95% %

Other REC Limits: NONE RECOMMENDED

Ingred Name: AMMONIUM THIOSULFATE

CAS:7783-18-8

RTECS #:XN6465000 Fraction by Wt: 5-10% %

Other REC Limits: NONE RECOMMENDED

Ingred Name: SODIUM ACETATE

CAS:127-09-3

RTECS #:AJ4300010 Fraction by Wt: 1-

5% %

Other REC Limits: NONE RECOMMENDED

Ingred Name:BORIC ACID

CAS:10043-35-3 RTECS #:ED4550000 Fraction by Wt: < 1%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:10 MG BORATES/M3 ACGIH TLV:5 MG BORATES/M3

Ingred Name: AMMONIUM SULFITE (SARA III)

CAS:10196-04-0 Fraction by Wt: < 1%

Other REC Limits: NONE RECOMMENDED

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name: ACETIC ACID (SARA III)


CAS:64-19-7

RTECS #:AF1225000 Fraction by Wt: < 1%

Other REC Limits: NONE RECOMMENDED

**OSHA PEL:10 PPM** 

**ACGIH T** 



========= Hazards Identification ==============

LD50 LC50 Mixture: NOT GIVEN FOR WORKING SOLUTION

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EXPECTED TO BE A LOW INHALATION HAZARD FOR RECOMMENDED HANDLING. MAY CAUSE TRANSIENT EYE IRRITATION. LOW SKIN CONTACT HAZARD FOR RECOMMENDED HANDLING. EXPECTED TO BE A LOW

INGESTION HAZARD.

Explanation of Carcinogenicity:THIS COMPOUND CONTAINS NO INGREDIENTS AT CONCENTRATIONS OF 0.1% OR GREATER THAT ARE CARCINOGENS OR SUSPECT CARCINOGENS.

Effects of Overexposure: EYE IRRITATION.

Medical Cond Aggravated by Exposure: NONE SPECIFIED BY MANUFACTURER.

First Aid:INHALATION: IF SYMPTOMATIC, MOVE TO FRESH AIR. GET MEDICAL ATTENTION IF SYMPTOMS PERSIST. EYES: WASH OUT IMEEDIATELY WIT H

WATER. GET MEDICAL ATTENTION IF SYMPTOMS OCCUR. SKIN: WASH WITH SOAP AND WATER. GET MEDICAL ATTENTION IF SYMPTOMS OCCUR. INGESTION: DRINK 1-2 GLASSES OF WATER. SEEK MEDICAL ATTENTION. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

============ Fire Fighting Measures =========================

Flash Point:NONFLAMMABLE Lower Limits:NOT GIVEN Upper Limits:NOT GIVEN

Extinguishing Media: USE APPROPRIATE AGENT FOR ADJACENT FIRE.

Fire Fighting Procedures:WEAR SELF-CONT

AINED BREATHING APPARATUS AND

PROTECTIVE CLOTHING.

Unusual Fire/Explosion Hazard:FIRE OR EXCESSIVE HEAT MAY PRODUCE HAZARDOUS DECOMPOSTION PRODUCTS.

======== Accidental Release Measures ===========

Spill Release Procedures:MAY REQUIRE NEUTRALIZATION. FLUSH TO SEWER IF ALLOWABLE WITH LARGE AMOUNTS OF WATER. OTHERWISE, ABSORB SPILL WITH VERMICULITE OR OTHER INERT MATERIAL, THEN PLACE IN A CONTAINER FOR CHEMICAL WASTE. CLE AN SURFACE TO REMOVE RESIDUAL CONTA

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.
============ Handling and Storage ==============
Handling and Storage Precautions:USE WITH ADEQUATE VENTILATION. WASH THOROUGHLY AFTER HANDLING. KEEP FROM CONTACT WITH OXIDIZING MATERIALS. KEEP CONTAINER TIGHTLY CLOSED.  Other Precautions:KEEP AWAY FROM INCOMPATIBLE MATERIALS.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:NONE SHOULD BE NEEDED.  Ventilation:GOOD  GENERAL VENTILATION, TYPICALLY 10 AIR CHANGES PER HOUR, SHOULD BE USED. RATES SHOULD MATCH CONDITIONS.  Protective Gloves:IMPERVIOUS Eye Protection:SAFETY GLASSES W/SIDE SHIELDS OR GOGGLES  Other Protective Equipment:CHEMICAL RESISTANT CLOTHING AS NECESSARY TO PREVENT SKIN CONTACT. AN EMERGENCY EYEWASH AND SHOWER SHOULD BE AVAILABLE.  Work Hygienic Practices:WASH HANDS THOROUGHLY WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING OR USING TOILET FACILITIES.  Supplemental Safety and Health REMOVE AND WASH CONTAMINATED CLOTHING BEFORE REUSE.
======================================
HCC:C3 Boiling Pt:B.P. Text:>212F,>100C Melt/Freeze Pt:M.P/F.P Text:NOT GIVEN Vapor Pres:18 Vapor Density:0.6 Spec Gravity:1.04 pH:4.4 Evaporation Rate & Description of the Company of th
========= Stability and Reactivity Data =======

======

Stability Indicator/Materials to Avoid:YES

BASES, SODIUM HYPOCHLORITE (BLEACH), STRONG OXIDIZING AGENTS, STRONG ACIDS.

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER. Hazardous Decomposition Products:AMMONIA, NITROGEN OXIDES, SULFUR DIOXIDE, CHLORAMINE.

======= Disposal Considerations ============

Waste Disposal Methods:DISCHARGE, TREATMENT OR DISPOSAL MAY BE SUBJECT TO NATIONAL, STATE OR LOCAL LAWS. MAY REQUIRE NEUTRALIZATION IF PH

2.0 OR PH > 12.5. DISPOSE OF IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND L OCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.