

FARWEST PAINT MFG CO -- OIL EXTERIOR GLOSS, 13613 IVORY CREAM -- 8010-00-290-4054  
===== Product Identification =====

Product ID:OIL EXTERIOR GLOSS, 13613 IVORY CREAM

MSDS Date:11/01/1991

FSC:8010

NIIN:00-290-4054

MSDS Number: BZQWJ

=== Responsible Party ===

Company Name:FARWEST PAINT MFG CO

Address:4522 SOUTH 133RD ST

City:TUKWILA

State:WA

ZIP:98168

Country:US

Info Phone Num:206-244-8844

Emergency

Phone Num:206-941-1619

CAGE:6F266

=== Contractor Identification ===

Company Name:FARWEST PAINT MANUFACTURING CO

Address:4522 SOUTH 133RD ST

Box:City:TUKWILA

State:WA

ZIP:98168

Country:US

Phone:206-244-8844

CAGE:6F266

===== Composition/Information on Ingredients =====

Ingred Name:LIGROINE; (MINERAL SPIRITS)

CAS:8032-32-4

RTECS #:OI6180000

Fraction by Wt: 9.48%

OSHA PEL:300 PPM

ACGIH TLV:300 PPM

Ingred Name:STODDARD SOLVENT; (MINERAL SPIRITS (STODDARD))

CAS:8052-41-3

RTECS #:

WJ8925000  
Fraction by Wt: 15.80%  
OSHA PEL:500 PPM  
ACGIH TLV:100 PPM

Ingred Name:XYLENE (SARA 313) (CERCLA)  
CAS:1330-20-7  
RTECS #:ZE2100000  
Fraction by Wt: 0.83%  
OSHA PEL:100 PPM  
ACGIH TLV:100 PPM/150STEL  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:VOLATILE ORGANIC CONTENT: 250 G/L  
RTECS #:9999999VO  
OSHA PEL:N/K  
ACGIH TLV:N/K

=====  
===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.  
Routes of Entry: Inhalation:YES Skin:  
YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:ACUTE: SKIN: MAY CAUSE IRRITATION,  
SENSITIZATION, OR DEFATTING OF SKIN UPON PROLONGED OR REPEATED  
CONTACT. INHALATION: EXCESSIVE EXPOSURE TO VAPORS OR SPRAY MISTS  
CAN RESULT IN HEADACHE, DIZZINESS, NA USEA AND LOSS OF  
CONSCIOUSNESS. EYES: MAY CAUSE IRRITATION. CHRONIC: SOME REPORTS  
HAVE ASSOCIATED (EFTS OF OVEREXPOSURE)  
Explanation of Carcinogenicity:NOT RELEVANT.  
Effects  
of Overexposure:HLTH HAZ: REPEATED AND PROLONGED OCCUPATIONAL  
OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM  
DAMAGE.  
Medical Cond Aggravated by Exposure:NONE, WHEN USED IN ACCORDANCE WITH  
SAFE HANDLING INSTRUCTIONS.

=====  
===== First Aid Measures =====

First Aid:SKIN: PROMPTLY WASH W/SOAP & WATER. REMOVE & WASH ANY CONTAM  
CLTHG BEFORE REUSE. EYES: FLUSH W/LGE QTYS OF WATER FOR AT LEAST 15  
MIN & SEEK MED ATTN. INGEST: DO NOT

INDUCE VOMIT. KEEP PERS WARM,  
QUIET , & GET MED ATTN. ASPIR OF MATL INTO LUNGS CAN CAUSE CHEM  
PNEUMIT WHICH CAN BE FATAL. INHAL: REMOVE TO FRESH AIR IMMED. IF  
RESP SYMP DEVELOP, SEEK MED ATTN AT ONCE.

===== Fire Fighting Measures =====

Flash Point Method:TCC  
Flash Point:100F,38C  
Lower Limits:1.0%  
Upper Limits:7.0%  
Extinguishing Media:USE FOAM, DRY CHEMICAL, CARBON DIOXIDE, WATER FOG,  
OR ANY CLASS B EXTINGUISHING AGENT.  
Fire Fighting Procedures:  
WEAR NIOSH/MSHA APPROVED SCBA & FULL  
PROTECTIVE EQUIPMENT . WATER MAY BE UNSUITABLE AS EXTINGUISHING  
MEDIUM, BUT HELPFUL IN KEEPING ADJACENT CONTRS COOL.  
Unusual Fire/Explosion Hazard:VAPORS MAY FORM AN EXPLOSIVE MIXTURE IN  
AIR AND MAY BE IGNITED BY SPARKS, PILOT LIGHTS, ETC. CLOSED  
CONTAINERS MAY RUPTURE WHEN EXPOSED TO EXTREME HEAT.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNIT. VENT AREA. ABSORB  
S  
PILL W/ABSORB MATL SUCH AS SAWDUST, VERMICULITE/SAND & PLACE INTO  
CLSD CONTR. IF LGE SPILL, DIKE AREA TO PVNT THIS MATL FROM ENTERING  
WATER SYS/SEWERS. WEAR PROT EQUIP DURING CLEANUP.  
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID PROLONGED OR REPEATED INHALATION  
OF HEATED VAPORS OR SPRAY MISTS. KEEP AWAY FROM HEAT OR OPEN FLAME.  
THIS MATERIAL MAY CAUSE SENSITIZATION.  
  
Other Precautions:DO NOT GET IN EYES, ON SKIN OR CLOTHING. DO NOT ALLOW  
CONTAMINATED CLOTHING TO CONTACT SKIN. DO NOT WELD ON FULL OR EMPTY  
CONTAINERS. KEEP CONTAINERS CLOSED WHEN NOT IN USE, AND PROPERLY  
LABELED.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:A NIOSH/MSHA APPROVED CANISTER-TYPE RESPIRATOR  
MUST BE WORN TO PREVENT THE INHALATION OF VAPORS OR SPRAY MISTS  
WHEN THE TLV OR PEL IS EXCEEDED.  
Ventilation:GEN VENT IS REQU

REQUIRED DURING NORM USE. LOC VENT MAY BE  
REQUIRED DURING CERTAIN OPERATIONS TO KEEP EXPOS LEVEL < LIMITS.  
Protective Gloves:NITRILE, NEOPRENE OR RUBBER.  
Eye Protection:ANSI APPRVD CHEM WORKERS GOGGS .  
Other Protective Equipment:WEAR PROTECTIVE CLOTHING TO PREVENT SKIN  
CONTACT. EMERGENCY EYEWASH & DELUGE SHOWER MEETING ANSI DESIGN  
CRITERIA .  
Work Hygienic Practices:WASH HANDS BEFORE EATING OR SMOKING.  
Supplemental Safety and Health  
WASTE DISP METH: STDS. DISP I/A/W LOC, STATE & FED AGENC  
IES. GROUND  
HNDLG EQUIP TO PVNT SPARKS. FOR FURTHER INFO CONT YOUR STATE/LOC  
WASTE AGENCY/UNITED STATES ENVIRON PROTECTION AGENCY'S RCRA HOTLINE  
(1-800-424-9346/1-202-382-3000).

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:>281F,>138C  
Vapor Pres:9.5  
Vapor Density:HVR/AIR  
Evaporation Rate & Reference:FASTER THAN ETHER  
Solubility in Water:NIL  
Appearance and Odor:WHITE LIQUID, WITH MILD ODOR, OR COLOR OF TINT  
Percent Volatiles by Volum  
e:43.89

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
AVOID CONTACT WITH STRONG OXIDANTS, ACIDS, BASES AND EPOXY HARDENERS  
UNDER UNCONTROLLED CONDITIONS.  
Stability Condition to Avoid:HEAT, SPARKS AND OPEN FLAMES. IF PRODUCT  
CONTAINS ALUMINUM, MOISTURE IN CLOSED CONTAINERS WILL GENERATE  
HYDROGEN GAS.  
Hazardous Decomposition Products:INCOMPLETE COMBUSTION CAN YIELD CABON  
MONOXIDE AND TOXIC VAPORS.

=====

=== Disposal Considerations =====

Waste Disposal Methods:IF DISCARDED, THIS MATL & CONTRS SHOULD BE  
TREATED AS HAZ WASTE BASED ON CHARACT OF IGNITABILITY AS DEFINED  
UNDER FED RCRA REGS (40 CFR 261). DISP OF THIS MATL/ITS CONTR  
REQUIRES COMPLIANCE W/APPLIC L ABELING, PACKAGING, & RECORDKEEPING  
(SUP DAT)

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The U

nited States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.