View NSN Online: https://aerobasegroup.gr/nsn/7930-01-097-0808

DIVERSEY CORP. -- LIQUA SAFE -- 7930-01-097-0808

Product ID:LIQUA SAFE MSDS Date:12/08/1993

FSC:7930

NIIN:01-097-0808

MSDS Number: BZSWS === Responsible Party ===

Company Name: DIVERSEY CORP. Address: 12025 TECH CENTER DR.

City:LIVONIA State:MI ZIP:48150 Country:US

Info Phone Num:313-458-5000

Emergency Phone Num:800-424-9300 (CHEMTREC)

Preparer's Name: REGULATORY

CA

GE:EO268

=== Contractor Identification ===
Company Name:DIVERSEY CORP
Address:12025 TECH CENTER DRIVE

Box:City:LIVONIA

State:MI

ZIP:48150-5000

Country:US

Phone:313-450-5000

CAGE:73042

Company Name:DIVERSEY CORP. Address:12025 TECH CENTER DRIVE

City:LIVONIA State:MI ZIP:48150 Country:US

Phone:313-458-5000

CAGE:EO268

======= Composition/Information on Ingredients ========

Ingred Name:POTASSIUM METASILICATE

CAS:10006-28-7 Fraction by Wt: 3.0%

Other REC Limits: NONE RECOMMENDED

EPA Rpt

Qty:100 LBS DOT Rpt Qty:100 LBS
======================================
Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:NAUSEA. CORROSIVE TO SKIN & EYES. MISTS ARE CORROSIVE TO SKIN, EYES, RESPIRATORY TRACT. Medical Cond Aggravated by Exposure:SENSITIVE SKIN & EYES. IMPAIRED PULMINARY FUNCTIONING.
======================================
First Aid:EYES: FLUSH THOROUGHLY W/FRESH WATER AT LEAST 15 MINUTES. GET MEDICAL AID. SKIN: FLUSH W/FRESH WATER. WASH W/SOAP & WATER. REMOVE CONTAMINATED CLOTHING/SHOES. INGESTION: GIVE WATER. DO NOT INDUCE VOMI TING. GET MEDICAL AID.
============= Fire Fighting Measures ==============
Flash Point:NA Lower Limits:NONE Upper Limits:NONE Extinguishing Media:WATER, WATER FOG, DRY CHEMICAL. Fire Fighting Procedures:WEAR PROTECTIVE GEAR & SCBA IN FIRE AREA. Unusual F ire/Explosion Hazard:NONE
======== Accidental Release Measures ==========
Spill Release Procedures:FLUSH SMALL AMOUNTS TO DRAIN. COLLECT & RETURN LARGE AMOUNTS TO CONTAINER. CERCLA REQUIREMENT - SODIUM HYPOCHLORITE = 4000 LBS/370 GL.
======================================
Handling and Storage Precautions:DO NOT PRESSURE CONTAINER TO EMPTY. IF FROZEN, THAW & MIX TO MAKE USEABLE. KEEP CONTAINER CLOSED.
====== Exposure Contro

Is/Personal Protection =======
Respiratory Protection:WEAR NIOSH APPROVED RESPIRATOR IF TLV OR PEL EXPOSURE LIMITS EXCEEDED. Ventilation:LOCAL VENTILATION. Protective Gloves:ALKALI RESISTANT Eye Protection:FACE SHIELD OR GOGGLES Other Protective Equipment:NONE Supplemental Safety and Health NK
======== Physical/Chemical Properties =========
Boiling Pt:B.P. Text:215F,102C Vapor Pres:17.5 Vapor Density:NA Spec Gravity:1.30 Evaporation Rate & Description Rate & Descrip
======================================
Stability Indicator/Materials to Avoid:YES MINERAL ACIDS; RELEASE CHLORINE. Hazardous Decomposition Products:CL2

======= Disposal Considerations ==========

Waste Disposal Methods:USE UNTIL