

CRAWFORD LABORATORIES, INC. -- MIL-C-22750, 24084 GREEN, PART A, M4-038 --
8010-01-419-1148

===== Product Identification =====

Product ID:MIL-C-22750, 24084 GREEN, PART A, M4-038

MSDS Date:03/07/1996

FSC:8010

NIIN:01-419-1148

Kit Part:Y

MSDS Number: CBVJQ

=== Responsible Party ===

Company Name:CRAWFORD LABORATORIES, INC.

Address:4165 SOUTH EMERALD AVENUE

City:CHICAGO

State:IL

ZIP:60609

Country:US

Info Phone Num:312-376-7132

Emergency Phone Num:800-424-9300

Preparer's Name:DAVID SCHMETTERER

CAGE:DO165

=== Contractor Identification ===

Company Name:CRAWFORD LABORATIES, INC

Address:4165 SOUTH EMERALD AVENUE

City:CHICAGO

State:IL

ZIP:60609

Phone:800-424-9300 CHEMTREC

CAGE:DO165

Company Name:CRAWFORD LABORATORIES, INC

Address:4165 SOUTH EMERALD AVENUE

Box:City:CHICAGO

State:IL

ZIP:60609

Country:US

Phone:312-376-7132

CAGE:5V430

===== Composition/Information on Ingredients =====

===

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III) (VP = 71.2 MMHG)

CAS:78-93-3

RTECS #:EL6475000

Fraction by Wt: 14.0%

OSHA PEL:200 PPM/300 STEL

ACGIH TLV:200 PPM/300STEL 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 3.4%

OSHA PEL:100 PPM

ACGIH TLV:100 PPM

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:EPOXY RESIN

CAS:25085-99-8

Fraction by Wt: 21.0%

Other REC Limits:NONE RECOMMENDED

Ing

red Name:NAPHTHA, LIGHT AROMATIC (VP = 9.0 MMHG)

CAS:64742-95-6

Fraction by Wt: 1.7%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:50 PPM

ACGIH TLV:50 PPM 9091

Ingred Name:SILICA, CRYSTALLINE - QUARTZ (MAY BE RELEASED BY SANDING DRIED PAINT FILM)

CAS:14808-60-7

RTECS #:VV7330000

Fraction by Wt: 19.0%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:NOT EST.

ACGIH TLV:0.1 MG/M3 RDUST;9495

Ingred Name:ALIPHATIC GLYCIDYL ETHER (DILUENT 8)

CAS:68609-97-2

Fraction by Wt: 2.2%

Other REC Limits:NONE RECOM

MENDED

Ingred Name:SILICONE DIOXIDE (DIATOMACEOUS EARTH)

CAS:68855-54-9

RTECS #:HL8600000

Fraction by Wt: 8.6%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:10 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:YES OSHA:NO

Health Hazards Acute and Chronic:REPEATED/PROLONGED OCCUPATIONAL

OVEREXPOSURE TO SOLVENTS ASSOCIATED W/PERMANENT BRAIN
/NERVOUS

SYSTEM DAMAGE. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND
INHALING THE CONTENTS MAY BE HARMFUL OR FATAL. PROLONGED
OVEREXPOSURE (INHAL)MAY CAUSE DELAYED LUNG DISEASE.

Explanation of Carcinogenicity:FROM INITIAL LIMITED TESTS/STUDIES IARC
CONCLUDES IS LIMITED EVIDANCE OF CARCINOGENICITY FROM CRYSTALLINE
SILICA.

Effects of Overexposure:OVEREXPOSURE MAY PRODUCE VARIOUS EFFECTS. ACUTE
TOXICITY (HEADACHE, DIZZINESS, NAUSEA, LOSS CONSCIOUSNESS. SEVERE
EYE

IRRITATION POSSIBLY RESULTING PERMANENT DAMAGE. IRRITATED
MUCOUS MEMBRANES. VOMITING FROM INGESTION. SKIN DEFATTING/DRYING.
SENSITIZATION AFTER REPEATED CONTACT.

=====
===== First Aid Measures =====

First Aid:EYE: FLUSH W/PLENTY CLEAN H2O 15 MIN, LIFTING LIDS, GET MED

ATTN. INHAL: GET FRESH AIR, PROVIDE OXYGEN IF BREATH DIFFICULT.

GIVE ARTIF RESP IF NOT BREATHING. GET MED ATTN. KEEP VICTIM

WARM/QUIET. NEVER GIVE UNCONS PERSON LIQ. INGEST:

CALL DR. IMMED.

DON'T INDUCE VOMIT. IF VOMIT SPONTANEOUSLY, KEEP HEAD BELOW HIPS.

SKIN: FLUSH W/H2O WHILE REMOVING CONTAM CLOTHES/SHOES. IF IRRIT

PERSIST, GET MED AID

=====
===== Fire Fighting Measures =====

Flash Point Method:SCC

Flash Point:22.0F,-5.6C

Lower Limits:1.4

Extinguishing Media:FOAM, CO2, OR DRY CHEMICAL

Fire Fighting Procedures:WATER MAY BE USED TO KEEP EXPOSED CONTAINERS

COOL & KEEP FLAMMABLE STRUCTURE WETDON'T ENTER FIRE AREA WITHOUT

PROPER PROTECTION, HAZARDOUS DECOMP MAY BE PRESENT
Unusual Fire/Explosion Hazard:WATER PRESSURE MAY SPREAD A FLAMMABLE
LIQUID FIRE. SEALED CONTAINERS MAY EXPLODE IF OVER HEATED.

===== Accidental Release Measures =====

Spill Release Procedures:WARNING - FLAMMABLE. ELIMINATE ALL IGNITION
SOURCES. HANDLING EQUIPMENT MUST BE GROUNDED TO PREVENT SPARKING.
SOAK UP WITH ABSORBENT & PLACE IN NON-LEAKING CONATINERS. SEAL
TIGHTLY FOR PROPER DISPOSAL .

===

===== Handling and Storage =====

Handling and Storage Precautions:TREAT AS A HAZARDOUS-FLAMMABLE
MATERIAL. KNOW APPLICABLE D.O.T. REG. BEFORE ATTEMPTING TO
TRANSPORT THIS MATERIAL.

Other Precautions:WARNING: HOT ORGANIC CHEMICAL VAPORS OR MISTS ARE
SUSCEPTIBLE TO SUDDEN SPONTANEOUS COMBUSTION WHEN MIXED W/AIR.
IGNITION MAY OCCUR @ TEMPS BELOW THOSE PUBLISHED AS
AUTOIGNITION/IGNITION TEMPS. IGNITI ON TEMPS DECREASE W/INCREASING
VAPOR*

====

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IMPORTANT-MUST PROVIDE ADEQUATE VENT TO MAINTAIN
VAPOR CONCENTRATE BELOW ESTAB- LISHED TLV LIMIT AS GIVEN BY OSHA.
IN MORE CONFINED AREAS A NIOSH/MSHA APPROVED RESPIRATOR EQUIPPED
WITH ORGANIC VAPOR C ARTRIDGE SHOULD BE WORN.

Ventilation:MUST PROVIDE ADEQUATE VENTILATION, SEE PARAGRAPH ABOVE.

Protective Gloves:USE RUBBER GLOVES

Eye Protection:APPROVED SAFETY GOGGLES &/OR FACE SHIELD

Other Protecti

ve Equipment:HAVE EYE BATH & SAFETY SHOWER AVAILABLE.

Supplemental Safety and Health

*VOLUME & VAPOR/AIR CONTACT TIME AND ARE INFLUENCED BY PRESSURE
CHANGES. IGNITION MAY OCCUR AT TYPICAL ELEVATED TEMPERATURE PROCESS
CONDITIONS, ESPECIALLY IN PROCESS OPERATING UNDER VACUUM IF
SUBJECTE D TO SUDDEN INGRESS OF AIR, OUTSIDE PROCESS EQUIPMENT
OPERATING UNDER ELEVATED PRESSURE IF SUDDEN ESCAPE OF VAPORS/MIST.

===== Physical/Chemical Properties =====

Boilin

g Pt:B.P. Text:175 TO 344F

Vapor Density:>AIR

Spec Gravity:1.34

pH:NA

Viscosity:85 KU

Evaporation Rate & Reference:3.87 X N-BUTYL ACETATE

Solubility in Water:SLIGHT

Appearance and Odor:GREEN LIQUID, SOLVENT ODOR

Percent Volatiles by Volume:34.5

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

OXIDIZING AGENTS & STRONG ALKALIES. NOT CORROSIVE TO METAL.

Stability Condition to Avoid:HEAT, SPARKS, OPEN FLAMES, STRONG

ALKALIES, &

OXIDIZING AGENTS.

Hazardous Decomposition Products:INCOMPLETE COMBUSTION OR PRODUCTS LIKE

THIS MAY GENERATE HIGHLY POISONOUS CARBON MONOXIDE AND OTHER TOXIC GASES

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSAL MUST BE IN ACCORDANCE WITH CURRENT

LOCAL, STATE & FEDERAL REG. CONTACT AN APPROVED DISPOSAL FACILITY

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements

of the Department

of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.