

HERNON MFG INC -- NUTS N' BOLTS 423 (ANEROBIC) -- 8030-01-014-5869

=====
Product Identification
=====

Product ID:NUTS N' BOLTS 423 (ANEROBIC)

MSDS Date:02/07/1996

FSC:8030

NIIN:01-014-5869

MSDS Number: CCCCY

=== Responsible Party ===

Company Name:HERNON MFG INC

Address:121 TECH DR

City:SANFORD (FORMALLY IN BROOKLYN, NY)

State:FL

ZIP:32771

Country:US

Info Phone Num:407-322-4000 407-321-9700(FAX)

E

mergency Phone Num:800-255-3924 407-322-4000

Preparer's Name:JOSEF ARNON

CAGE:61603

=== Contractor Identification ===

Company Name:HERNON MANUFACTURING

Address:121 TECH DRIVE

Box:City:SANFORD

State:FL

ZIP:32771

Country:US

Phone:407-322-4000/800-255-3924

CAGE:61603

=====
Composition/Information on Ingredients
=====

Ingred Name:POLYGLYCOL DIMETHACRYLATE

Fraction by Wt: 60-65%

Other REC Limits:NONE RECOMMENDED

Ingred Name:POLYGLYCOL OLEATE

Fraction by Wt: 25-30%

Other REC Limit

s:NONE RECOMMENDED

Ingred Name:SACCHARIN (SARA 313) (CERCLA)

CAS:81-07-2

RTECS #:DE4200000

Fraction by Wt: 3-5%

Other REC Limits:NONE RECOMMENDED

EPA Rpt Qty:100 LBS

DOT Rpt Qty:100 LBS

Ingred Name:CUMENE HYDROPEROXIDE

CAS:80-15-9

RTECS #:MX2450000

Fraction by Wt: 1-3%

Other REC Limits:NONE RECOMMENDED

EPA Rpt Qty:10 LBS

DOT Rpt Qty:10 LBS

Ingred Name:METHYL ALCOHOL (METHANOL) (SARA 313) (CERCLA)

CAS:67-56-1

RTECS #:PC1400000

Fraction by Wt: 1-3%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:S,

200 PPM

ACGIH TLV:S,200PPM/250STEL; 96

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:SILICA, AMORPHOUS, DIATOMACEOUS EARTH

CAS:61790-53-2

RTECS #:HL8600000

Fraction by Wt: 1-3%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:20 MPPCF; Z-3

ACGIH TLV:10 MG/M3 TDUST; 9596

Ingred Name:N,N-DIALKYL TOLUIDINES

Fraction by Wt: 0.1-1%

Other REC Limits:NONE RECOMMENDED

Ingred Name:TITANIUM DIOXIDE

CAS:13463-67-7

RTECS #:XR2275000

Fraction by Wt: 0.1-.50%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:15

MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9596

=====
===== Hazards Identification =====
=====

LD50 LC50 Mixture:ORAL LD50 (RAT) IS >5G/KG
Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO
Health Hazards Acute and Chronic:MAY CAUSE DERMATITIS IS SENSITIVE
INDIVIDUALS.
Explanation of Carcinogenicity:SACCHARIN IS LISTED IARC-2B AND NTP-AC.
Effects of Overexposure:DERMATITIS.
Medical Cond Aggravated by Exposure:PERS
ONS WITH PRE-EXISTING SKIN
CONDITIONS MAY BE AT INCREASED RISK FROM EXPOSURE.

=====
===== First Aid Measures =====
=====

First Aid:SKIN:REMOVE CONTAMINATED CLOTHING;WASH WITH SOAP AND
WATER.GET MEDICAL ATTENTION.EYES:FLUSH WITH WATER FOR 15
MINUTES.GET MEDICAL ATTENTION.INHAL:UNLIKELY ROUTE OF
EXPOSURE.INGEST:DO NOT INDUCE VOMITI NG.GET PROMPT QUALIFIED
MEDICAL ATTENTION.KEEP VICTIM CALM.

=====
===== Fire Fighting Measures =====
=====

Flash Point Method:TCC
Flash Point:>200F,>93C
Extinguishing Media:DRY CHEMICAL,CARBON DIOXIDE,FOAM.
Fire Fighting Procedures:USE A SELF-CONTAINED BREATHING APPARATUS AND
FULL PROTECTIVE EQUIPMENT.
Unusual Fire/Explosion Hazard:FIRE CONDITIONS MAY EVOLVE TOXIC FUMES.

=====
===== Accidental Release Measures =====
=====

Spill Release Procedures:SOAK UP WITH NON-COMBUSTIBLE INERT
ADSORBANT(EG.CLAY);PLACE COLLECTED MATERIAL IN AN APPROPRIATE
CONTAINER FOR DISP
OSAL;CLEAN SPILL AREA TO REMOVE SLIPPERINESS.
Neutralizing Agent:NOT APPLICABLE.

=====
===== Handling and Storage =====
=====

Handling and Storage Precautions:STORE BELOW 110F TO PRESERVE SHELF
LIFE.
Other Precautions:AVOID SKIN AND EYE CONTACT.

=====
===== Exposure Controls/Personal Protection =====
=====

Respiratory Protection:NOT NEEDED IN NORMAL SERVICE.
Ventilation:NO SPECIAL REQUIREMENTS.
Protective Gloves:RUBBER OR PLASTIC
Eye Protection:SAFETY GLASSES

OR GOGGLES.

Other Protective Equipment:PROVIDE A LOCAL EYE WASH STATION.

Work Hygienic Practices:USE REASONABLE CARE IN HANDLING THIS PRODUCT.WASH HANDS AFTER USE AND BEFORE EATING.

Supplemental Safety and Health

NONE

===== Physical/Chemical Properties =====

HCC:T6

Boiling Pt:>148.9C, 300.F

Vapor Pres: