

RUBATEX CORP -- R-373 RUBBER INSUL. ADHESIVE #373 -- 8040-00-841-9773

=====  
Product Identification  
=====

Product ID:R-373 RUBBER INSUL. ADHESIVE #373

MSDS Date:01/01/1995

FSC:8040

NIIN:00-841-9773

MSDS Number: CCJYC

=== Responsible Party ===

Company Name:RUBATEX CORP

Address:805 MONROE ST.

City:BEDFORD

State:VA

ZIP:24523

Country:US

Info Phone Num:703-586-2611

Emergency Phone Num:703-586-2611

Prep

arer's Name:CAROL N. BUSH

CAGE:IO124

=== Contractor Identification ===

Company Name:RUBATEX CORP

Box:UNKNOW

CAGE:79101

Company Name:RUBATEX CORP

Address:805 MONROE ST

Box:340

City:BEDFORD

State:VA

ZIP:24523

Country:US

Phone:800-378-4091

CAGE:IO124

Company Name:THE CLAREMONT COMPANY

Address:174 STATE STREET

Box:952

City:MERIDEN

State:CT

ZIP:06450

Country:US

Phone:800-222-4448 / 203-238-2384

CAGE:52307

=====  
Composition/Information on Ingredients  
=====

Ingred Name:TOLUENE (SAR

A 313) (CERCLA)(VP = 22.0)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 15.0%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:200 PPM

ACGIH TLV:100 PPM

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:HEXANE (N-HEXANE) (CERCLA)(SARA 313)(VP = 140)

CAS:110-54-3

RTECS #:MN9275000

Fraction by Wt: 28.0%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:50 PPM

ACGIH TLV:50 PPM

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:ACETONE (SARA 313) (CERCLA)(VP = 186)

CAS:67-64-1

RTECS #:AL3150000

Fraction by Wt

: 36.0%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:750 PPM

ACGIH TLV:750 PPM

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION: DIZZINESS, BREATHING

DIFFICULTY, HEADACHES, LOSS OF COORDINATION. EYE: SEVERE

IRRITATION, REDNESS, TEARING, BLURRED VISION. SKIN: CAN DRY/DEFAT

CAUSING CRACKS, IRRITATION, DERMATITIS. INGESTION: CAN CAUSE GI

IRRITATION, VOMITING, NAUSEA, DIARRHEA.

Effects of Overexposure:INHALATION: DIZZYNESS, BREATHING DIFFICULTY,

HEADACHES, AND LOSS OF COORDINATION. EYE: SEVERE IRRITATION,

TEARING, REDNESS, BLURRED VISION. SKIN: CAN DRY/DEFAT SKIN CAUSING

CRACKS, IRRITATION, DERMITITIS. INGESTION: CAN CAUSE

GASTROINTESTINAL IRRITATION, VOMITING, NAUSEA, DIARRHEA.

Medical Cond Aggravated by Exposure:ANESTHESIA, RESPIRATORY TRACT

IRRITATION, DERMATITIS, NAUSEA, VOMITING.

=====  
===== First Aid Measures =====

First Aid:INHALATION: MOVE TO FRESH AIR. IF BREATHING STOPS GIVE ARTIFICIAL RESPIRATION, GET MED AID IMMED. EYE: FLUSH W/LARGE AMOUNTS WATER 15 MINUTES. SKIN: WASH THOROUGHLY W/SOAP & WATER. GET MED AID. INGESTION: DO NOT INDUCE VOMITING. CAN CAUSE CHEMICAL PNEUMONITIS, EDEMA. CONTACT DR IMMEDIATELY.

=====  
===== Fire Fighting Measures =====

Flash Point Method:CC

Flash Point:-14F,-26C

Lower Limits:1.0

Upper Limits:NA

Extinguishing Media:FOAM, CO2, DRY CHEMICAL.

Fire Fighting Procedures:RESPIRATORY EQUIPMENT SHOULD BE WORN TO AVOID INHALATION OF CONCENTRATED VAPORS. WATER SHOULD NOT BE USED EXCEPT AS FOG TO KEEP NEARBY CONTAINERS COOL.

Unusual Fire/Explosion Hazard:HANDLE AS FLAM LIQ. VAPORS FORM EXPLOSIVE MIXTURES & AIR BETWEEN UPPER/LOWER EXPLOSIVE LIMITS, CAN BE IGNITED BY PILOT LIGHTS/FLAME/ELECTRICAL MOTOR S/SWITCHES.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:REMOVE IGNITION SOURCES. PROVIDE GOOD VENTILATION. DIKE SPILL AREA. USE ABSORBENT TO CLEAN UP.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:USE NONSPARKING TOOLS WHEN HANDLING. AVOID HOT METAL SURFACES. USE IN COOL WELL-VENTILATED AREAS. KEEP CONTAINERS CLOSED WHEN NOT IN USE.

Other Precautions:KEEP AWAY FROM EXCESSIVE HEAT & OPEN FLAMES. NO

SMOKING AROUND MATERIAL. TOOLS USED W/THIS MAT'L SHOULD BE MADE OF ALUMINUM, BRASS, COPPER. PLASTIC SHOULD NOT BE USED.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:WHEN SPRAYING ADHESIVE, USE NIOSH APPROVED CARTRIDGE RESPIRATOR OR GAS MASK SUITABLE TO KEEP AIRBORNE MISTS/CONCENTRATIONS BELOW THE TLV/TWA. WHEN USING IN POORLY VENTILATED AREA USE FRESH AIR SUPPLYING RESPIRATOR OR SCBA.

Ventilation:GENERAL ME

CHANICAL OR LOCAL EXHAUST SHOULD BE SUITABLE TO  
KEEP CONCENTRATIONS BELOW TLV. USE EXPLOSION PROOF EQUIPMENT.  
Protective Gloves:IMPERMEABLE CHEMICAL HANDLING GLOVES.  
Eye Protection:CHEM SAFETY GLASSES/GOGGLES/FACE SHIELD.  
Other Protective Equipment:USE IMPERMEABLE APRONS & PROTECTIVE CLOTHING  
WHENEVER POSSIBLE TO PREVENT SKIN CONTACT. USE OF HEAD CAPS  
STRONGLY REC.  
Work Hygienic Practices:EYEWASHES/SAFETY SHOWERS IN WORK PLACES  
RECOMMENDED.  
Supplemental Safety and Health  
NK

=====

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:132 TO 231F  
Vapor Density:>AIR  
Spec Gravity:0.8  
Evaporation Rate & Reference:SLOWER THAN ETHER  
Solubility in Water:NO  
Appearance and Odor:BLUE, OFFENSIVE ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
ALKALINE MATERIALS, STRONG ACIDS, OXIDIZING MATERIALS.  
Stability Condition to Avoid:EXCESSIVE HEAT, POOR VENTILATION,  
CORROSIVE ATMOS  
PHERE, EXCESSIVE AGING.  
Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE,  
OXIDES OF NITROGEN, POSSIBLE ACROLEIN.

===== Disposal Considerations =====

Waste Disposal Methods:COLLECT ABSORBENT/SPILLED LIQ MIXTURE, PLACE  
INTO METAL CONTAINERS. CONSULT LOCAL, STATE, FEDERAL HAZARDOUS  
WASTE REGS BEFORE DISPOSING INTO APPROVED HAZARDOUS WASTE LANDFILL.  
OBEY RELEVANT LAWS.

Disclaimer (provided with this information by the compiling agen

cies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.