

A J P SCIENTIFIC INC -- TRICHROME STAIN -- 6550-01-211-4779

===== Product Identification =====

Product ID:TRICHROME STAIN

MSDS Date:01/02/1996

FSC:6550

NIIN:01-211-4779

MSDS Number: CCLYK

=== Responsible Party ===

Company Name:A J P SCIENTIFIC INC

Address:82 INDUSTRIAL EAST

Box:1589

City:CLIFTON

State:NJ

ZIP:07015

Country:US

Info Phone Num:201-472-7200

Emergency Phone Num:201-472-7200

CAGE:55930

=

== Contractor Identification ==

Company Name:ENG SCIENTIFIC INC (FORMERLY A J P SCIENTIFIC INC)

Address:82 INDUSTRIAL EAST

Box:1589

City:CLIFTON

State:NJ

ZIP:07015

Country:US

Phone:973-472-7200; 201-472-7200

CAGE:55930

===== Composition/Information on Ingredients =====

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA 313) (CERCLA)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 100%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM

ACGIH TLV:100 PPM/150STEL;9596

EPA Rpt Qty:100

0 LBS
DOT Rpt Qty:1000 LBS

===== Hazards Identification =====

LD50 LC50 Mixture:100 PPMM (435 MG/M3) FOR 8-HR WORKDAY
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:PROLONGED OR REPEATED LIQUID CONTACT
WILL DRY AND DEFAT THE SKIN LEADING TO IRRITATION AND DERMATITIS.
Explanation of Carcinogenicity:NOT CARCINOGENIC.
Effects of Overexposure:AVOID BREATHING VAPOR.
INHALATION OF HIGH VAPOR
CONCENTRATIONS MAY HAVE RESULTS RANGING FROM DIZZINESS AND
HEADACHES TO UNCONSCIOUSNESS.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:IF IVERCOME BY VAPOR, REMOVE FROM EXPOSURE IMMEDIATELT; CALL
A PHYSICIAN. IF BREATHING IS IRREGULAR OR STOPPED, START
RESUSCITATION, ADMINISTER OXYGEN. IF SWALLOWED, DO NOT INDUCE
VOMITING; CALL A PHY SICIAN. REMOVE C
ONTAMINATED CLOTHING AND WASH
SKIN WITH SOAP AND WATER. FLUSH EYES WITH WATER UNTIL IRRITATION
SUBSIDES.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:80.0F,26.7C
Autoignition Temp:Autoignition Temp Text:930F
Extinguishing Media:FOAM, CARBON DIOXIDE, DRY CHEMICAL, WATER SPRAY
(FOG).
Fire Fighting Procedures:USE AIR SUPPLIED RESCUE EQUIPMENT FOR ENCLOSED
AREAS. COOL EXPOSED CONTAINERS WITH WATER.
Unusual Fire/Explosion Ha
zard:COMBUSTIBLE LIQUID. DO NOT STORE OR MIX
WITH STRONG OXIDANTS.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL IGNITION SOURCES. KEEP PEOPLE AWAY.
RECOVER FREE LIQUID. ADD ABSORBENT TO SPILL AREA. AVOID BREATHING
VAPORS. VENTILATE ENCLOSED SPACES. OPEN ALL WINDOWS AND DOORS. KEEP
PETROLEUM PRODUCTS O UT OF SEWERS, STREAMS AND WATERWAYS.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling

and Storage =====

Handling and Storage Precautions:AVOID BREATHING VAPORS. AVOID CONTACT WITH SKIN, PROLONGED OR REPEATED. WASH SKIN WITH SOAP AND WATER AFTER CONTACT.

Other Precautions:KEEP CONTAINERS CLOSED. KEEP AWAY FROM SPARKS AND OPEN FLAMES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:HYDROCARBON VAPOR CANISTER.

Ventilation:MECHANICAL-EXPLOSION PROOF VENTILATION EQUIPMENT. SPECIAL-USE ONLY WITH ADEQUATE VENTILATION.

Protective Gloves:CHEMICALLY RESISTANT GLOVES.

Eye Protection:NONE SPECIFIED BY MANUFACTURER.

Other Protective Equipment:HYDROCARBON-INSOLUBLE APRON IF NEEDED.

Work Hygienic Practices:WASH AFTER HANDLING.

Supplemental Safety and Health
COMBUSTIBLE LIQUID.

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:280F,138C

Vapor Pres:38

Vapor Density:3.7

Spec Gravity:15.6

Solubility in Water:NEGLIGIBLE

Appearance and Odor:WATER-WHITE COLOR. AROMATIC HYDROCARBON CHARACTERISTIC ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDANTS LIKE LIQUID CHLORINE AND CONCENTRATED OXYGEN.

Stability Condition to Avoid:AVOID OPEN FLAMES, HEAT.

Hazardous Decomposition Products:CARBON MONOXIDE IN THE CASE OF INCOMPLETE COMBUSTION.

===== Disposal Considerations =====

Waste Disposal Methods:SUPERVISED INCINERATION OR IN A CHEMICAL

DISPOSAL AREA IN COMPLIANCE WITH LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.