

FARWEST PAINT MFG CO -- FLOOR & TRIM VARNISH -- 8010-00-165-4420

=====
Product Identification
=====

Product ID:FLOOR & TRIM VARNISH

MSDS Date:12/26/1995

FSC:8010

NIIN:00-165-4420

MSDS Number: CCQRH

=== Responsible Party ===

Company Name:FARWEST PAINT MFG CO

Address:4522 S 133 ST

City:TUKWILA

State:WA

ZIP:98168

Country:US

Info Phone Num:206-244-8844

Emergency Phone Num:206-941-1619

Preparer's Name

:PAUL SHEEHAN

CAGE:6F266

=== Contractor Identification ===

Company Name:FARWEST PAINT MANUFACTURING CO

Address:4522 SOUTH 133RD ST

Box:City:TUKWILA

State:WA

ZIP:98168

Country:US

Phone:206-244-8844

CAGE:6F266

=====
Composition/Information on Ingredients
=====

Ingred Name:MINERAL SPIRITS #350

CAS:8032-32-4

RTECS #:OI6180000

Fraction by Wt: 18.0%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM

ACGIH TLV:100 PPM

Ingred Name:GLYCOL ETHER EP

CAS:2807-30-9

RTECS #:KM2800000

Frac

tion by Wt: 7.0%

Other REC Limits:NONE RECOMMENDED

Ingred Name:VM&P NAPHTHA, SOLVENT TYPE

CAS:64742-89-8

Fraction by Wt: 6.0%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:250 PPM

ACGIH TLV:250 PPM

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:SKIN: IRRITATION, SENSITIZATION,
DEFATTING. INHALATION: HEADACHE, DIZZINESS, NAUSEA,

UNCONSCIOUSNESS, PERMANENT BRAIN/NS DAMAGE. EYE: IRRITATION

=====
===== First Aid Measures =====

First Aid:SKIN: WASH W/SOAP & WATER. WASH CONTAMINATED CLOTHES BEFORE
REUSE. EYE: WASH W/LARGE AMOUNT WATER 15 MINUTES. GET MEDICAL AID.
INGESTION: DON'T INDUCE VOMITING. KEEP WARM/QUIET. GET MEDICAL AID.
ASPIR ATION MAY CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL.
INHALATION: GET FRESH AIR. IF SYMPTOMS DEVELOP GET MEDICAL AID AT
ONCE.

=====
===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:104F,40C

Lower Limits:1.0

Upper Limits:7.0

Extinguishing Media:FOAM,CHEM,WATER FOG,CO2.USE CLASS B EXTINGUISHING
AGENT.WATER UNSUITABLE EXTINGUISHING AGENT,USE TO COOL CONTAINERS.

Fire Fighting Procedures:FIREFIGHTERS & OTHERS EXPOSED TO VAPORS OR
PRODUCTS OF COMBUSTION SHOULD WEAR SCBA. EVACUATE AREA OF
UNPROTECTED PERSONNEL. WEAR PROTECTIVE CLOTHING.

Unusual Fire/Explosion Hazard:VAP

ORS MAY FORM AN EXPLOSIVE MIXTURE IN AIR AND MAY BE IGNITED BY SPARKS, PILOT LIGHT, ETC. CLOSED CONTAINERS MAY RUPTURE WHEN EXPOSED TO EXTREME HEAT.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE IGNIT SOURCES. VENTILATE. ABSORB W/ABSORBENT. PLACE IN CLOSED CONTAINER. DIKE LARGE SPILL TO PREVENT ENTRY INTO WATER SYSTEMS/SEWERS. USE PROTECTIVE EQUIPMENT.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID CHRONIC INHALATION. KEEP AWAY FROM HEAT/FLAME. DON'T GET IN EYES ON SKIN/CLOTHES. DON'T WELD ON FULL/EMPTY CONTAINER
Other Precautions:KEEP CONTAINER CLOSED WHEN NOT IN USE. KEEP CONTAINER PROPERLY LABELED.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:CANISTER TYPE RESPIRATOR (WHEN TLV/PEL EXCEEDED).
Ventilation:GENERAL VENTILATION REQUIRED DURING NORMAL USE. LOCAL VENTILATION MAY BE REQUIRED FOR CERTAIN OPERATIONS.
Protective Gloves:CHEM RESISTANT NITRILE/NEOPRENE/RUBBER
Eye Protection:FACE SHIELD, CHEMICAL GOGGLES
Other Protective Equipment:CLOTHING TO PREVENT SKIN CONTACT. EYEWASH STATION/SAFETY SHOWER AVAILABLE.
Work Hygienic Practices:WASH HANDS BEFORE EATING/SMOKING.
Supplemental Safety and Health
NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:282 TO 387F
Melt/Freeze Pt:M.P/F.P Text:NA
Decomp Temp:Decomp Text:NA
Vapor Pres:6.0

@ 68F
Vapor Density:> AIR
VOC Pounds/Gallon:443
pH:NA
Viscosity:NA
Evaporation Rate & Reference:SLOWER THAN ETHER
Solubility in Water:NIL
Appearance and Odor:CLEAR LIQUID, MILD ODOR
Percent Volatiles by Volume:46.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
AVOID CONTACT WITH STRONG OXIDANTS, ACIDS, BASES, AND EPOXY HARDENERS
UNDER UNCONTROLLED CONDITIONS.
Stability Condition to Avoid:HEAT, SPARKS, & OPEN FLAMES. IF P
RODUCT
CONTAINS ALUMINUM, MOISTURE IN CLOSED CONTAINER WILL GENERATE
HYDROGEN GAS.
Hazardous Decomposition Products:CARBON MONOXIDE, TOXIC VAPORS.

===== Disposal Considerations =====

Waste Disposal Methods:HAZARDOUS. DISPOSE IN COMPLIANCE W/APPLICABLE
LABELING/PACKAGING/RECORD KEEPING STANDARDS & ACCORDING TO LOCAL,
STATE, FEDERAL AGENCIES. GROUND HANDLING EQUIPMENT TO PREVENT
SPARKS. 1-800-424-9316 FOR MORE INFO.

===== Ot
her Information =====

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of thi
s information to their
particular situation.