View NSN Online: https://aerobasegroup.gr/nsn/3439-01-030-6128

POWDER ALLOY CORP -- PAC90C METAL ALLOY POWDER -- 3439-01-030-6128

Product ID:PAC90C METAL ALLOY POWDER MSDS Date:01/29/1996 FSC:3439 NIIN:01-030-6128 MSDS Number: CCVSM === Responsible Party === Company Name: POWDER ALLOY CORP Address:12036 COOPERWOOD LN City:CINCINNATI State:OH ZIP:45242-6321 Country:US Info Phone Num:513-984-4016 Emergency Phone Num:513-984-401 6 CAGE:56923 === Contractor Identification === Company Name: POWDER ALLOY CORP Address:12036 COOPERWOOD LN Box:City:CINCINNATI State:OH ZIP:45242-6321 Country:US Phone:513-984-4016 CAGE:56923

Ingred Name:COBALT (SARA 313) CAS:7440-48-4 RTECS #:GF8750000 Fraction by Wt: 44-64% Other REC Limits:NONE RECOMMENDED OSHA PEL:0.1 MG/M3 ACGIH TLV:0.02 MG/M3; A3; 9596

Ingred Name:CHROMIUM (SARA 313) (CERCLA) CAS:7440-47-3 RTECS #:GB420 0000 Fraction by Wt: 24-27% Other REC Limits:NONE RECOMMENDED OSHA PEL:1 MG/M3 ACGIH TLV:0.5 MG/M3; 9596 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingred Name:NICKEL (SARA 313) (CERCLA) CAS:7440-02-0 RTECS #:QR5950000 Fraction by Wt: 9-12% Other REC Limits:NONE RECOMMENDED OSHA PEL:1 MG/M3 ACGIH TLV:1 MG/M3; 9596

Ingred Name:TUNGSTEN,AS W,SOLUBLE COMPOUNDS. CAS:7440-33-7 RTECS #:YO7175000 Fraction by Wt: 7-9% Other REC Limits:NONE RECOMMENDED OSHA PEL:NOE ESTABLISHED ACGIH TLV:1 MG/M3/3 STEL; 9596

In gred Name:IRON CAS:7439-89-6 RTECS #:NO4565500 Fraction by Wt: 0-2% Other REC Limits:NONE RECOMMENDED

Ingred Name:MANGANESE (SARA 313) CAS:7439-96-5 RTECS #:OO9275000 Fraction by Wt: 0-1% Other REC Limits:NONE RECOMMENDED OSHA PEL:C, 5 MG/M3 (FUME) ACGIH TLV:0.2 MG/M3; 9596

Ingred Name:SILICON CAS:7440-21-3 RTECS #:VW0400000 Fraction by Wt: 0-1% Other REC Limits:NONE RECOMMENDED OSHA PEL:15 MG/M3 TDUST ACGIH TLV:10 MG/M3 TDUST; 9596

LD50 LC50 Mixture:NOT GIVEN FOR PRODUCT AS A WHOLE Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:SKIN CONTACT MAY CAUSE DERMATITIS. EYE CONTACT MAY CAUSE IRRITATION AND REDNESS. INHALATION MAY CAUSE IRRITATION TO UPPER RESPIRATORY TRACT. INGESTION MAY CAUSE NAUSEA, VOMITING AND DIARRHEA. CHRONIC SKIN CONTACT MAY LEAD TO LESIONS AND REDNESS. CHRONIC INHALATION MAY CAUSE FIBRO TIC DISEASE. Explanation of Carcinogenicity: THIS MATERAIAL MAY CONTAIN NICKEL AND/OR CHROMIUM. CHROMIUM IS LISTED AS A HUMAN CARCINOGEN AND NICKEL IS PROBABLE. Effects of Overexposure: DERMATITIS, EYE IRRITATION/REDNESS, UPPER RESPIRATORY TRACT IRRITATION, NAUSEA, VOMITING, DIARRHEA, LESIONS, SKIN REDNESS, FIBROTIC DISEASE. Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER. First Aid: EYES: FLUS H WITH WATER FOR 15 MINUTES WHILE HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION. SKIN: REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP AND WATER. IF IRRITATION PERSIST, GET MEDICAL

ATTENTION. INH ALATION: REMOVE TO FRESH AIR. RESTORE BREATHING. GET MEDICAL ATTENTION. INGESTION: INDUCE VOMITING. CONSULT A PHYSICIAN.

Flash Point:NONFLAMMABLE Lower Limits:NOT GIVEN Upper Limits:NOT GIVEN Extinguishing Media:USE CLASS "D" FIRE EXTINGUISHER Fire Fighting Procedures:SELF CONTAINED BREATHING APPARATUS SHOULD BE WORN. COMPLY WITH NFPA51B STANDARD FOR FIRE PREVENTION IN THE USE OF CUTTING AND WELDING PROCESSES. Unusual Fire/Explosion Hazard:MODERATE FIRE HAZARD IN THE FORM OF DUST OR ACCUMULATION OF SUCH. IN ADDITION, MINIMIZE AIRBORNE POWDER

PARTICLES.

Spill Release Procedures:USE RESPIRATORY EQUIPMENT DURING CLEANUP. USE EQ

UIPMENT THAT KEEPS MATERIAL FROM BECOMING AIRBORN. TO MINIMIZE DUST GENERATION, USE WET MOP, HEPA VACUUM. Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling and Storage Precautions: KEEP MATERAIL CONTAINERS CLOSED AND DRY DURING STROAGE. NO FOOD OR SMOKING IN WORK AREAS. WASH THOROUGHLY AFTER HANDLING.

Other Precautions: INSTALL EYE WASH STATIONS. HAVE SAFETY MANAGERS AND OPERATORS REVIEW "RECOMMENDED S

AFE PRACTICES FOR THERMAL SPRAY" AWS PUBLICATION C2.1-73.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection: WEAR RESPIRATOR AS APPROVED BY NIOSH OR OSHA 1910.134 TO PROTECT OPERATOR FROM FUMES.

Ventilation:LOCAL EXHAUST AND MECHANICAL (GENERAL) VENTILATION AS REQUIRED TO MAINTAIN EXPOSURE LEVELS.

Protective Gloves: IMPERVIOUS

Eye Protection: PER OSHA 1910.3

Other Protective Equipment: CHEMICAL RESISTANT CLOTHING AS NECESSARY TO PREVENT SKIN

CONTACT. AN EMERGENCY EYEWASH AND SHOWER SHOULD BE AVAILABLE.

Work Hygienic Practices:WASH HANDS THOROUGHLY WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING OR USING TOILET FACILITIES. Supplemental Safety and Health NONE SPECIFIED BY MANUFACTURER.

NONE SPECIFIED BY MANUFACTURER.

HCC:N1

Boiling Pt:B.P. Text:NOT GIVEN Melt/Freeze Pt:M.P/F.P Text:NOT GIVEN Vapor Pres:NOT GIVEN Vapor Density:NOT GIVEN Spec Gravity:NOT GIVEN Evaporation Rate & amp; R eference:NOT GIVEN Solubility in Water:INSOLUBLE Appearance and Odor:GRAY METALLIC POWDER WITH NO APPRECIABLE ODOR Percent Volatiles by Volume:NIL

Stability Indicator/Materials to Avoid:YES NONE SPECIFIED BY MANUFACTURER. Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER. Hazardous Decomposition Products:OZONE AND NITRIC OXIDE ARE FORMED DURING SPRAYING.

Waste Disposal Methods:PREVENT WASTE FROM CONTAMINATING SURROUNDING ENVIRONMENT. DISCARD ANY PRODUCT, RESIDUE, DISPOSAL CONTAINER OR LINER IN ACCORDANCE WITH ALL FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and d

isclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.