

LOCTITE PERMATEX CORP -- RC 635 RETAINING COMPOUND MAXIMUM STRENGTH, 6

=====
MSDS Safety Information
=====

FSC: 8030
NIIN: 00-614-9206
MSDS Date: 01/01/1994
MSDS Num: CCXPH
Product ID: RC 635 RETAINING COMPOUND MAXIMUM STRENGTH, 63541
MFN: 02
Responsible Party
Cage: LO692
Name: LOCTITE PERMATEX CORP
Address: 705 NORTH MOUNT
AIN RD
City: NEWINGTON CT 06111
Info Phone Number: 800-641-7376
Emergency Phone Number: 800-641-7376
Preparer's Name: STEPHEN REPETTO
Proprietary Ind: Y
Published: Y

=====
Contractor Summary
=====

Cage: LO692
Name: LOCTITE PERMATEX CORP
Address: 705 NORTH MOUNTAIN RD
City: NEWINGTON CT 06111
Phone: 800-641-7376
Cage: 62377
Name: PERMATEX INDUSTRIAL
Address: HARTFORD SQUARE N 10 COLUMBUS BLVD
City
: HARTFORD CT 06106
Phone: 877-376-2839

=====
Item Description Information
=====

Item Manager: GSA
Item Name: SEALING COMPOUND
Unit of Issue: BT
Quantitative Expression: 00000000250CC
UI Container Qty: 1

=====
Ingredients
=====

Name: *** PROPRIETARY ***

=====

=====
Health Hazards Data
=====

LD50 LC50 Mixture: LD50 (ORAL RAT): > 5000 MG/KG.

Route Of Entry Inds - Inhalation: NO

Skin: NO

Ingestion: NO

Carcinogenicity Inds - NTP: NO

IARC: NO

OSHA: NO

Effects of Exposure: ACUTE: LIQUID IS AN EYE AND SKIN IRRITANT. VAPORS MAY IRRITATE EYES, NOSE AND THROAT. CHRONIC: NONE SPECIFIED BY MANUFACTURER.

Explanation Of Carcinogenicity: NOT RELEVANT.

Signs And Symptoms Of

Overexposure: IRRITATION OF EYES, SKIN, NOSE OR THROAT.

MAY CAUSE DERMATITIS ON PROLONGED CONTACT IN SENSITIVE INDIVIDUALS.

Medical Cond Aggravated By Exposure: ACRYLIC ACID: UPPER RESPIRATORY AND LUNG DISEASES, DERMATITIS.

First Aid: INGESTION: DO NOT INDUCE VOMITING. KEEP INDIVIDUAL CALM. OBTAIN MEDICAL ATTENTION. INHALATION: REMOVE TO FRESH AIR. IF SYMPTOMS PERSIST, OBTAIN MEDICAL ATTENTION. SKIN: WASH WITH SOAP AND WATER. EYES: FLUSH AT LEAST 15 MINUTES WITH WATER. OBTAIN MEDICAL ATTENTION.

=====
Handling and Disposal
=====

Spill Release Procedures: SOAK UP IN AN INERT ABSORBENT. STORE IN A PARTLY FILLED, CLOSED CONTAINER UNTIL DISPOSAL.

Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

Waste Disposal Methods: INCINERATE FOLLOWING EPA AND LOCAL REGULATIONS. DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS (FP N).

Handling And Storage Precautions: S

TORE BELOW 110F. AVOID PROLONGED SKIN

CONTACT. KEEP AWAY FROM EYES. AVOID PROLONGED BREATHING OF VAPORS.

Other Precautions: NONE SPECIFIED BY MANUFACTURER.

=====
Fire and Explosion Hazard Information
=====

Flash Point Method: TCC

Flash Point Text: >200F,>93C

Lower Limits: SEE INGS

Upper Limits: SEE INGS

Extinguishing Media: CARBON DIOXIDE, FOAM, DRY CHEMICAL.

Fire Fighting Procedures: WEA

R NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT (FP N).
Unusual Fire/Explosion Hazard: IRRITATING ORGANIC VAPORS.

=====
Control Measures
=====

Respiratory Protection: USE NIOSH APPROVED RESPIRATOR APPROPRIATE FOR EXPOSURE OF CONCERN (FP N).
Ventilation: SUFFICIENT TO MAINTAIN VAPOR CONCENTRATIONS BELOW TLV.
Protective Gloves: RUBBER OR PLASTIC GLOVES.
Eye Protection: ANSI APPRVD CHEM WORKERS GOGGLES (FP N).
Other Protective Equipment: EMERGENCY EYEWASH AND DELUGE SHOWER MEETING ANSI DESIGN CRITERIA (FP N).
Work Hygienic Practices: NONE SPECIFIED BY MANUFACTURER.
Supplemental Safety and Health: NONE SPECIFIED BY MANUFACTURER.

=====
Physical/Chemical Properties
=====

B.P. Text: >300F,>149C
Vapor Pres: <10 @ 80F
Spec Gravity: 1.09
Solubility in Water: SLIGHT
Appearance
and Odor: GREEN LIQUID; SHARP, IRRITATING ODOR

=====
Reactivity Data
=====

Stability Indicator: YES
Stability Condition To Avoid: NONE SPECIFIED BY MANUFACTURER.
Materials To Avoid: NONE.
Hazardous Decomposition Products: NONE.
Hazardous Polymerization Indicator: NO
Conditions To Avoid Polymerization: NOT RELEVANT.

=====
Toxicological Information
=====

=====
Ecological Information
=====

=====
MSDS Transport Information
=====

=====
Regulatory Information
=====

=====

Other Information

=====

HAZCOM Label

=====

Product ID: RC 635 RETAINING COMPOUND MAXIMUM STRENGTH, 63541

Cage: LO692

Assigned IND: Y

Company Name: LOCTITE PERMATEX CORP

Street: 705 NORTH MOUNTAIN RD

City: NEWINGTON CT

Zipcode: 06111

Health Emergency Phone: 800-641-7376

Label Required IND: Y

Date Of Label Review: 12/
20/1996

Status Code: C

Label Date: 12/20/1996

Origination Code: G

Chronic Hazard IND: Y

Eye Protection IND: YES

Skin Protection IND: YES

Signal Word: CAUTION

Respiratory Protection IND: YES

Health Hazard: Slight

Contact Hazard: Slight

Fire Hazard: Slight

Reactivity Hazard: None

Hazard And Precautions: ACUTE: LIQUID IS AN EYE AND SKIN IRRITANT. VAPORS MAY IRRITATE EYES, NOSE AND THROAT. CHRONIC: PROLONGED CONTACT IN SENSITIVE INDIVIDUALS MAY CAUSE DERMATITIS.

=====

=====

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of

America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.