View NSN Online: https://aerobasegroup.gr/nsn/6830-01-008-3431

OXNARD WELDING SUPPLIES -- HELIUM -- 6830-01-008-3431

Product ID:HELIUM MSDS Date:12/01/1992

FSC:6830

NIIN:01-008-3431

MSDS Number: CCZCJ === Responsible Party ===

Company Name: OXNARD WELDING SUPPLIES

Address:241 E HUENEME RD

City:PORT HUENEME

State:CA ZIP:93041 Country:US

Info Phone Num:805-488-3563

Emergency Phone Num:805-488-3563

CAGE:0GXH1 === Contractor Iden

tification ===

Company Name: OXNARD WELDING SUPPLIES

Address:241 E HUENEME RD Box:City:PORT HUENEME

State:CA ZIP:93041 Country:US

Phone:805-488-3563

CAGE:0GXH1

======= Composition/Information on Ingredients ========

Ingred Name:HELIUM

CAS:7440-59-7

RTECS #:MH6520000 Fraction by Wt: 100% OSHA PEL:N/K ACGIH TLV:N/K

Ingred Name: HNDLG/STOR PRECS: DEFICIENCY. STORE & USE W/ADEQ VENT. CLOSE VALVE WHEN NOT IN USE & WHEN EMPTY. DO NOT STRIKE (ING 3) RTECS #:9999999ZZ

Ingred Name: IN

G 2: ARC ON CYL. DO NOT GROUND CYL OR ALLOW TO BECOME PART OF ELECTRICAL CIRCUIT.

RTECS #:9999999ZZ

Ingred Name:OTHER PRECS: OR OTHER TRAINED PERSON WHEN YOU MAKE YOUR SAFETY EVAL OF END PROD. REMEMBER, GASES & LIQS HAVE (ING 5) RTECS #:9999999ZZ

Ingred Name:ING 4: PROPERTIES WHICH CAN CAUSE SERIOUS INJURY/DEATH. BE SURE TO READ & UNDERSTAND ALL LABELS & OTHER (ING 6) RTECS #:9999999ZZ

Ingred Name:ING 5: INSTRUCTIONS SUPPLIED W/ALL CNTNRS OF THIS PROD. WHEN USED IN WELDING & C UTTING:READ & UNDERSTAND MFR'S (ING 7) RTECS #:9999999ZZ

Ingred Name:ING 6: INSTRUCTIONS & PRECAUTIONARY LABEL ON PROD. SEE AMERICAN STD Z49.1 "SAFETY IN WELDING & CUTTING" PUB BY (ING 8) RTECS #:9999999ZZ

Ingred Name:ING 7: AWS & OSHA PUB 2206 (29 CFR 1910), US GOVT PRINTING OFFICE, WASHINGTON, DC 20402 FOR MORE DETAIL. FOR (ING 9) RTECS #:9999999ZZ

Ingred Name:ING 8: FURTHER SFTY & HEALTH INFO, REFER TO PRAXAIR'S FREE PUB, L-52-529. NOTE:SUITABILITY FOR USE AS (ING 10) RTECS #:9 999999ZZ

Ingred Name:ING 9:COMPONENT IN UNDERWATER BRTHG GAS MIXS IS TO BE DETERMINED BY OR UNDER SUPERVISION OF PERS EXPERIENCED IN (ING 11) RTECS #:9999999ZZ

Ingred Name:ING 10: USE OF UNDERWATER BRTHG GAS MIXS & FAMILIAR W/EFTS, METHS, FREQUENCY & DURATION OF USE, HAZS, SIDE EFTS (ING 12) RTECS #:9999992Z

Ingred Name:ING 11: & PRECS TO BE TAKEN. FOR SAFETY INFO ON GEN HNDLG OF COMPRESSED GAS CYLS, OBTAIN A COPY OF PAMPHLET P-1,(ING 13) RTECS #:9999999ZZ

Ingred Name: ING 12: "SA

FE HANDLING OF COMPRESSED GAS IN CONTAINERS" FROM COMPRESSED GAS ASSOC, INC, 1725 JEFFERSON DAVIS HWY, (ING 14) RTECS #:9999992Z

Ingred Name:ING 13: SUITE 1004, ARLINGTON, VA 22202. NEVER WORK ON A PRESSURIZED SYS. IF THERE IS A LEAK, CLOSE CYL VALVE, (ING 15) RTECS #:9999999ZZ

Ingred Name:ING 14: BLOW DOWN THE SYSTEM BY VENTING TO SAFE PLACE, THEN REPAIR THE LEAK.
RTECS #:9999992Z

Ingred Name:RESP PROT: CONFINED SPACES. THE RESPIRATORY PROTECTION USE MUST CONFORM W/OSHA RULE

S AS SPECIFIED IN 29 CFR 1910.134.

RTECS #:9999999ZZ

Ingred Name: VENT: WORKER'S BRTHG ZONE. MECH (GEN): UNDER CERTAIN CNDTNS, GEN EXHST VENT MAY BE ACCEPTABLE PROVIDED IT IS (ING 18) RTECS #:9999999ZZ

Ingred Name:ING 17: ADEQ TO MAINTAIN CONC OF HAZ FUMES & GASES BELOW APPLICABLE TLVS IN WORKER'S BRTHG ZONE. SPECIAL/OTHER:NONE. RTECS #:9999999ZZ

========== Hazards Identification ================

LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inha

lation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic: INGESTION: AN UNLIKELY ROUTE OF

EXPOSURE. THIS PRODUCT IS A GAS AT NORMAL TEMPERATURE AND PRESSURE.

SKIN CONTACT/ABSORPTION: NO EVIDENCE OF ADVERSE EFFECTS FROM

AVAILABLE INFORMATION. INHALATION: ASPH YXIANT. MODERATE

CONCENTRATIONS MAY CAUSE HEADACHE, DROWSINESS, DIZZINESS,


EXCITATION, EXCESS (EFTS OF OVEREXP)

Explanation of Carcinogenicity:NOT RELEVANT

Eff

ects of Overexposure:HLTH HAZ: SALIVATION, VOMITING AND UNCONSCIOUSNESS. EYES: NO EVIDENCE OF ADVERSE EFFECTS FROM AVAILABLE INFORMATION. CHRONIC: NO EVIDENCE OF ADVERSE EFFECTS FROM AVAILABLE INFORMATION. OTHER EFFECTS: NONE CURRENTLY KNOWN. THIS PRODUCT IS AN ASPHYXIANT. LACK OF OXYGEN CAN CAUSE DEATH.

Medical Cond Aggravated by Exposure: A KNOWLEDGE OF THE AVAILABLE TOXICOLOGY INFORMATION AND OF THE PHYSICAL AND CHEMICAL PROPERTIES OF THE MATERIAL SUGGEST THAT OVEREXPO



Neutralizing Agent: NONE SPECIFIED BY MANUF ACTURER.

============= Handling and Storage ==========================

Handling and Storage Precautions: HIGH PRESS GAS. USE PIPING & EQUIP ADEQUATELY DESIGNED TO W/STAND PRESS TO BE ENCOUNTERED. CAN CAUSE RAPID SUFFOCATION DUE TO OXYGEN (ING 2)

Other Precautions: MIXTURES: WHEN TWO OR MORE GASES OR LIQUIFIED GASES ARE MIXED, THEIR HAZ PROPERTIES MAY COMBINE TO CREATE ADDNL, UNEXPECTED HAZS. OBTAIN & EVALUATE SAFETY INFO FOR EACH COMPONENT BEFORE YOU PRDCE MIXT URE. CON

SULT INDUS HYGIENIST (ING 4)
====== Exposure Controls/Personal Protection ========
Respiratory Protection: USE NIOSH APPRVD AIR-PURIFYING OR AIR-SUPPLIED RESPS, AS APPROP, WHERE LOC &/OR GEN EXHST VENT IS NOT ADEQ TO KEEP WORKER EXPOS BELOW APPLIC TLVS DURING WELDING W/PROD. NIOSH APPRVD AIR SUPPLIED RESP IS REQD WHILE WORKING IN (ING 16) Ventilation: LOC EXHST: USE LOC EXHST VENT SYS, IF NEC, TO MAINTAIN CONC OF HAZ FUMES & GASES BELOW APPLIC TLVS IN (ING 17) Prot
ective Gloves:IMPERVIOUS GLOVES . Eye Protection:ANSI APPRVD CHEM WORKERS GOGGLES . Other Protective Equipment:ANSI APPROVED EYE WASH & DELUGE SHOWER . METATARSAL SHOES FOR CYL HNDLG. SELECT I/A/W OSHA 29 1910.132 & 1910.133.
Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER. Supplemental Safety and Health FIRE FIGHT PROC: MOVE CNTNRS AWAY FROM FIRE AREA IF W/OUT RISK. EXPLO HAZ: (APPROX 125F). MOST CNTNRS ARE PROVIDED W/PRESS RELIEF DEVICE DESIGNED TO VENT CONTENTS WHEN THE
Y ARE EXPOS TO ELEVATED TEMP. SPILL PROC: SUFFICIENT OXYGEN CONTENT PRIOR TO PERMITTING RE-ENTRY OF PERSONNEL.
========= Physical/Chemical Properties ==========
Boiling Pt:B.P. Text:-454F,-270C Melt/Freeze Pt:M.P/F.P Text:-458F,-272C Vapor Pres:GAS Vapor Density:0.138 Spec Gravity:GAS (H*2O=1) Solubility in Water:NEGLIGIBLE Appearance and Odor:COLORLESS GAS AT NORMAL TEMPERATURE AND PRESSURE; ODORLESS. Percent Volatiles by Volume:100
========= Stabilit y and Reactivity Data ==================================

Stability Indicator/Materials to Avoid:YES

NONE CURRENTLY KNOWN. HELIUM IS CHEMICALLY INERT.

Stability Condition to Avoid: SEE SPECIAL PRECAUTIONS.

Hazardous Decomposition Products:NONE.

======= Disposal Considerations ============

Waste Disposal Methods: SLOWLY RELEASE INTO THE ATMOSPHERE. DISCARD ANY PRODUCT, RESIDUE, DISPOSABLE CONTAINER OR LINER IN AN ENVIRONMENTALLY ACCEPTABLE MANNER, IN FULL COMPLIANCE WITH FEDERAL,

STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.