

DEXTER AEROSPACE MATERIAL DIVISION -- HYSOL EA 9317 GAL SYSTEM, AS9204018 --
8040-01-320-0142

===== Product Identification =====

Product ID:HYSOL EA 9317 GAL SYSTEM, AS9204018

MSDS Date:01/01/1995

FSC:8040

NIIN:01-320-0142

Kit Part:Y

MSDS Number: CDHDS

=== Responsible Party ===

Company Name:DEXTER AEROSPACE MATERIAL DIVISION

Address:2850 WILLOW PASS ROAD

Box:312

City:PITTSBURG

State:CA

ZIP:94565-

0031

Country:US

Info Phone Num:510-458-8000

Emergency Phone Num:800-424-9300(CHEMTREC)

Preparer's Name:MSDS DEPT

CAGE:33564

=== Contractor Identification ===

Company Name:DEXTER CORPORATION ADHESIVE & COATING SYSTEMS

Address:2850 WILLOW PASS ROAD

Box:312

City:BAY POINT

State:CA

ZIP:94565-3299

Country:US

Phone:202-483-7616

CAGE:33564

Company Name:WATKINS AND ASSOCIATES INC

Address:5395 WEBB PKY

Box:City:LILBURN

State:GA

ZIP:30047

Country:US

Phone:770-279-9200

CAGE:3D523

===== Compositio

n/Information on Ingredients =====

Ingred Name:EPOXY POLYMER (ORAL RAT LD50 = >4000 MG/KG)

Fraction by Wt: 40-70%

Other REC Limits:NONE RECOMMENDED

Ingred Name:4-GLYCIDYLOXY-N,N-DIGLYCIDYLANILINE (ORAL RAT LD50 = 1000
MG/KG)(DERMAL RABBIT LD50 = >4000 MG/KG)

CAS:5026-74-4

Fraction by Wt: 15-40%

Other REC Limits:NONE RECOMMENDED

Ingred Name:ALUMINUM POWDER (SARA 313) (ORAL RAT LD50 = >4000 MG/KG)

CAS:7429-90-5

RTECS #:BD0330000

Fraction by Wt: 10-30%

Other REC Limits:NONE RECOMMEN

DED

OSHA PEL:15 MG/M3

ACGIH TLV:10 MG/M3

Ingred Name:SILICA (DERMAL RABBIT LD50 = >4000 MG/KG)

CAS:112926-00-8

Fraction by Wt: 1-5%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:6 MG/M3

ACGIH TLV:10 MG/M3

===== Hazards Identification =====

LD50 LC50 Mixture:MIXTURE HAS NOT BEEN TESTED AS A WHOLE.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:BRIEF CONTACT MAY IRRIT SK
IN OR CAUSE

A RASH. REPEATED OR PROLONGED SKIN CONTACT MAY RESULT IN ALLERGIC
SENSITIZATION. CARCINOGENICITY NOTE: BISPHENOL A/EPICHLOROHYDRIN
EPOXY RESIN HAS EXHIBITED MUTAG ENICITY IN BACTERIA.

Explanation of Carcinogenicity:NEITHER THIS MATERIAL NOR ANY OF IT'S
COMPONENTS IS CONSIDERED A CARCINOGEN.

Effects of Overexposure:SKIN RASH, IRRITATION.

Medical Cond Aggravated by Exposure:SKIN SENSITIZATION.

===== First Aid Measures =====

First

Aid:EYE:FLUSH W/WATER FOR 15MINS. IF IRRIT PERSISTS GET MED ATTN.
SKIN:WASH THOROUGHLY W/SOAP & WATER. IF IRRIT PERSISTS GET MED
ATTN. INHAL:REMOVE VICTIM TO FRESH AIR. IF SYMPTOMS PERSIST GET MED
ATTN. I NGEST:DRINK PLENTY OF WATER. GET MED ATTN IMMED.

=====
===== Fire Fighting Measures =====

Flash Point:NOT TESTED
Lower Limits:NOT TESTED
Upper Limits:NOT TESTED
Extinguishing Media:DRY CHEMICAL, OR HALON FIRE EXTINGUISHER, OR WATER
SPRAY, FOAM OR FO

G.

Fire Fighting Procedures:WEAR SCBA & FULL PROTECTIVE CLOTHING, SUCH AS
TURN-OUT GEAR. CARTRIDGE RESP DO NOT PROVIDE ADEQUATE PROTECTION
FOR FIREFIGHTERS OR EXOTHERM MITIGATION.

Unusual Fire/Explosion Hazard:MAY LIBERATE LARGE QUANTITIES OF DENSE
FOUL-SMELLING SMOKE WHICH MAY CONTAIN UNIDENTIFIED TOXIC GASES.

=====
===== Accidental Release Measures =====

Spill Release Procedures:WEAR PROTECTIVE CLOTHING, GLOVES & SAFETY
GLASSES. SCRAPE UP OR SHOVEL INTO
DOT APPROVED WASTE CONTAINERS.

Neutralizing Agent:NOT APPLICABLE.

=====
===== Handling and Storage =====

Handling and Storage Precautions:REFRIGERATED STORAGE IS RECOMMENDED TO
MAINTAIN PRODUCT QUALITY. THIS PRODUCT MAY BE STORED @ 40F FOR UP
TO 12 MONTHS.

Other Precautions:FOLLOW CURING SCHEDULE AS RECOMMENDED IN PRODUCT
LITERATURE.DON'T CUT/GRIND/WELD/DRILL ON/NEAR CONTAINER.AVOID
MIXING PARTS A&B IN BATCHES >1LB UNLESS PLAN TO USE IMMED.DON'T

HEAT MIXED ADHESIVE >75F UNLESS CURING SURFACES TO BE BONDED.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:UNNECESSARY WITH ADEQUATE EXHAUST VENTILATION.

Ventilation:LOCAL EXHAUST VENTILATION AT THE POINT OF USE.

Protective Gloves:BUTYL RUBBER, PVC, NITRILE RUBBER GLOVES

Eye Protection:SAFETY GLASSES W/SIDE SHIELD;CHEM GOGGLE

Other Protective Equipment:AN EYEWASH AND SAFETY SHOWER SHOULD BE
NEARBY AND READY FOR USE.

Work Hygienic Practices:WA

SH HANDS THOROUGHLY AFTER HANDLING MATERIALS.

Supplemental Safety and Health

FAILURE TO OBSERVE PRECAUTIONS IN MIXING/HEATING MAY RESULT IN EXCESSIVE HEAT BUILD-UP CAUSING AN EXOTHERM. THE EXOTHERM HAS POTENTIAL FOR RELEASE OF TOXIC GASES.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:UNDEFINED

Decomp Temp:Decomp Text:UNTESTED

Vapor Pres:NIL

Vapor Density:>1.0

Spec Gravity:1.59

VOC Pounds/Gallon:10

Viscosity:*

Solubility in Water:NEGLIGIBLE.

Appearance and Odor:VISCOUS GRAY PASTE, SLIGHT ODOR

Corrosion Rate:NA

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS, STRONG LEWIS OR MINERAL ACIDS.

Stability Condition to Avoid:AVOID MIXING RESIN & CURING AGENT IN

BATCHES >1 LB. UNLESS YOU PLAN TO USE IMMEDIATELY, DON'T HEAT MIXED ADHESIVE >120F.

Hazardous Decomposition Products:CO, NOX, ALDEHYDES, ACIDS & UNDETERMINED ORGANICS.

Conditions to A

void Polymerization:POLYMERIZATION NOT LIKELY

===== Disposal Considerations =====

Waste Disposal Methods:NOT RCRA HAZ WASTE.HOWEVER, INCINERATION IN EPA APPROVED WASTE INCINERATOR IS PREFERRED.CHEM ADDITIONS/ PROCESSING/OTHERWISE ALTERING MATL MAY MAKE WASTE MANAGEMENT INFOR HEREIN INCOMPLETE/INACCURATE/ INAPPROPRIATE.CONSULT STATE/LOC REGULATIONS.

===== Other Information =====

Disclaimer (provided with th

is information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.