

KRYLON PRODUCTS GROUP,SPEC DIV,SHWERWIN-WMS CO DIV -- MSC/KR12 SPRAYS-2,1301  
ACRYLIC CRYSTAL CLEAR(CLEAR ACRYLIC) -- 8010-00-990-7289

===== Product Identification =====

Product ID:MSC/KR12 SPRAYS-2,1301 ACRYLIC CRYSTAL CLEAR(CLEAR ACRYLIC)

MSDS Date:03/01/1995

FSC:8010

NIIN:00-990-7289

MSDS Number: CDKQC

=== Responsible Party ===

Company Name:KRYLON PRODUCTS GROUP,SPEC DIV,SHWERWIN-WMS CO DIV

Add

ress:31500 SOLON ROAD

City:SOLON

State:OH

ZIP:44139

Country:US

Info Phone Num:800-247-3266

Emergency Phone Num:216-292-7400

CAGE:IO479

=== Contractor Identification ===

Company Name:KRYLON PRODUCTS

Address:180 EAST BROAD ST

Box:City:COLUMBUS

State:OH

ZIP:43215

Country:US

Phone:614-431-6600;800-848-9400

CAGE:IO479

Company Name:SHERWIN-WILLIAMS DIVERSIFIED BRANDS, INC.

Address:26300 FARGO AVENUE

Box:City:BEDFORD HEIGHTS

State:OH

ZIP:44146

Country:US

Phone:216-292-7400 OR 216-595-8634

CAGE:09800

=

=====  
Composition/Information on Ingredients  
=====

Ingred Name:PROPANE (PROPELLENT)  
CAS:74-98-6  
RTECS #:TX2275000  
Fraction by Wt: 13%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:1000 PPM  
ACGIH TLV:ASPHYXIAN; 9596

Ingred Name:BUTANE (PROPELLANT)  
CAS:106-97-8  
RTECS #:EJ4200000  
Fraction by Wt: 17%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:800 PPM  
ACGIH TLV:800 PPM; 9596

Ingred Name:VM & P NAPHTHA  
CAS:64742-89-8  
Fraction by Wt: 22%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:  
ETHYL BENZENE (SARA 313)  
CAS:100-41-4  
RTECS #:DA0700000  
Fraction by Wt: 2%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:100 PPM  
ACGIH TLV:100 PPM/125STEL;9596  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:TOLUENE (SARA 313) (CERCLA)  
CAS:108-88-3  
RTECS #:XS5250000  
Fraction by Wt: 12%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:200 PPM; Z-2  
ACGIH TLV:S, 50 PPM; 9596  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA 313) (CERCLA)  
CAS:1330-20-7  
RTECS #:ZE2

100000  
Fraction by Wt: 14%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:100 PPM  
ACGIH TLV:100 PPM/150STEL;9596  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:ACETONE (SARA 313) (CERCLA)  
CAS:67-64-1  
RTECS #:AL3150000  
Fraction by Wt: 11%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:1000 PPM  
ACGIH TLV:750PPM/1000STEL;9596  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of En

try: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE:IRRIT EYE,SKIN,RESP SYSTEM.MAY  
CAUSE NERVOUS SYSTEM DEPRESSION.EXTREME OVEREXPO MAY RESULT IN  
UNCONSC,POSSIBLY DEATH.CHRONIC:PROL/REP OVEREXPO TO SOLVNTS INGREDIENTS  
MAY CAUSE ADVERSE EFFECTS TO LIVER,URINARY,BLOOD-FORMING,CARDIOVASCULAR,REPRODUCTIVE  
SYSTEMS.REPORTS HAVE ASSOC REP/PROL OVEREXPO TO SOLVNTS (SUPPLEMENT)

Explanation of Carcinogenicity

ty:PER MSDS:NO INGREDIENTS IN THESE PRODUCTS IS  
AN IARC/NTP/OSHA LISTED CARCINOGEN.

Effects of Overexposure:HEADACHE,DIZZINESS,NAUSEA,LOSS OF COORDINATION  
ARE INDICATIONS OF EXCESSIVE EXPOSURE TO VAPORS/SPRAY  
MISTS.REDNESS/ITCHING/BURNING SENSATION MAY INDICATE EYE/EXCESSIVE  
SKIN EXPOSURE.

Medical Cond Aggravated by Exposure:NONE GENERALLY RECOGNIZED.

===== First Aid Measures =====

First Aid:INHAL:REMOVE FROM EXPOSURE.RESTORE BREATHING.KEEP  
WAR

M/QUIET.SKIN:WASH THOROUGHLY W/SOAP/WATER.REMOVE CONTAMIN  
CLOTH.EYE:FLUSH W/LG AMTS OF WATER FOR 15MINS.GET MED  
ATTN.INGEST:GET MED ATTN.

===== Fire Fighting Measures =====

Flash Point Method:PMCC

Flash Point: