View NSN Online: https://aerobasegroup.gr/nsn/5610-01-281-9740

CROSSFIELD PRODUCTS CORP -- DEX-O-TEX N-38 POWDER PLAIN #1254 -- 5610-01-281-9740

Product ID:DEX-O-TEX N-38 POWDER PLAIN #1254

MSDS Date:11/11/1985

FSC:5610

NIIN:01-281-9740

Kit Part:Y

MSDS Number: CDPJL === Responsible Party ===

Company Name: CROSSFIELD PRODUCTS CORP

Address:140 VALLEY ROAD

City:ROSELLE PARK

State:NJ

ZIP:07204-1402

Country:US

Info Phone Num:908-2

45-2800 / FAX 908-245-2583

Emergency Phone Num:908-245-2800

CAGE:88167

=== Contractor Identification ===

Company Name: CROSSFIELD PRODUCTS CORP

Address:140 VALLEY ROAD Box:City:ROSELLE PARK

State:NJ

ZIP:07204-1402 Country:US

Phone:908-245-2800

CAGE:88167

====== Composition/Information on Ingredients ========

Ingred Name: CALCIUM ALUMINATE CEMENT

CAS:65997-16-2

Other REC Limits: NONE RECOMMENDED

Ingred Name: SILICA, CRYSTALLINE - QUARTZ

CAS:14808-60-7 RTECS #:VV7330000

Other REC Limi

ts:NONE RECOMMENDED ACGIH TLV:10 MG/M3 ========= Hazards Identification =============== Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: SKIN: MAY CAUSE ALKALI BURNS & DRYING. INHALATION: MAY CAUSE DELAYED LUNG INJURY. EYE/NOSE INFLAMMATION. First Aid:INHALATION: MOVE TO FRESH AIR. EYE: FLUSH W/PLENTY OF WAT CALL DR. SKIN: WASH W/SOAP & WATER. INGESTION: CALL DR. ============ Fire Fighting Measures ========================= Flash Point:NA Autoignition Temp: Autoignition Temp Text: NA Lower Limits:NA **Upper Limits:NA** Fire Fighting Procedures: NONE Unusual Fire/Explosion Hazard:NONE ======== Accidental Release Measures ============ Spill Release Procedures: SWEEP OR VACUUM USING GOOD VENTILATION. ============= Handling and Storage ========================== Hand ling and Storage Precautions: STORE IN DRY AREA AFTER HANDLING. WASH THOROUGHLY Other Precautions:PROTECT SKIN FROM CONTACT W/WET CEMENT. MAKE SURE TLV OF SIO2 NOT EXCEEDED. ====== Exposure Controls/Personal Protection ========

Respiratory Protection:IF ENVIRONMENT DUSTY USE NIOSH APPROVED RESPIRATOR.

Ventilation: GOOD, LOCAL EXHAUST, MECHANICAL GENERAL RECOMMENDED.

Protective Gloves: RUBBER

Eye Protection:TIGHT FITTING GOGGLES

Other Protective Equipment: AS NEEDED TO PRO

| Supplemental Safety and Health NK | |
|--|--|
| ======== Physical/Chemical Properties ========= | |
| Boiling Pt:B.P. Text:NA Vapor Pres:NA Vapor Density:NA Spec Gravity:NA Evaporation Rate & Deference:NA Solubility in Water:SLIGHT Appearance and Odor:GRAY, TAN OR WHITE POWDER, NO ODOR Percent Volatiles by Volume:0 | |
| ======== Stability and Reactivity Data ========= | |
| Stability Indicator/Materials to Avoid:YES NONE Stability Condition to Avoid:KEEP DRY UNTIL USED | |
| Hazardous Decomposition Products:NONE | |

TECT SKIN

======== Disposal Considerations ============

Waste Disposal Methods:DISPOSE IN SANITARY LANDFILL ACCORDING TO STATE, FEDERAL, LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and discla

ims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.