Product ID:SANDVIK MSDS Date:04/01/1991 FSC:3439 NIIN:00-460-7667 MSDS Number: CDPXR === Responsible Party === Company Name: SANDVIK STEEL CO Box:1220 City:SCRANTON State:PA ZIP:18501-1220 Country:US Info Phone Num:717-587-5191 Emergency Phone Num:717-587-5191 CAGE:1BT93 === Contractor Identification === Company Name :SANDVIK STEEL CO. Box:1220 **City:SCRANTON** State:PA ZIP:18501-1220 Country:US Phone:717-587-5191 CAGE:1BT93

Ingred Name:CALCIUM CARBONATE; (CACO*2) CAS:1317-65-3 RTECS #:EV9580000 Fraction by Wt: 1-10% OSHA PEL:15 MG/M3 TDUST ACGIH TLV:10 MG/M3 TDUST

Ingred Name:CALCIUM FLUORIDE; (CAF*2) CAS:7789-75-5 RTECS #:EW1760000 Fraction by Wt: 1-10% OSHA PEL:2.5 MG/M3 (F) (MFR) ACGIH TLV:2.5 MG/M3 (F) (MFR)

Ingred Name:CHROMIUM; (CR)

(SARA 313) (CERCLA) CAS:7440-47-3 RTECS #:GB4200000 Fraction by Wt: 5-30% OSHA PEL:1 MG/M3 ACGIH TLV:0.5 MG/M3 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB Ingred Name:COPPER; (CU) (SARA 313) (CERCLA) CAS:7440-50-8 RTECS #:GL5325000 Fraction by Wt: 0-4% OSHA PEL:0.1MG/M3 FUME;1 DUST ACGIH TLV:0.2 MG/M3 FUME EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS Ingred Name: IRON; (FE) CAS:7439-89-6 RTECS #:NO4565500 Fraction by Wt: BALANCE OSHA PEL:10 MG/M3 (MFR) ACGIH TLV:5 MG/M3 (MFR) Ingred Name:MANGANESE; (MN) (SARA 313) CAS:7439-96-5 RTECS #:009275000 Fraction by Wt: 1-10% OSHA PEL:5 MG/M3 DUST, C ACGIH TLV:5 MG/M3 DUST Ingred Name:MOLYBDENUM; (MO) CAS:7439-98-7 RTECS #:QA4680000 Fraction by Wt: 1-10% OSHA PEL:10 PPM ACGIH TLV:10 PPM Ingred Name:NICKEL; (NI) (SARA 313) (CERCLA) CAS:7440-02-0 RTECS #:QR5950000 Fraction by Wt: 1-35% OSHA PEL:1 MG/M3 ACGIH TLV:1 MG/M3 Ingred Name:NIOBIUM; (NB) (ALSO CALLED COLUMBIUM) CAS:7440-03-1 RTECS #:QT9900000 Fraction by Wt: 1-10% **OSHA PEL:N/K** ACGIH TLV:N/K

L

ngred Name:POTASSIUM; (POTASSIUM (K)) CAS:7440-09-7 RTECS #:TS6460000 Fraction by Wt: 1-10% **OSHA PEL:N/K** ACGIH TLV:N/K Ingred Name:SODIUM; (NA) (CERCLA) CAS:7440-23-5 RTECS #:VY0686000 Fraction by Wt: 1-10% **OSHA PEL:N/K** ACGIH TLV:N/K Ingred Name:SILICON; (SI) CAS:7440-21-3 RTECS #:VW0400000 Fraction by Wt: 1-10% OSHA PEL:15 MG/M3 TDUST ACGIH TLV:10 MG/M3 TDUST Ingred Name:SODIUM FLUOALUMINATE; (SODIUM ALUMINUM FLUORIDE (NA*3ALF*2)) CAS:15096-52-3 RTECS #:WA9625000 Fraction by Wt: 1-10 % OSHA PEL:2.5 MG/M3 (F) (MFR) ACGIH TLV:2.5 MG/M3 (F) (MFR) Ingred Name: TITANIUM OXIDE; (TITANIUM DIOXIDE (TIO*2)) CAS:13463-67-7

RTECS #:XR2275000 Fraction by Wt: 1-20% OSHA PEL:15 MG/M3 TDUST ACGIH TLV:10 MG/M3 TDUST

Ingred Name:SUPP DATA:GOGGLES, IF NECESSARY, TO SHIELD OTHERS. RTECS #:99999992Z

Ingred Name:OTHER PROT EQUIP:SPKS & ELEC SHOCK. SEE ANSI Z49.1. THIS MAY INCL ARM PROTECTORS, APRONS, HATS, SHOULDER PROT & (ING 17) RTECS #:9999999ZZ

Ingred Name: ING 16: DARK SUBSTANTIAL CLOT

HING. RTECS #:9999999ZZ

Ingred Name:HAZ DECOMP PROD:COATING, ETC, & FUMES & GASES (CARBON DIOXIDE, CARBON MONOXIDE, DINITROGEN TETROXIDE, HYDROGEN (ING 19) RTECS #:9999999ZZ

Ingred Name:ING 18:FLUORIDE, NITRIC OXIDE, NITROGEN DIOXIDE, OZONE, PHOSGENE & PHOSPHINE). FOR MORE SPECIFIC INFO, CONT NEHC . RTECS #:9999999ZZ

Ingred Name:EFTS OF OVEREXP:TO BE POTNTL CARCIN IN IARC MONOGRAPHS & LISTED BY OSHA/ACGIH AS POTNTL CARCIN (MFR). RTECS #:9999999ZZ

====== Hazards Id

entification ========================

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO

Health Hazards Acute and Chronic:WELDING CONSUMABLES APPLIC TO THIS MSDS AS SHIPPED ARE NON REACTIVE, NON FLAMM, NON EXPLO & ESSNTLY NON HAZ UNTIL WELDED. ELEC ARC WELDING MAY CREATE ONE/MORE OF FOLLOWING HLTH HAZS: FUMES & GASES CAN BE DANGEROUS TO YOUR HLTH. ACUTE:OVEREXP TO WELDIN

G FUMES MAY RSLT IN DISCOMFORT SUCH AS DIZZ,

NAUS OR(EFTS OF OVEREXP)

Explanation of Carcinogenicity:NICKEL:IARC MONOGRAPHS ON EVAL OF CARCIN RISK OF CHEMS TO MAN, VOL 49, PG 257, 1990:GRP 2B. NTP 7TH ANNUAL RPT (SUPDAT)

Effects of Overexposure:HLTH HAZ:DRYNESS/IRRIT OF NOSE, THROAT/EYES. CHRONIC:OVEREXP TO WELDING FUMES CAN LEAD TO SIDEROSIS (IRON PRODS IN LUNGS), CNS DMG, SENSIT DERM & BELIEVED BY SOME INVESTIGATORS TO AFFECT PULM FUNC. AR C RAYS CAN INJURE EYES & BURN SKIN. ELEC SHOCK

CAN KILL. CHROMIUM IS LISTED IN NTP ANNUAL RPT ON CARCINS & FOUND(ING 20)

Medical Cond Aggravated by Exposure:AGGRAVATION OF RESPIRATORY OR ALLERGIC CONDITIONS MAY AFFECT SOME EXPOSED INDIVIDUALS.

First Aid:REMOVE FROM EXPOSURE & CALL FOR MEDICAL AID. EMPLOY FIRST AID TECHNIQUE RECOMMENDED BY THE AMERICAN RED CROSS. INGEST:CALL MD IMMEDIATELY . INHAL:REMOVE TO FRESH AIR. SUPPORT BREATHING (GIVE

O*2 /ARTF RESP) . EYES:IMMEDIATELY FLUSH W/POTABLE WATER FOR A MINIMUM OF 15 MINUTES, SEEK ASSISTANCE FROM MD . SKIN:FLUSH W/COPIOUS AMOUNTS OF WATER. CALL MD .

Flash Point:NONFLAMMABLE Extinguishing Media: MEDIA SUITABLE FOR SURROUNDING FIRE . Fire Fighting Procedures: USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT. Unusual Fire/Explosion Hazard:WELDING ARC & SPARKS CAN IGNITE **COMBUSTIBLES & FLA** MMABLES. REFER TO ANSI Z49.1 FOR FIRE PREVENTION **DURING USE OF WELDING & ALLIED PROCEDURES.** Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER. Handling and Storage Precautions: TRAIN EACH WELDER TO KEEP HIS/HER HEAD OUT OF FUMES. TRAIN EACH WELDER NOT TO TOUCH LIVE ELEC PARTS & TO INSULATE HIS/PER PERSON FROM WORK & GROUND. Other Precautions:READ & UNDERSTAND MFR'S INSTRUCTIONS & PRECAUTIONARY LBL ON PROD. SEE ANSI Z49.1, SAFETY IN WELDING & CUTTING, PUBLISHED BY AWS, P.O. BOX 351040, MIAMI, FL 33195 & OSHA PUBLICATION 2206 (29 CFR 1910), U.S. GOVT PRINTING OFFICE, (SUPP DATA)

Respiratory Protection: USE NIOSH APPROVED RESPIRABLE FUME RESPIRATOR OR AIR-SUPPLIED RESPIRATOR WHEN WELDING IN CONFINED SPACE OR WHERE LOCAL EXHAUST OR VENTILATION DOES NOT

KEEP EXPOSURE BELOW TLV/PEL.

Ventilation:USE ENOUGH VENT, LOCAL EXHST AT THE ARC, OR BOTH, TO KEEP FUMES & GASES BELOW TLV/PEL IN WORKER'S BRTHG ZONE & GEN AREA. Protective Gloves:WELDER'S GLOVES.

Eye Protection: ANSI APPRVD CHEM WORKERS GOGGS & (SUPDAT)

Other Protective Equipment: ANSI APPRVD EYE WASH FOUNTAIN & DELUGE SHOWER. WEAR HEAD, HAND & BODY PROT TO HELP PVNT INJURY FROM RADIA, (ING 16)

Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health

EXPLAN

OF CARCIN:ON CARCINS, 1994:ANTIC TO BE CARCIN. ANIMAL:LUNGS, NASAL CAVITIES. OTHER PREC:WASHINGTON, D.C. 20402, FOR MORE DETAILS. EYE PROT:FULL LGTH FCSHLD . WEAR HELMET/USE FCSLD W/FILTE R LENS. LENS FILTER SHOULD BE AS DARK AS POSS W/OUT OBSTRUCTING VIEW OF WELD ZONE. PROVIDE PROT SCREENS & FLASH (ING 15)

HCC:T6 Appearance and Odor:SOLID CORE AND A FLUX COATING.

========= Stability and Reactivity

Stability Indicator/Materials to Avoid:YES
NONE SPECIFIED BY MANUFACTURER.
Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.
Hazardous Decomposition Products:WELDING FUMES & GASES CANNOT BE
CLASSIFIED SIMPLY. DECOMP PRODS INCL OXIDATION OF INGS FROM BASE
METAL & (ING 18)

Waste Disposal Methods:PREVENT WASTE FROM CONTAMINATING SURROUNDING ENVIRONMENT. DISCARD ANY PRODUCT, RESIDUE, DISPOSABLE CONTAINER OR

LINER IN AN ENVIRONMENTALLY ACCEPTED MANNER, IN FULL COMPLIANCE W/FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should see k competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.