

CAAP CO INC -- CAAPCOAT POLYURETHANE CURING AGENT -- 8010-01-255-5414

=====
Product Identification
=====

Product ID:CAAPCOAT POLYURETHANE CURING AGENT

MSDS Date:12/01/1992

FSC:8010

NIIN:01-255-5414

Kit Part:Y

MSDS Number: CDRVR

=== Responsible Party ===

Company Name:CAAP CO INC

Address:152 PEPES FARM ROAD

City:MILFORD

State:CT

ZIP:06460

Country:US

Info Phone Num:203-877-0375

Emergency Phone Num:2

03-877-0375

CAGE:60922

=== Contractor Identification ===

Company Name:CAAP CO INC

Address:152 PEPE'S FARM RD

Box:City:MILFORD

State:CT

ZIP:06460

Country:US

Phone:203-877-0375

CAGE:60922

=====
Composition/Information on Ingredients
=====

Ingred Name:HEXONE, METHYL ISOBUTYL KETONE (MIBK), 4-METHYL-2-PENTANONE
96-4

CAS:108-10-1

RTECS #:SA9275000

Fraction by Wt: 35%

Other REC Limits:50 PPM

OSHA PEL:50 PPM

ACGIH TLV:50 PPM

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred

Name:ALIPHATIC AMINES

Fraction by Wt: 65%

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYES: BURNING & DAMAGE. SKIN:
IRRITATION, BURNING, DERMATITIS, SENSITIZATION. INHALATION:
RESPIRATORY IRRITATION, NEURAL DYSFUNCTION, KIDNEY & LIVER DAMAGE.
PRODUCT IS CORROSIVE ACCORDING TO D.O.T. CO RROSIVITY TEST.

Explanation of C

arcinogenicity:NONE

Effects of Overexposure:IRRITATION, BURNING, DEFATTING, HEADACHE,
DIZZINESS, LOSS OF APPETITE, NAUSEA.

Medical Cond Aggravated by Exposure:PREEXISTING ALLERGIES, EYE/SKIN &
RESPIRATORY DISORDERS.

=====
===== First Aid Measures =====

First Aid:EYES: FLUSH W/LUKEWARM WATER FOR 15 MINS. SKIN: WASH WELL
W/SOAP & WATER. INHALATION: REMOVE TO FRESH AIR. GIVE CPR/OXYGEN IF
NEEDED. INGESTION: DON'T INDUCE VOMITING. OBTAIN MEDICAL ATTE
NTION
IN ALL CASES.

=====
===== Fire Fighting Measures =====

Flash Point Method:TOC

Flash Point:74F

Lower Limits:1.2

Upper Limits:8

Extinguishing Media:CO2, FOAM, DRY CHEMICAL.

Fire Fighting Procedures:USE FULL PROTECTIVE GEAR, INCLUDING SCBA &
CHEMICAL PROTECTIVE SUIT FOR AMINE/AMMONIA TYPE CORROSIVE VAPORS.
KEEP PERSONNEL UPWIND OF FIRE.

Unusual Fire/Explosion Hazard:NONE. PRODUCT IS A FLAMMABLE LIQUID.
PRODUCT BECOMES A CORROSIVE LIQUID UPON ADDI
TION OF WATER.

=====
===== Accidental Release Measures =====

Spill Release Procedures:REMOVE IGNITION SOURCES & DON'T SMOKE IN AREA.
WEAR SOLVENT RESISTANT GLOVES, APRON, BOOTS & SCBA IN PRESSURE
DEMAND MODE/POSITIVE PRESSURE AIR SUPPLIED RESPIRATOR. CONTAIN
W/ABSORBENT MATERIAL. CLEAN UP ABSORBENT & CONTAIN SECURELY. (SEE
SUPP)

=====
===== Handling and Storage =====

Other Precautions:DON'T WEAR CONTACT LENSES WHEN USING THI

S PRODUCT

BECAUSE CONTACT LENSES CONTRIBUTE TO SEVERITY OF AN EYE INJURY.
DON'T SMOKE IN IMMEDIATE AREA WHERE PRODUCT IS BEING USED.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WEAR A NIOSH APPROVED FULL FACEPIECE/PURIFYING
CARTRIDGE RESPIRATOR EQUIPPED FOR ORGANIC VAPORS & MISTS, SCBA IN
PRESSURE DEMAND MODE/POSITIVE PRESSURE AIR SUPPLIED RESPIRATOR IF
USE CONDITIONS GENERATE VAPORS/MISTS.

Ventilation:SPRAY BOOTH REQUIRED FOR

SPRAY APPLICATIONS. EXHAUST:

SUFFICIENT TO KEEP AIRBORNE CONCENTRATIONS 100F & OTHER IGNITION
SOURCES.

Hazardous Decomposition Products:NITROGEN, CO, CO2, OXIDES OF NITROGEN,
AMMONIA.

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATION IN AN APPROPRIATELY DESIGNED &
LICENSED INCINERATOR IS PREFERRED. DISPOSE OF IAW/FEDERAL, STATE &
LOCAL REGULATIONS. FLAMMABLE LIQUID UN1263.

Disclaimer (provided with this information by
the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.