

COURTAULDS AEROSPACE, INC -- PR1750 A-1/2 #1750A2 -- 8030-00-312-6128

=====  
Product Identification  
=====

Product ID:PR1750 A-1/2 #1750A2

MSDS Date:06/21/1996

FSC:8030

NIIN:00-312-6128

Kit Part:Y

MSDS Number: CDVJH

=== Responsible Party ===

Company Name:COURTAULDS AEROSPACE, INC

Address:5430 SAN FERNANDO RD.

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Country:US

Info Phone Num:818-240-2060

Emergency

Phone Num:800-424-9300 (CHEMTREC)

Preparer's Name:SEROJE HARTOONIANI

CAGE:83574

=== Contractor Identification ===

Company Name:PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY

Address:5430 SAN FERNANDO RD

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Country:US

Phone:818-240-2060

CAGE:83574

=====  
Composition/Information on Ingredients  
=====

Ingred Name:METHYL ETHYL KETONE (SARA 313) (CERCLA) (VP = 70.0 MMHG)

CAS:78-93-3

RTECS #:EL6475000

Fraction by Wt: 10.0%

Other REC Li

mits:NONE RECOMMENDED  
OSHA PEL:200 PPM/STEL 300 PPM  
ACGIH TLV:200 PPM/STEL 300 PPM  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:EYES: POSSIBLE BURNING, TEARING,  
REDDENING, IRRITATION. POSSIBLE TRANSIENT CORNEAL CLOUDING. SKIN:  
POSSIBLE REDNESS, BURNING, DRYING, CRACKING, DERMATITI  
S W/PROLONGED  
EXPOSURE. INHALATION: POSSIBLE LI VER/KIDNEY DAMAGE. COUGH, CHEST  
PAIN, THROAT IRRIT, HEADACHE, DIZZY, ANESTHETIC & CAUSE OTHER CNS  
EFFECTS. INGESTION:\*\nEffects of Overexposure:\*DIZZINESS, DROWSINESS, NAUSEA, FATIGUE. MAY  
CAUSE LIVER/KIDNEY DAMAGE. CHRONIC: MAY CAUSE DISTURBANCE IN  
MEMORY, THINKING ABILITY, EMOTIONS, COORDINATION.

=====  
===== First Aid Measures =====

First Aid:EYES: FLUSH W/LUKE WARM WATER 15 MINUTES. IF SYMPTOM  
S PERSIST  
CONSULT DR. SKIN: WASH W/SOAP & WATER. IF SYMPTOMS PERSIST CONSULT  
DR. INHALATION: GET FRESH AIR. IF SYMPTOMS PRESENT CONSULT DR.  
INGESTIO N: CONSULT DR. DO NOT INDUCE VOMITING.

=====  
===== Fire Fighting Measures =====

Flash Point Method:PMCC  
Flash Point:62.0F,16.7C  
Lower Limits:1.3  
Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM, WATER FOG.  
Fire Fighting Procedures:USE AIR-SUPPLIED RESPIRATOR. USE WATER TO COOL  
HEAT EXPOSED CONTAINERS.  
Unusual Fire/Explosion Hazard:HIGH TEMPERATURE MAY CAUSE PRESSURE  
BUILD-UP IN CLOSED CONTAINER.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL IGNITION SOURCES. WEAR AIR-SUPPLIED  
RESPIRATOR FOR MAJOR UNVENTILATED SPILL. COVER W/ABSORBENT. SCOOP  
INTO CONTAINER. CLEAN UP RESIDUE W/SUITABLE SOLVENT. CERCLA RQ FOR  
MEK = 5000 LBS, FOR TOLUENE IS 1000 LBS.

=====  
===== Handling and Storage =====

=

Handling and Storage Precautions:KEEP CONTAINER TIGHTLY CLOSED. DO NOT STORE ABOVE 120F. GROUNDING/BONDING PROCEDURE SHOULD BE FOLLOWED WHEN TRANSPORTING MATERIAL.

Other Precautions:EMPTY DRUMS MAY CONTAIN EXPLOSIVE VAPORS. DO NOT CUT, PUNCTURE OR WELD ON OR NEAR DRUM. VAPORS OF THIS PRODUCT ARE HEAVIER THAN AIR & MAY COLLECT IN LOW OR CONFINED AREAS.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:WHEN SPRAYING OR APPLYING IN ANY CIRCUMSTANCES

LIKELY TO PRODUCE AIRBORNE LEVEL OF HAZARDOUS INGREDIENTS IN EXCESS OF TLV, USE ORGANIC VAPOR CARTRIDGE OR AIR-SUPPLIED RESPIRATOR.

Ventilation:GENERAL TO MAINTAIN VAPORS AIR

Spec Gravity:1.412

pH:NA

Viscosity:1200 @10 RPM

Evaporation Rate & Reference:NOT AVAILABLE

Solubility in Water:SLIGHT

Appearance and Odor:BEIGE LIQUID

Percent Volatiles by Volume:22.8

Corrosion Rate:NA

=====  
===== Stability and Reactivity Data =====

Stability Indicator/Material

s to Avoid:YES

STRONG OXIDIZING AGENTS.

Hazardous Decomposition Products:OXIDES OF CARBON, SULPHUR DIOXIDE, TRACES OF HYDROGEN SULFIDE.

=====  
===== Disposal Considerations =====

Waste Disposal Methods:EPA #D-001 & D-035 ARE HAZARDOUS WASTE. DISPOSE IN ACCORDANCE W/FEDERAL, STATE, LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The Uni

ted States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.