

HENTZEN COATINGS, INC -- GREEN HIGH SOLIDS HEAT RESISTNT COATING 02359GML --  
8010-01-235-4164

===== Product Identification =====

Product ID:GREEN HIGH SOLIDS HEAT RESISTNT COATING 02359GML

MSDS Date:02/14/1996

FSC:8010

NIIN:01-235-4164

MSDS Number: CDVSQ

=== Responsible Party ===

Company Name:HENTZEN COATINGS, INC

Address:6937 WEST MILL ROAD

City:MILWAUKEE

State:WI

ZIP:53218

Country:US

Info Phone

Num:414-353-4200

Emergency Phone Num:414-353-4200/CHEMTREC 800-424-9300

Preparer's Name:JANE FREEMAN

CAGE:09225

=== Contractor Identification ===

Company Name:HENTZEN COATINGS INC

Address:6937 WEST MILL ROAD

Box:18749

City:MILWAUKEE

State:WI

ZIP:53218

Country:US

Phone:414-353-4200

CAGE:09225

===== Composition/Information on Ingredients =====

Ingred Name:BUTYL ALCOHOL SOLVENT (SARA III)

CAS:71-36-3

RTECS #:EO1400000

Fraction by Wt: 3.397%

Other REC Limits:NONE RECOMMENDED

OSHA

PEL:50 PPM (CEILING)  
ACGIH TLV:50 PPM (CEILING)  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:TALC PIGMENT  
CAS:14807-96-6  
RTECS #:WW2710000  
Fraction by Wt: 1-5.0%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:2 MG/M3  
ACGIH TLV:2 MG/M3

Ingred Name:NICKEL COMPOUNDS (INSOLUBLE COMPOUNDS) (SARA III)  
CAS:7440-02-0  
RTECS #:QR5950000  
Fraction by Wt: 0.636%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:1 MG/M3  
ACGIH TLV:1 MG/M3

Ingred Name:ISOBUTYL ALCOHOL SOLVENT (SARA III)  
CAS:78-83-1  
RTECS #:NP  
9625000  
Fraction by Wt: 1.144%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:50 PPM  
ACGIH TLV:50 PPM  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:ETHYL BENZENE SOLVENT (SARA III)  
CAS:100-41-4  
RTECS #:DA0700000  
Fraction by Wt: 2.018%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:100 PPM;STEL 125 PPM  
ACGIH TLV:100 PPM;STEL 125 PPM  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:XYLENE SOLVENT (SARA III)  
CAS:1330-20-7  
RTECS #:ZE2100000  
Fraction by Wt: 18.373%  
Other REC Limits:NONE RECOMM

ENDED

OSHA PEL:100 PPM;STEL 150 PPM

ACGIH TLV:100 PPM;STEL 150 PPM

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:SILICEOUS EXTENDER POWDER

CAS:66402-68-4

Fraction by Wt: 1-5.0%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:15 MG/M3

ACGIH TLV:10 MG/M3

Ingred Name:MICA PIGMENT

CAS:12001-26-2

RTECS #:VV8760000

Fraction by Wt: 5-10%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:20 MPPCF

ACGIH TLV:3 MG/M3 (RESP DUST)

Ingred Name:BARIUM COMPOUND

Fraction by Wt: 1.912%

Other REC Limits:NUISANCE DU

ST

Ingred Name:AROMATIC HYDROCARBONS (MIXTURE OF C8'S TO C10'S)

CAS:64742-95-6

Fraction by Wt: 1.822%

Other REC Limits:MFR'S LIMIT: 100 PPM

Ingred Name:TRIVALENT CHROME (INSOLUBLE) (SARA 313) (CERCLA)

CAS:7440-47-3

RTECS #:GB4200000

Fraction by Wt: 7.645%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:0.5 MG/M3

ACGIH TLV:0.5 MG/M3

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:ZINC METAL (SARA 313) (CERCLA)

CAS:7440-66-6

RTECS #:ZG8600000

Fraction by Wt: 1.427%

Other REC Limits:NUISSANCE DUST

EPA

Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:FRITS  
Fraction by Wt: 15-20%  
Other REC Limits:NUISSANCE DUST

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO  
Health Hazards Acute and Chronic:INHAL: ANESTHETIC. RESPIRATORY TRACT  
IRRITATION OR ACUTE NERVOUS SYSTEM DEPRESSION (HEADACHE, DIZZINESS,  
STAGGERING, CONFUSION OR COMA). SKIN: IRRITATION, DEFATT  
ING,  
DERMATITIS. EYE: IRRITATION. CHRON IC: BRAIN/NS/LIVER/KIDNEY DAMAGE  
DERMATITIS, DELAYED RESPIRATORY SYSTEM EFFECTS.  
Explanation of Carcinogenicity:IARC & NTP LIST NICKEL AS PROBABLY  
CARCINOGENIC TO HUMAN.  
Medical Cond Aggravated by Exposure:ASTHMA AND OTHER RESPIRATORY  
AILMENTS; CHEMICAL SENSITIZATION.

===== First Aid Measures =====

First Aid:INHAL: REMOVE FROM EXPOSURE. RESTORE BREATHING. KEEP WARM &  
QUIET. NOTIFY A PHYSICIAN. EY  
ES: FLUSH IMMEDIATELY WITH LARGE  
AMOUNTS OF RUNNING WATER FOR AT LEAST 15 MINUTES. LIFT LIDS. TAKE  
TO PHYSICIAN FOR MEDICAL TREATMENT. SKIN: WASH WITH SOAP & WATER.  
REMOVE CONTAM CLOTHES, WASH BEFORE REUSE, CALL DR. INGEST: CALL  
DR/POISON CONTROL CENTER IMMED.

===== Fire Fighting Measures =====

Flash Point Method:TCC  
Flash Point:81.0F,27.2C  
Autoignition Temp:Autoignition Temp Text:NA  
Lower Limits:1.0  
Upper Limits:11.2  
Extinguishing Media:FOAM,

DRY CHEMICAL, CO2

Fire Fighting Procedures:WEAR PROTECT EQUIP INCLUDING SCBA. WATER MAY BE INEFFECTIVE, USE WATER (FOG NOZZLES PREFERRED) COOL CLOSED CNTNR TO PREVENT PRESSURE BLDUP,AUTOIGNITN,EXPLOSION.

Unusual Fire/Explosion Hazard:KEEP CONTAINER TIGHTLY CLOSED. KEEP FROM HEAT/IGNIT SOURCE. CLOSED CNTNR MAY EXPLODE W/HEAT. DON'T APPLY TO HOT SRFCs. NEVER USE WELD/CUT TORCH ON/NEAR DRUM.

===== Accidental Release Measures =====

Spill Release Procedur

es:REMOVE ALL SOURCES OF IGNITION. VENTILATE AREA. USE APPROPRIATE PROTECTIVE EQUIPMENT. AVIOD BREATHING VAPORS/SKIN CONTACT. PREVENT ENTRY TO DRAINS/SEWERS/WATERWAYS. NOTIFY AUTHORITIES. CONTAIN & REMOV E WITH INERT ABSORBENT AND NONSPARKING TOOLS.

===== Handling and Storage =====

Handling and Storage Precautions:DONT STORE @>120F. LARGE AMTS IN BUILDINGS DESIGNED (OSHA 1910.106). NO IGNITS. KEEP CLOSED/UPRIGHT/TIGHT WHEN NOT IN USE. EMPTY CNTNR HAZARDOUS.

Other Precautions:SOAK SOILED RAGS/WASTES IN H2O FILLED CLOSED CNTNR. USE W/ADEQUATE VENT, AVOID VAPOR BREATHING/SKIN CONTACT, GROUND/BOND WHEN TRANSFERRING, AVOID FREEFALL OF LIQ >FEW INCHES, USE SPARKPROOF TOOLS/EXPL OSION PROOF EQUIPMENT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:OUTDOOR/SANDING/GRINDING: NIOSH MECHANICAL FILTER RESPRTR. CONFINED AREA: NIOSH AIR SUPPLIED RESPIRATOR/HOOD. AIR MONITORI NG MAY BE REQUIRED.

Ventilation:GENERAL DILUTION/LOCAL EXHAUST TO KEEP BELOW PEL/TLV.

Protective Gloves:CHENICAL RESISTANT

Eye Protection:SAFETY EYEWEAR W/SPLASH GUARDS/SIDE SHLD

Other Protective Equipment:APPROPRIATE TO PREVENT PROLONGED SKIN CONTACT.

Work Hygienic Practices:WASH HANDS BEFORE EATING OR SMOKING. SMOKE IN DESIGNATED SMOKING AREAS ONLY.

Supplemental Safety and Health  
NMORE INFORMATION ON FILE.

===== Physical/Chemical Properties =====

Boiling P

t:B.P. Text:220 TO 418F  
Melt/Freeze Pt:M.P/F.P Text:NA  
Vapor Pres:9.00 @ 68F  
Vapor Density:> AIR  
Spec Gravity:1.43  
pH:NA  
VOC Grams/Liter:3.37  
Evaporation Rate & Reference:SLOWER THAN BUTYL ACETATE  
Solubility in Water:NEGLIGIBLE  
Appearance and Odor:OPAQUE LIQUID, SOLVENT ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
STRONG OXIDIZERS  
Hazardous Decomposition Products:MAY PRODUCE HAZARDOUS FUMES WHEN  
HEATED TO DECOMPOSIT  
ION AS IN WELDING. MAY CONTAIN CARBON MONOXIDE  
& CARBON DIOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:RECYCLE OR INCINERATE IN ACCORDANCE WITH LOCAL,  
STATE, & FEDERAL REGULATIONS.

===== Other Information =====

=====

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by  
elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.