

R.H.CARLSON COMPANY, INC. -- NORCAST A-4000 PART A -- 8040-00-097-6524

=====
Product Identification
=====

Product ID:NORCAST A-4000 PART A
MSDS Date:12/13/1993
FSC:8040
NIIN:00-097-6524
Kit Part:Y
MSDS Number: CDXPY
=== Responsible Party ===
Company Name:R.H.CARLSON COMPANY, INC.
Address:41 CHESTNUT STREET
Box:1687
City:GREENWICH
State:CT
ZIP:06830-5921
Country:US
Info Phone Num:203-661-9288
Emer
gency Phone Num:203-531-5500
CAGE:33530
=== Contractor Identification ===
Company Name:R.H.CARLSON COMPANY,INC.
Address:41-CHESTNUT STREET
Box:1687
City:GREENWICH
State:CT
ZIP:06830-5921
Country:US
Phone:203-531-5500
CAGE:33530

=====
Composition/Information on Ingredients
=====

Ingred Name:TOLUENE (SARA 313) (CERCLA)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 30-60.0%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:100 PPM
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

=====

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INGEST: ABDOMINAL PAIN, DIARRHEA,
NAUSEA & VOMITING. INHAL: HEADACHE, DIZZINESS, NAUSEA,
INCOORDINATION. MAY CAUSE SKIN & RESPIRATORY SENSITIZATION,
EYE/THROAT IRRIT, MAY BE ACUTELY TOXIC & POTENTIAL CANCER HAZARD.

=====
First Aid Measures
=====

First Aid:INGEST: IMMED GIVE SEVERAL GLASSES WATER, DONT INDUCE VOMIT,
IF VOMIT OCCURS, GIVE FLUID, CALL DR. DONT GIVE FLUID TO
UNCONSCIOUS PERSON. SKIN: FLUSH W/WATER 15 MIN, REMOVE CONTAM
CLOTHES/SHOES WASH O R DISCARD, GET MED AID. EYE: IMMED FLUSH W/LG
AMTS WATER >15 MIN, LIFT LIDS, GET MED AID ASAP, FLUSH ANOTHER 15
MIN. INHAL: GET FRESH AIR, GET MED AID, IF NO BREATH GIVE MOUTH TO
MOUTH.

=====
Fire Fighting Measures
=====

Flash Po
int Method:TCC
Flash Point:35.0F,1.7C
Autoignition Temp:Autoignition Temp Text:997F
Lower Limits:1.2
Upper Limits:7.0
Extinguishing Media:USE STANDARD FIREFIGHTING TECHNIQUES.
Fire Fighting Procedures:EVAC AREA, FIREFIGHTERS SHOULD WEAR
FULLFACE SCBA & IMPERVIOUS PROTECTIVE CLOTHING.

=====
Accidental Release Measures
=====

Spill Release Procedures:WEAR PERSONAL PROTECTIVE CLOTHING & EQUIPMENT,
SOAK UP W/ABSORBENT, SWEEP UP & PLACE IN CHEM WASTE DRUM FOR
D
ISPOSAL, WASH AREA W/DETERGENT & WATER, FLUSH W/WATER. LG:
DIKE/PUMP INTO DRUM FOR SALVAGE OR DISPOSAL.

=====
Handling and Storage
=====

Handling and Storage Precautions:AVOID SKIN/EYE CONTACT, USE GROUND
STRAP AND STORE UPRIGHT