

DEXTER ELECTRONIC MATERIALS -- CAT-L-INK 50-771R GLOS BLACK (XX1190) -- 7510-01-413-2492

=====  
Product Identification  
=====

Product ID:CAT-L-INK 50-771R GLOS BLACK (XX1190)

MSDS Date:04/03/1996

FSC:7510

NIIN:01-413-2492

Kit Part:Y

MSDS Number: CFBBS

=== Responsible Party ===

Company Name:DEXTER ELECTRONIC MATERIALS

Address:15051 EAST DON JULIAN ROAD

City:INDUSTRY

State:CA

ZIP:91746-1282

Country:U

S

Info Phone Num:818-968-6511

Emergency Phone Num:800-424-9300 (CHEMTREC)

CAGE:04347

=== Contractor Identification ===

Company Name:DEXTER CORP DEXTER ELECTRONIC MATERIALS

Address:15051 E DON JULIAN RD

Box:City:INDUSTRY

State:CA

ZIP:91746-1282

Country:US

Phone:626-968-6511

CAGE:79436

Company Name:DEXTER CORP THE DEXTER ELECTRONIC MATERIAL DIV

Address:211 FRANKLIN ST.

Box:City:OLEAN

State:NY

ZIP:14760-1297

Country:US

Phone:716-372-6300/6309

CAGE:04347

=====  
Composition/Information on Ing

redients =====

Ingred Name:DGBA EPOXY RESINS  
CAS:25068-38-6  
RTECS #:SL6475000  
Fraction by Wt: 15-40%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:BISPHENOL A (SARA 313)  
CAS:80-05-7  
RTECS #:SL6300000  
Fraction by Wt: 7-13%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:DIETHYLENEGLYCOL ETHYL ETHER ACETATE (SARA 313)  
CAS:112-15-2  
Fraction by Wt: 7-13%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:DIPROPYLENE GLYCOL METHYL ETHER  
CAS:34590-94-8  
RTECS #:JM1575000  
Fraction by Wt: 5-10%  
Oth  
er REC Limits:NONE RECOMMENDED  
OSHA PEL:100 PPM/150 STEL  
ACGIH TLV:100 PPM/150 STEL

Ingred Name:PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE (SARA 313)  
CAS:108-65-6  
RTECS #:AI8925000  
Fraction by Wt: 5-10%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:100 PPM  
ACGIH TLV:100 PPN

Ingred Name:BLACK PIGMENT  
CAS:68186-91-4  
Fraction by Wt: 15-40%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:AROMATIC HYDROCARBON SOLVENT  
CAS:64742-94-5  
RTECS #:WF3100000  
Other REC Limits:NONE RECOMMENDED

=====

== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:EYE: IRRITATING W/REDNESS, PAIN OR  
TEARING, BURNS. SKIN: IRRITATING, RASH, DERMATITIS, ALLERGIC  
REACTION, SENSITIZATION. INHAL: IRRITATING TO  
EYES/NOSE/THROAT/LUNGS. INGEST: IRRITATING TO MOUTH/STOMAC  
H/DIGESTIVE TRACT, VOMITING. TARGET ORGANS: SKIN/EYES/LUNGS/MUCOUS  
MEMBRANES.

=====  
===== First Aid Measures =====

First Aid:EYE: FLUSH W/H2O 10-15 MINS, BLINK. REPEAT FLUSHING, CALL DR.  
SKIN: RINSE W/PLENTY H2O, WASH W/SOAP/H2O. REMOVE CONTAM CLOTHES.  
DONT APPLY LOTIONS/CREAMS W/OUT ADVICE OF DR/POISON CONTROL. CALL  
DR. IN HAL: GET FRESH AIR. IF BREATH DIFF, GETMED AID. IF NO  
BREATH, GIVE ARTIF RESP, CALL 911. INGEST: DONT INDUCE VOMIT, RINSE  
MOUTH W/H2O. DRINK AS MUCH H2O AS DESIRED. CALL POISON CNTRL. GET  
MED AID.

=====  
===== Fire Fighting Measures =====

Flash Point Method:SCC  
Flash Point:145F,63C  
Extinguishing Media:CARBON DIOXIDE, FOAM OR DRY CHEMICAL.  
Fire Fighting Procedures:WEAR SCBA PRESSURE DEMAND MSHA/NIOSH APPROVED  
& FULL FIREFIGHTING PROTECTIVE GEAR.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE IGNITS. PROVIDE ADEQUATE VENT/PERSONAL  
PROTECTIVE EQUIPMENT. ABSORB. CONTAINERIZE. DIKE.

=====  
Handling and Storage =====

Handling and Storage Precautions:STORE UPRIGHT, KEEP AWAY FROM  
HEAT/FLAME.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE OSHA APPROVED AIR PURIFYING HALF-FACE  
RESPIRATOR W/APPROPRIATE CARTRIDGE.  
Ventilation:LOCAL EXHAUST.  
Protective Gloves:CHEMICAL RESISTANT, RUBBER.  
Eye Protection:SAFETY GLASSES W/SIDE OR FACE SHIELD.  
Other Protective Equipment:RUBBER APRON, SAFETY SHOWER, EYEWASH  
STATIO

N.  
Supplemental Safety and Health  
NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:320 TO 370F  
Spec Gravity:1.27  
pH:NE  
VOC Grams/Liter:3.43  
Appearance and Odor:BLACK LIQUID, MILD ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
OXIDIZING AGENTS.  
Stability Condition to Avoid:EXTREME TEMPERATURES.  
Hazardous Decomposition Products:NONE

===== Disposal Considerations =  
=====

Waste Disposal Methods:FOLLOW APPLICABLE FEDERAL/STATE/LOCAL  
REGULATIONS. REUSE, RECYCLE, BURN, OR TREAT MATERIAL.

===== Other Information =====

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims a  
ll liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.