View NSN Online: https://aerobasegroup.gr/nsn/5826-01-307-7380

POINTER INC -- 7938174-60/3000-9, BATTERY PACK, LITHIUM -- 5826-01-307-7380

Product ID:7938174-60/3000-9, BATTERY PACK, LITHIUM MSDS Date:09/27/1995 FSC:5826 NIIN:01-307-7380 **MSDS Number: CFCWN** === Responsible Party === **Company Name: POINTER INC** Address:1027 N STADEM DR City:TEMPE State:AZ ZIP:85281 Country:US Info Phone Num:602-966-1674 Emergency Phone Num:602-96 6-1674, 800-424-9300 CHEMTREC CAGE:58507 === Contractor Identification === **Company Name: POINTER INC** Address:1027 N STADEM DR Box:City:TEMPE State:AZ ZIP:85281 Country:US Phone:602-966-1674 CAGE:58507

Ingred Name:LITHIUM METAL CAS:7439-93-2 RTECS #:OJ5540000 Fraction by Wt: 2.5% Other REC Limits:NONE RECOMMENDED

Ingred Name:SULFUR DIOXIDE CAS:7446-09-5 RTECS #:WS4550000 Fraction by Wt: 25% Other REC Limits:NONE RECOMMENDED OS HA PEL:5 PPM ACGIH TLV:2 PPM

Ingred Name:ACETONITRILE CAS:2206-26-0 Fraction by Wt: 60% Other REC Limits:NONE RECOMMENDED

Ingred Name:ACETYLENE BLACK CAS:133-86-4 Fraction by Wt: 5% Other REC Limits:NONE RECOMMENDED

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:DEPENDING ON THE CONCENTRATION OF SULFUR DIOXIDE, ACTS AS AN ASP
HYXIANT AND MAY POSSIBLY CAUSE UNCONSCIOUSNESS WITH NO KNOWN CHRONIC HEALTH EFFECTS.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:SULPUR DIOXIDE-IRRITATION OF NOSE, THROAT, EYES AND/OR SKIN. SUFFOCATING ODOR.
Medical Cond Aggravated by Exposure:SULPHUR DIOXIDE-ASTHMA AND OTHER RESPIRATORY DISEASE.

First Aid:IF CELLS OF BATTERY VENTS PERSONNEL SHOULD BE EVACUATED FROM THE CONTAMINATED AREA, ARTIF ICIAL RESPIRATION SHOULD BE GIVEN IF BREATHING STOPS. FLUSH MATERIAL FROM SKIN.

Flash Point Method:COC

Flash Point:NON-FLAMMABLE

Extinguishing Media:USE WATER OR CARBON DIOXIDE ON BURNING LITHIUM SULPHUR DIOXIDE CELLS OR BATTERIES. USE CLASS D FIRE EXT. AGENT ON RAW LI Fire Fighting Procedures:USE SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:BATTERY MAY VENT WHEN SUBJECT TO EXCESSIVE HEAT EXPOSING CELL CONTENTS.

Spill Release Procedures: KEEP OUT OF AREA UNLESS USING IMPERVIOUS GLOVES AND CLOTHING AND FULL FACE BREATHING APPARATUS. PROVIDE MAXIMUM VENTILATION TO CLEAR OUT HAZARDOUS GASES. Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

Handling and Storage Precautions:DO NOT STORE AT TEMPERATURES ABOVE 160F. STORE AT 70F FOR MAX
IMUM SHELF LIFE IN WELL VENTILATED AREA. DO NOT CRUSH OR PUNCTURE PACK OR CELLS.
Other Precautions:DO NOT BYPASS FUES/DIODE ASSEMBLY IN PACK. TRANSPORT RESTRICTIONS APPLY.

Eye Protection:SAFETY GLASSES WITH SIDE SHIELDS. Supplemental Safety and Health NONE

HCC:R2 Melt/Freeze Pt:M.P/F.P Text:374F,190C Spec Gravity:1 Solubility in Water:NOT SOLUBLE IN WATER

Stability Indicator/Materials to Avoid:YES Stability Condition to Avoid:BATTERY CONTAINS HERMATICALLY SEALED CELLS AND IS NON-REACTIVE PROVIDED THE CELL SEAL REMAINS INTACT. Conditions to Avoid Polymerization:HEATING, MECHANICAL ABUSE AND ELECTRICAL ABUSE. DO NOT ATTEMPT TO RECHARGE OR SHORT CIRCUIT.

Waste Disposal Methods: DISPOSE OF IN ACCORD

ANCE WITH LOCAL, STATE AND FEDERAL ENVIRONMENTAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility f or the suitability of this information to their particular situation.