

COURTAULDS COATINGS, INC. INTERNATIONAL -- 5347 TPD-24607 SOFT WHITE CHLOR/ALKYD F124 -- 8010-01-344-5089

===== Product Identification =====

Product ID:5347 TPD-24607 SOFT WHITE CHLOR/ALKYD F124

MSDS Date:12/18/1995

FSC:8010

NIIN:01-344-5089

Kit Part:Y

MSDS Number: CFDGS

=== Responsible Party ===

Company Name:COURTAULDS COATINGS, INC. INTERNATIONAL

Address:6001 ANTOINE DRIVE

City:HOUSTON

State:TX

ZIP:77091

Country:US

Info Phone Num:800-854-6813

Emergency Phone Num:800-424-9300 (CHEMTREC)

CAGE:50411

=== Contractor Identification ===

Company Name:COURTAULDS COATINGS INC

Address:400 S 13TH STREET

Box:City:LOUISVILLE

State:KY

ZIP:40203-1714

Country:US

Phone:502-588-9651

CAGE:50411

Company Name:INTERNATIONAL PAINT INC

Address:6001 ANTOINE DRIVE

Box:City:HOUSTON

State:TX

ZIP:77091

Country:US

Phone:713-684-1244

CAGE:028S6

===== Composition/Information on Ingredients =====

I

ingred Name:TRIMETHYL BENZENE (SARA 313)
CAS:25551-13-7
RTECS #:DC3220000
Fraction by Wt: 5-10%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:25 PPM
ACGIH TLV:25 PPM

Ingred Name:METHYL-BENZENE (VP = 22.0)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 0-1.0%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:100 PPM
ACGIH TLV:100 PPM
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:LIGROINE (VP = 7.0)
CAS:8032-32-4
RTECS #:OI6180000
Fraction by Wt: 1-5.0%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:10
0 PPM
ACGIH TLV:100 PPM

Ingred Name:LIGROINE (VP = 2.0)
CAS:64742-88-7
Fraction by Wt: 5-10%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:100 PPM
ACGIH TLV:100 PPM

Ingred Name:ALUMINA TRIHYDRATE
CAS:21645-51-2
RTECS #:BD0940000
Fraction by Wt: 5-10%
Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EY

E: IRRITATION, RED, TEAR, BLURRED VISION. SKIN: DERMATITIS. INHAL: IRRITATION, HEADACHE, DIZZINESS, UNCONSCIOUSNESS. INGEST: GI IRRITATION, NAUSEA, VOMIT, DIARRHEA. Medical Cond Aggravated by Exposure:SKIN & RESPIRATORY CONDITIONS.

=====
===== First Aid Measures =====

First Aid:EYE: FLUSH IMMED W/LARGE AMOUNTS WATER FOR 15 MINUTES. GET MED AID. SKIN: REMOVE CONTAM CLOTHES. WASH BEFORE REUSE. WASH W/PLENTY SOAP & WATER. GET IMMED MED AID. INHAL: MOVE TO FRESH AIR. GIVE ARTIF RESP. INGEST: CALL DR.

=====
===== Fire Fighting Measures =====

Flash Point:105F,41C
Lower Limits:1.0
Extinguishing Media:FOAM, CO2, DRY CHEMICAL.
Fire Fighting Procedures:SMOTHER FLAMES. USE WATER TO COOL UNOPENED CONTAINERS. CLOSED CONTAINERS MAY EXPLODE W/EXTREME HEAT.
Unusual Fire/Explosion Hazard:KEEP AWAY FROM IGNITS.

=====
===== Accidental Release Measures =====

Spill Release Procedures:REMOVE IGNIT S. VENT AREA. CLEAN UP W/ABOSRBENT.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN BUILDINGS DESIGNED FOR PRODUCT.
Other Precautions:CHRONIC OVEREXPOSURE & MISUSE OF SOLVENTS HAS BEEN LINKED TO PERMANENT BRAIN/NERVOUS SYSTEM DAMAGE.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:OUTDOORS: NIOSH/APPROVED FILTER RESPIRATOR. IN RESTRICTED VENT AREA: NIOSH APPROVED RESPIRATOR.
Ventilation:SUFFICIENT.
Protective Gloves:CHEMICAL RESISTANT.
Eye Protection:CHEMICAL GOGGLES &/OR FACE SHIELD.
Other Protective Equipment:IMPERVIOUS PROTECTIVE CLOTHING.
Work Hygienic Practices:WASH HANDS BEFORE EATING/SMOKING.
Supplemental Safety and Health
NK

=====
===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:300F,149C
Vapor Density:>AIR
VOC Grams/Liter:2.8
Evaporation Rate & Reference: