View NSN Online: https://aerobasegroup.gr/nsn/1440-01-368-3822

Product ID:ACCUMULATOR MSDS Date:06/01/1989 FSC:1440 NIIN:01-368-3822 MSDS Number: CFFJZ === Responsible Party === **Company Name:SENIOR FLEXONICS INC** Address:1075 PROVIDENCE HWY **City:SHARON** State:MA ZIP:02067 Country:US Info Phone Num:617-784-1400 Emergency Phone Num:617-784-1400 Preparer's Name: HMIS (DSCR-VB A) CAGE:16519 === Contractor Identification === Company Name: SENIOR FLEXONICS INC Address:1075 PROVIDENCE HWY Box:City:SHARON State:MA ZIP:02067 Country:US Phone:617-784-1400 CAGE:16519 Company Name: WILDWOOD ELECTRONICS, INC (205-461-7110) Box:UNKNOW CAGE:6X173

======= Composition/Information on Ingredients ==========

Ingred Name:NITROGEN CAS:7727-37-9 RTECS #:QW9700000 Fraction by Wt: 100% ACGIH TLV:ASPHYXIANT; 9192

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:NITROGEN IS A SIMPLE ASPHYXIANT. NITROGEN UNDER HIGH PRESSURE CAN PRODUCE NARCOSIS. Explanation of Carcinogenicity:NONE OF THE CHEMICALS IN THIS PRODUCT IS LISTED BY IARC, NTP OR OSHA AS A CARCINOGEN. Effects of Overexposure: INHALATION (IN ABSENCE OF OXYGEN): DIZZINESS, NAUSEA, VOMITING, LOSS OF CONSCIOUSNESS, AND DEATH. Medical Cond Aggravate d by Exposure:NONE NOTED. First Aid:INHALATION: REMOVE SUBJECT TO FRESH AIR. GIVE OXYGEN/CPR AS NEEDED. Extinguishing Media: AS APPROPIATE FOR SURROUNDING FIRE. Fire Fighting Procedures: FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCB & FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER SPRAY TO CO NEARBY CONTAINERS EXPOSED TO FIRE. Unu sual Fire/Explosion Hazard: CYLINDERS MAY EXPLODE IN HEAT OF FIRE. Spill Release Procedures: VENTILATE ENCLOSED AREAS TO PREVENT FORMATION OF OXYGEN-DEFICIENT ATMOSPHERES CAUSED BY THE RELEASE OF GASEOUS NITROGEN. Neutralizing Agent:NONE APPLICABLE FOR THIS MATERIAL Handling and Storage Precautions: USE ONLY IN WELL VENTILATED AREAS. CONTAINS NITROG EN AT HIGH PRESSURE (1100 PSI). HANDLE WITH CARE. **Other Precautions:NONE** Respiratory Protection: USE SCBA IN OXYGEN-DEFICIENT ATMOSPHERES. CAUTION! RESPIRATORS WILL NOT FUNCTION. USE MAY RESULT IN ASPHYXIATION. Ventilation: MECHANICAL (GENERAL) VENTILATION AND/OR LOCAL EXHAUST AS NECESSARY. Protective Gloves: LEATHER WORK GLOVES. Eye Protection:SAFETY GLASSES. Other Protective Equipment: OXYGEN MONITORING EQUIPMENT TO

===

TEST FOR OXYGEN DEFICIENT ATMOSPHERES. Work Hygienic Practices:STANDARD HYGENIC PRACTICES. Supplemental Safety and Health MSDS NOT AVAILABLE FROM MFR. MSDS GENERATED WITH INFORMATION PROVIDE BY MFR AND DDSP-TH. CHARGE PRESSURE IS 1100 PSI, PROOF PRESSURE IS 4500 PSI, VOLUME OF GAS 445 CU.IN.

HCC:G3 Boiling Pt:B.P. Text:-320F,-196C Melt/Freeze Pt:M.P/F.P Text:-346F,-210C Vapor Pres:1100 PSI Vapor Density:0.07245 Sp ec Gravity:0.967 Solubility in Water:1.52% Appearance and Odor:COLORLESS, ODORLESS GAS. Percent Volatiles by Volume:100

Stability Indicator/Materials to Avoid:YES NONE. Stability Condition to Avoid:NONE. Hazardous Decomposition Products:NONE.

Waste Disposal Methods:VENT NITROGEN GAS SLOWLY TO A WELL VENTILATED OUTODOOR LOCATION REMOTE FROM WORK AREAS. DO NOT DISPOSE OF RESIDUAL NITROGEN IN CYLINDERS. RETURN TO MANUFACTURER WITH RESIDUAL PRESSURE.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice t o verify and assume responsibility for the suitability of this information to their particular situation.