

PRATT AND LAMBERT, INC; INDUSTRIAL COATINGS DIV -- ENAMEL ALKYD SEMIGLOSS #775402 --  
8010-01-131-9194

===== Product Identification =====

Product ID:ENAMEL ALKYD SEMIGLOSS #775402

MSDS Date:03/23/1993

FSC:8010

NIIN:01-131-9194

MSDS Number: CFNCC

=== Responsible Party ===

Company Name:PRATT AND LAMBERT, INC; INDUSTRIAL COATINGS DIV

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Info Phone Num:3

16-733-1361

Emergency Phone Num:716-873-6000/DOT: 800-255-3924

Preparer's Name:L. A. ELLISON

CAGE:61196

=== Contractor Identification ===

Company Name:PRATT AND LAMBERT INC

Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

===== Composition/Information on Ingredients =====

Ingred Name:PETROLEUM DISTILLATE HYDROTREATED LIGHT SOLVENT

CAS:64742-47-8

Fraction by Wt: 10.0%

Other REC Limits:NONE RECOMMENDED

Ingred Name:XYLENE (SARA 313) (CERC

LA) (VP = 5 @ 20C)  
CAS:1330-20-7  
RTECS #:ZE2100000  
Fraction by Wt: 10.0%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:100 PPM/STEL 150  
ACGIH TLV:100 PPM/STEL 150  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:METHYL ISOAMYL KETONE  
CAS:110-12-3  
RTECS #:MP3850000  
Fraction by Wt: 5.0%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:50 PPM  
ACGIH TLV:50 PPM

Ingred Name:TALC  
CAS:14807-96-6  
RTECS #:MW2700000  
Fraction by Wt: 15.0%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:2.0 MG/M3  
ACGIH TLV:2 MG/M3

Ingred Name:CRYSTALLINE SILICA  
CAS:14808-60-7  
RTECS #:VV7330000  
Fraction by Wt: 115F. STORE LARGE  
QUANTITIES IN COMPLIANCE WITH OSHA 29 CFR 1910.106.  
Other Precautions:DONT WASH OR REUSE EMPTY CONTAINER FOR ANY PURPOSE.  
GROUND & BOND CONTAINERS TO RECEIVING CONTAINER. DONT WELD, BRAZE  
OR CUT ON EMPTY CONTAINER. NEVER USE PRESSURE TO EMPTY. DRUM IS NOT  
A PRESSURE VESSEL.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH CHEMICAL CARTRIDGE RESPIRATOR. FOR  
SPRAYING USE MECHANICAL PREFILTER. IN CONFINED AREAS USE AIR  
SUPPLIED RESPIRATOR.  
Ventilation:LOCAL EXHAUST.  
Protective Gloves:IMPERMEABLE.  
Eye Protection:SAFETY SPECTACLES.  
Other Protective Equipment:EYEWASH FACILITY, SAFETY SHOWER.  
Supplemental Safety and Health  
MORE INFORMATION ON FILE

=====  
===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:165 TO 383F  
Melt/Freeze Pt:M.P/F.P Text:-50F,-46C  
Decomp Temp:Decomp Text:1832F,1

000C  
Vapor Pres:10.0  
Vapor Density:>AIR.  
Spec Gravity:1.2  
pH:4-7  
Viscosity:67-77 KU  
Evaporation Rate & Reference:SLOWER THAN DIETHYL ETHER  
Solubility in Water:SLIGHT.  
Appearance and Odor:LIQUID, W/SOLVENT ODOR.  
Percent Volatiles by Volume:42.0  
Corrosion Rate:NA

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
STRONG ACIDS OR ALKALINE MATERIALS. OXIDIZING MATERIALS.  
Stability Condition to Avoid:AVOID EXCESSIVE HEAT (>115F) AND SO  
URCES  
OF IGNITION.  
Hazardous Decomposition Products:SMOKE, CARBON MONOXIDE & CARBON  
DIOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:IN ACCORDANCE W/FEDERAL, STATE & LOCAL  
LAWS/REGULATIONS. RCRA CLASSIFICATION: D001.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.