

LELAND LIMITED INC -- CARBON DIOXIDE, GAS

=====
MSDS Safety Information
=====

FSC: 4220
NIIN: 00-630-8714
MSDS Date: 10/19/1996
MSDS Num: CFRDV
Product ID: CARBON DIOXIDE, GAS
MFN: 01
Responsible Party
Cage: 2W134
Name: LELAND LIMITED INC
Address: LAMINGTON RD
Box: 382
City: BEDMINSTER NJ 07921-9779
Info Phone Number: 908-668-1008
Emergency Phone Number: 908-668-1008
Review Ind: Y
Published: Y

=====
Contractor Summary
=====

Cage: 2W134
Name: LELAND LTD INC
Address: 2614 S CLINTON AVE
City: SOUTH PLAINFIELD NJ 07080
Phone: 908-561-2000; 908-568-1310
Cage: 87286
Name: SPARKLET DEVICES INC
Address: 4400 GUSTINE AVE
City: ST LOUIS MO 63116-1712
Phone: 314-353-0400

=====
Item Description Information
=====

Item Manager: S9I
Unit of Issue: EA
UI Container Qty: 1

=====
Ingredients
=====

Cas: 124-38-9
RTECS #: FF6400000
Name: CARBON DIOXIDE
Other REC Limits: NONE RECOMMENDED
OSHA PEL: 5000 PPM
ACGIH TLV: 5000PPM/30000STEL;96

=====
Health

Hazards Data

LD50 LC50 Mixture: TLV IS 5000 PPM.

Route Of Entry Inds - Inhalation: YES

Skin: NO

Ingestion: NO

Carcinogenicity Inds - NTP: NO

IARC: NO

OSHA: NO

Effects of Exposure: TARGET ORGANS:LUNGS, CNS, EYES, SKIN. ACUTE- CONTACT WITH LIQUID CAN CAUSE SKIN FROSTBITE. GAS MAY CAUSE EYE IRRITATION. ASPHYXIANT. INHALATION MAY CAUSE RESPIRATORY ACIDOSIS. HIGH CONCENTRATIONS MAY CAUSE RAPID CIRCULATORY INSUFFICIENCY LEADING TO DEATH.

INGESTION IS NOT LIKELY

(GAS). CHRONIC- UNKNOWN.

Explanation Of Carcinogenicity: NONE

Signs And Symptoms Of Overexposure: EYE OR SKIN FROSTBITE AND FREEZE BURNS, HEADACHE, DROWSINESS, DIZZINESS, STINGING OF THE EYES, NOSE AND THROAT, EXCITATION, RAPID BREATHING AND HEART RATE, EXCESS SALIVATION, SHORTNESS OF BREATH, MUSCULAR WEAKNESS, RINGING IN THE EAR, UNCONSCIOUSNESS, COMA, NAUSEA, VOMITING, WATERY EYES (FORMATION OF WEAK CARBONIC ACID)

Medical Cond Aggravated By Exposure: PERSONNEL

WITH PRE-EXISTING CHRONIC

RESPIRATORY DISEASES OR HEART DISORDERS SHOULD REFRAIN FROM BREATHING EXCESSIVE CARBON DIOXIDE.

First Aid: INHALATION:REMOVE TO FRESH AIR. PROVIDE CPR/OXYGEN IF NEEDED.

EYES:IMMEDIATELY FLUSH WITH WATER FOR AT LEAST 15 MINUTES. SEE AN OPHTHALMOLOGIST, URGENTLY. SKIN:FLUSH WITH WARM WATER (NOT TO EXCEED 107 F). PROMPT MEDICAL ATTENTION IS MANDATORY IN ALL CASES OF OVEREXPOSURE TO CO2. RESCUE PERSONNEL SHOULD BE EQUIPPED WITH SELF CONTAINED BREATHING APPARATUS.

US.

ORAL:NOT LIKELY.

Handling and Disposal

Spill Release Procedures: LIQUID CARBON DIOXIDE WILL FORM SOLID CO2 (DRY ICE)

WHEN RELEASED TO ATMOSPHERIC PRESSURE. THE AREA SHOULD BE VENTILATED. CLEAN UP PERSONNEL SHOULD WEAR SELF-CONTAINED BREATHING APPARATUS WITH FULL FACE MASK AND HEAVY PROTECTIVE CLOTHING.

Neutralizing Agent: NOT RELEVANT

Waste Disposal Methods: SLOWLY RELEASE

INTO ATMOSPHERE OUTDOORS. DISPOSAL SHOULD BE IN COMPLIANCE WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS. DEFECTIVE CYLINDERS SHOULD BE TAGGED TO INDICATE A DEFECT.

Handling And Storage Precautions: STORE IN A COOL, WELL-VENTILATED PLACE. DO NOT STORE ABOVE 120F. KEEP OUT OF REACH OF CHILDREN.

Other Precautions: KEEP AWAY FROM SOURCES OF HEAT. CAUTION! CAN CAUSE RAPID SUFFOCATION DUE TO OXYGEN DEFICIENCY. USE WITH ADEQUATE VENTILATION. CO2 IS HEAVIER THAN AIR AND TENDS TO ACCUMULATE NEAR THE FLOOR IN CLOSED SPACES. READ ALL LABELS INSTRUCTIONS.

=====
Fire and Explosion Hazard Information
=====

Flash Point Text: NONE

Extinguishing Media: CARBON DIOXIDE CANNOT CATCH FIRE. USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL FOR SURROUNDING FIRE.

Fire Fighting Procedures: WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A NIOSH-APPROVED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY. EVACUATE AREA.

Unusual Fire/Explosion Hazard: THOUGH GAS CYLINDERS ARE EQUIPPED WITH PRESSURE RELIEF DEVICES, THEY SHOULD BE REMOVED FROM FIRE TO AVOID RISK OF RUPTURE.

=====
Control Measures
=====

Respiratory Protection: NONE REQUIRED UNDER NORMAL USE. HOWEVER, AIR-SUPPLIED RESPIRATORS ARE REQUIRED WHILE WORKING IN CONFINED SPACES WITH THIS PRODUCT.

THE RESPIRATORY PROTECTION USE MUST CONFORM WITH OSHA RULES AS SPECIFIED IN 29 CFR 1910.134.

Ventilation: SUFFICIENT TO PREVENT ACCUMULATION ABOVE TLV. LOCAL EXHAUST LOCATED NEAR THE FLOOR.

Protective Gloves: INSULATED AND COLD RESISTANT NEOPRENE

Eye Protection: SAFETY GOGGLES RECOMMENDED

Other Protective Equipment: EYE WASH STATION, SAFETY SHOWER, INDUSTRIAL-TYPE WORK CLOTHING, SAFETY SHOES AND APRON AS REQUIRED.

Work Hygienic Practices: OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND

RECOMMENDED PROCEDURES.

Supplemental Safety and Health: CARBON DIOXIDE CYLINDER IN LIFE PRESERVER.

=====
Physical/Chemical Properties
=====

HCC: G3

NRC/State LIC No: NOT RELEVANT

B.P. Text: -109F,-78C

M.P/F.P Text: -71F,-57C

Decomp Text: UNKNOWN

Vapor Pres: 43700@21C

Vapor Density: 1.5

Spec Gravity: 1.52

PH: ACIDIC

Evaporation Rate & Reference: NOT RELEVANT (GAS)

Solubility in Water: SOLUBLE

Appearance and Odor: COLORLESS, ODORLESS GAS WITH A SLIGHT ACIDIC TASTE.
Corrosion Rate: UNKNOWN

=====
Reactivity Data
=====

Stability Indicator: YES
Stability Condition To Avoid: OVERHEATING CYLINDERS
Materials To Avoid: (AL+NA2O2), CS2O, LITHIUM, POTASSIUM, MG(C2H5)2, (MG+NA2O),
SODIUM
Hazardous Decomposition Products: NONE
Hazardous Polymerization Indicator: NO
Conditions To Avoid Polymerization: NOT RELEVANT

=====
Toxicological Information
=====

=====
Ecological Information
=====

=====
MSDS Transport Information
=====

=====
Regulatory Information
=====

=====
Other Information
=====

=====
Transportation Information
=====

Responsible Party Code: 2W134
Trans ID NO: 80319
Product ID: CARBON DIOXIDE, GAS
MSDS Prepared Date: 10/19/1996
Review Date: 12/03/1997
MFN: 1
Multiple KIT Nu

number: 0
Review IND: Y
Unit Of Issue: EA
Container QTY: 1
Additional Data: PRODUCT IS A LIFE PRESERVER WITH CARBON DIOXIDE GAS FOR INFLATION.

=====
Detail DOT Information
=====

DOT PSN Code: ZZZ
DOT Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION
=====

Detail IMO Information
=====

=====
IMO PSN Code: ZZZ
IMO Proper Shipping Name: NOT REGULATED FOR THIS MODE OF TRANSPORTATION
=====

Detail IATA Information
=====

IATA PSN Code: ZZZ
IATA Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION
=====

Detail AFI Information
=====

AFI PSN Code: ZZZ
AFI Proper Shipping Name
: NOT REGULATED BY THIS MODE OF TRANSPORTATION
=====

HAZCOM Label
=====

Product ID: CARBON DIOXIDE, GAS
Cage: 2W134
Company Name: LELAND LTD INC
Street: 2614 S CLINTON AVE
City: SOUTH PLAINFIELD NJ
Zipcode: 07080
Health Emergency Phone: 908-668-1008
Label Required IND: Y
Date Of Label Review: 10/12/1999
Status Code: A
Origination Code: G
Hazard And Precautions: TARGET ORGANS:LUNGS, CNS, EYES, SKI

N. ACUTE- CONTACT

WITH LIQUID CAN CAUSE SKIN FROSTBITE. GAS MAY CAUSE EYE IRRITATION. ASPHYXIAN. INHALATION MAY CAUSE RESPIRATORY ACIDOSIS. HIGH CONCENTRATIONS MAY CAUSE RAPID CIRCULATORY INSUFFICIENCY LEADING TO DEATH. INGESTION IS NOT LIKELY (GAS). CHRONIC- UNKNOWN.

=====
Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense.

The Unite

d States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competen

t professional advice to verify

and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.