View NSN Online: https://aerobasegroup.gr/nsn/9150-01-386-7693

ITW DEVCON/ A DYKEM COMPANY -- 71912-0351 SAFETAP PLUS -- 9150-01-386-7693

======== Product Identification ============

Product ID:71912-0351 SAFETAP PLUS

MSDS Date:02/02/1997

FSC:9150

NIIN:01-386-7693

MSDS Number: CFRKB === Responsible Party ===

Company Name: ITW DEVCON/ A DYKEM COMPANY

Address:8501 DELPORT DRIVE

City:ST. LOUIS

State:MO

ZIP:63114-5905 Country:US

Info Phone Num:800-452-5823

Emergency Phone N

um:800-424-9300(CHEMTREC) Preparer's Name:DEBBIE MAKITA

CAGE:98148

=== Contractor Identification ===

Company Name: INDUSTRIAL SUPPLY CORP

Address:1905 WESTWOOD AVE

Box:6356

City:RICHMOND

State:VA ZIP:23230 Country:US

Phone:804-355-8041

CAGE:6A908

Company Name: ITW DYKEM/ DYMON

Address:805 E OLD 56 HWY

Box:City:OLATHE

State:KS ZIP:66061 Country:US

Phone:800-443-9536

CAGE:98148

======= Composition/Information on Ingredients ========

Ingred Name:PER MSDS:PRODUCT CONTAINS NO COMPONENTS

SUBJ TO REPORTING REQMTS OF OSHA'S HAZ COMM STD 1910.1200. Other REC Limits: NONE RECOMMENDED ============= Hazards Identification ======================== LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER. Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: INHALATION RISKS ARE UNLIKELY AT NORMAL ROOM TEMPERATURES. AT ELEVATED TEMPERATURES EYE, NOSE & THROAT IRRITATION MAY OCCUR. SKIN & EY E CONTACTS RISKS ARE SLIGHT IRRITATION. SKIN ABSORPTION RISKS ARE SLIGHT IRRITATION. INGESTION HEALTH RISKS ARE SLIGHT NAUSEA & VOMITING. CHRONIC: NO KNOWN EFFECTS. Explanation of Carcinogenicity:PER MSDS:CARCINOGENICITY:NTP/IARC/OSHA/ ACGIH:NO. Effects of Overexposure:INGESTED-NAUSEA, VOMITING. SKIN-IRRITATION. EYES-IRRITATION. INHALATION-POSSIBLE IRRITATION OF EYES, NOSE, THROAT FROM VAPORS PRODUCED AT HIGH TEMPERATURES. Medical Cond Aggravated by Exposure: SKIN DISORDE RS. First Aid:EYE-FLUSH WELL WITH WATER. CONTACT PHYSICIAN IF IRRITATION PERSISTS. SKIN-WASH WITH SOAP & WATER. INHAL-NO EMERGENCY CARE ANTICIPATED UNDER NORMAL CONDITIONS, INGEST-DO NOT INDUCE VOMITING. CONTACT PH YSICIAN. IF VOMITING OCCURS KEEP HEAD BELOW HIPS TO PREVENT ASPIRATION OF LIQUID INTO LUNGS. Flash Point Method:TCC Flash Point :>200F,>93C

Autoignition Temp: Autoignition Temp Text: NP

Lower Limits:NA **Upper Limits:NA**

Extinguishing Media:WATER, CO2, DRY CHEMICAL, FOAM, ALCOHOL FOAM.

Fire Fighting Procedures: FIRE FIGHTERS SHOULD WEAR SELF-CONTAINED BREATHING APPARATUS IN CONFINED AREAS.

Unusual Fire/Explosion Hazard:NONE.

======== Accidental Release Measures ============

Spill Release Procedures: PREVENT SKIN & EYE CONTACT. MOP UP OR USE ABSORBENT MATERIAL, WASH AREA, DISCARD IN SUITABLE CONTAINER

| S. Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER. |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| =========== Handling and Storage ============ |
| Handling and Storage Precautions:NONE SPECIFIED BY MANUFACTURER. Other Precautions:NONE SPECIFIED BY MANUFACTURER. |
| ====== Exposure Controls/Personal Protection ======== |
| Respiratory Protection:NONE REQUIRED AT NORMAL HANDLING TEMPERATURES. Ventilation:LOCAL EXHAUST IS RECOMMENDED FOR CONFINED AREAS. GENERAL MECHANICAL VENTILATION IS ADEQUATE FOR NORMAL US E. |
| Protective Gloves:CHEMICAL RESISTANT-PVC. Eye Protection:SAFETY GLASSES, SPLASH PROOF GOGGLES. Other Protective Equipment:PROTECTIVE GEAR AS REQUIRED TO MINIMIZE SKIN CONTACT. EYE BASH, SAFETY SHOWER. Work Hygienic Practices:FOLLOW CURRENT HMIS REGULATIONS. Supplemental Safety and Health NEW RECORD PRODUCED BECAUSE OF USE OF NEW/DIFFERENT MFR PART NUMBER & |
| TRADE NAME. MSDS RECEIVED PER SOLICITATION/CONTRACT NUMBER(S) SP0400-97-T6496/SP0450-97-MN625 FROM CAGE 6A908. |
| ====================================== |
| HCC:V6 Boiling Pt:B.P. Text:163F,73C Vapor Density:>1 Spec Gravity: 1.01 |

Spec Gravity:1.01 VOC Grams/Liter:.09

Evaporation Rate & Department Reference: