View NSN Online: https://aerobasegroup.com/nsn/9130-01-429-4563

Product ID: JP-8 MSDS Date:05/21/1997 FSC:9130 NIIN:01-429-4563 **MSDS Number: CFTCP** === Responsible Party === Company Name: COASTAL CORP Address:9 GREENWAY PLAZA **City:HOUSTON** State:TX ZIP:77046 Country:US Info Phone Num:713-877-1400 Emergency Phone Num:800-424-9300 (CHEMTREC) CAGE:46684 === Contractor Identification === Comp any Name: COASTAL CORP Address:9 GREENWAY PLAZA Box:City:HOUSTON State:TX ZIP:77046 Country:US Phone:713-877-6732 CAGE:46684

Ingred Name:KEROSENE CAS:8008-20-6 RTECS #:OA5500000 Fraction by Wt: 100% OSHA PEL:N/K ACGIH TLV:N/K

Ingred Name:OTHER PREC: CANCER, BIRTH DEFECTS/OTHER REPRO HARM MAY BE FOUND IN CRUDE OIL & PETRO PRODS. ALTHOUGH IT IS POSS (ING 3) RTECS #:9999999ZZ

Ingred Name: ING 2: TO SUFFICIENTLY REFINE CRUD

E OIL/ITS END PRODS TO REMOVE POTENTIAL FOR CANCER, MFR ADVISES THAT ONE/MORE (ING 4) RTECS #:9999999ZZ Ingred Name: ING 3: OF LISTED CHEMS MAY BE PRESENT IN SOME DETECTABLE QTYS. READ & FOLLOW DIRECTIONS & USE CARE WHEN HNDLG (ING 5) RTECS #:9999992Z Ingred Name: ING 4: CRUDE OIL AND PETROLEUM PRODUCTS. RTECS #:9999992Z LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER. Routes of Entry: Inhalation:YES Skin:YES Ing estion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: ACUTE: EYES: SLIGHTLY TO MOD IRRIT. SKIN: MOD IRRIT. MAY CAUSE REDNESS & DRYING OF SKIN. INHAL: IRRIT TO MUC MEMB & RESP TRACT. MAY CAUSE HDCH, DIZZ, NAUS, VOMIT, LOSS OF CONSCIOUSNESS. INGEST: CAN BE IRRIT TO MOUTH, THROAT & DIGESTIVE TRACT. MAY CAUSE DROW & DMG TO LIVER & KIDNEYS. ASPIR INTO LUNGS (EFTS OF OVEREXP) Explanation of Carcinogenicity:NOT RELEVANT. Effects of Overexp osure:HLTH HAZ: MAY CAUSE HEMORRHAGING, PULM EDEMA, & CHEM PNEUMONITIS. CHRONIC: MAY CAUSE REDUCTION OF ERYTHROCYTES, MARROW HYPOPLASMIA, & CHANGES IN FORMED ELEMENTS OF BLOOD. MIDDLE DISTILS HAVE CAUSED KI DNEY DMG & SKIN CANCER IN LAB ANIMALS. IARC HAS DETERMINED THERE IS SUFFICIENT EVIDENCE OF CARCIN IN HUMANS. (SUP DAT) Medical Cond Aggravated by Exposure: MAY AGGRAVATE PREEXISTING DERMATITIS.

First

Aid:EYE: IMMED FLUSH THORO W/LGE AMTS OF WATER FOR AT LEAST 15 MIN, INCL UNDER EYELIDS. CONT MD IMMED, PREF OPHTHALMOLOGIST. SKIN: IMMED REMOVE CONTAM CLTHG & SHOES. WASH AFFECTED AREAS W/SOAP & WATER. CO NT MD IF REDDENING/BLISTERING OCCURS. INHAL: REMOVE TO FRESH AIR. APPLY ARTF RESP IF NOT BRTHG. GET MED ATTN. INGEST: DO NOT INDUCE VOMIT. IF SPONT VOMIT OCCURS, HOLD VICTIM'S HEAD LOWER (SUP DAT)

ash Point:>100F,>38C

Extinguishing Media:DRY CHEMICAL, CARBON DIOXIDE, FOAM OR WATER SPRAY. Fire Fighting Procedures:WEAR NIOSH APPRVD SCBA & FULL PROT EQUIP . USE WATER SPRAY TO COOL FIRE-EXPOSED CONTRS. USE SMOTHERING TECHNIQUE FOR EXTING FIRE. DO NOT USE A (SUP DAT)

Unusual Fire/Explosion Hazard:FLOWING FUEL CAN BE IGNITED BY SELF-GENERATED STATIC ELECTRICITY; CONTAINERS SHOULD BE GROUNDED AND BONDED.

Spill

Release Procedures:REMOVE SOURCES OF HEAT OR INGITION INCLUDING INTERNAL COMBUSTION ENGINES AND POWER TOOLS. CLEAN UP SPILL, BUT DO NOT FLUSH TO SEWER OR SURFACE WATER. VENTILATE AREA AND AVOID BREATHING VAPORS OR MISTS.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling and Storage Precautions:STORE IN COOL, DRY AREA AWAY FROM INCOMPATIBLE SOURCES OF HEAT & IGNIT. EMPTY CONTR MAY CONTAIN RESIDUE

(LIQ &/VAP) & CAN BE DANGEROUS.

Other Precautions: GROUND & BOND ALL TRANSFER & STOR EQUIP TO PVNT STATIC SPKS & EQUIP W/SELF-CLOSING VALVES, PRESS VACUUM BUNGS & FLAME ARRESTORS. DO NOT WELD, HEAT/DRILL CONTR. CAL PROP 65 WARNING: CHEMS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE (ING 2)

Respiratory Protection: USE NIOSH APPROVED RESPIRATORY PROTECTION EQUIPMENT IN SITUATIONS WHERE AIRBORNE CONCENTRATIONS MAY EXC EED

OCCUPATIONAL EXPOSURE LEVELS.

Ventilation:PROVIDE ADEQ VENT: (1) TO MEET OCCUP EXPOS LIMS; (2) TO PVNT FORM OF EXPLO ATM; (3) TO PVNT OXYGEN DEFICIENT (SUP DAT)

Protective Gloves: IMPERVIOUS GLOVES.

Eye Protection: ANSI APPRVD CHEM WORKERS GOGGLES .

Other Protective Equipment: ANSI APPRVD EMER EYEWASH & DELUGE SHOWER . WEAR IMPERVIOUS APRON, LONG SLEEVES, BOOTS & FSHLD WHEN HNDLG LGE AMTS.

Work Hygienic Practices:REMOVE CONTACT LENSES. Supplemental Safety and Health FIRE FIGHT P ROC: FORCED WATER STREAM DIRECTLY ON PETRO FIRES AS THIS MAY SCATTER FIRE. EFTS OF OVEREXP: INHAL OF JP-8 BY PREGNANT LAB RATS HAS CAUSED REDUCTION IN FETAL BODY WEIGHT. FIRST AID PROC: TH AN HIPS TO PVNT ASPIR. GET MED ATTN. VENT: ATMS, ESP IN CONFINED SPACES.

Boiling Pt:B.P. Text:>401F,>205C Spec Gravity:0.78-0.84 Solubility in Water:INSOLUBLE Appearance and Odor:CLEAR TO LIGHT AMBER LIQUID; MILD PETROLEUM O DOR Percent Volatiles by Volume:100

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:HEAT, SPARKS, FLAME AND BUILD-UP OF STATIC ELECTRICITY.

Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE, AND HYDROCARBONS.

Waste Disposal Methods:DISPOSE THROUGH A LICENSED WASTE DISPOSAL COMPANY. F OLLOW FEDERAL, STATE, AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.