

GC THORSEN -- RED X CORONA DOPE, 10-5002 -- 8040-00-779-2863

=====
Product Identification
=====

Product ID:RED X CORONA DOPE, 10-5002

MSDS Date:03/04/1997

FSC:8040

NIIN:00-779-2863

MSDS Number: CFTYP

=== Responsible Party ===

Company Name:GC THORSEN

Address:1801 MORGAN ST

City:ROCKFORD

State:IL

ZIP:61105

Country:US

Info Phone Num:815-968-9661

Emergency Phone Num:815-968-9661

Preparer's Name:M. WI

NSEL

CAGE:EO177

=== Contractor Identification ===

Company Name:GC THORSEN

Address:1801 MORGAN STREET

Box:City:ROCKFORD

State:IL

ZIP:61105

Country:US

Phone:815-968-9661

CAGE:72653

Company Name:GC THORSEN

Address:1801 MORGAN STREET

Box:1209

City:ROCKFORD

State:IL

ZIP:61105-1209

Country:US

Phone:815-968-9661

CAGE:EO177

=====
Composition/Information on Ingredients
=====

Ingred Name:LIGROINE; (VM&P NAPHTHA)

CAS:8032-32-4

RTECS #:OI6180000

Fraction by Wt: 34%

OSHA PEL:300 PPM

ACGIH

TLV:300 PPM

Ingred Name:XYLENE (SARA 313) (CERCLA)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 15%

OSHA PEL:100 PPM

ACGIH TLV:100 PPM;150 STEL

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:ISOPROPYL ALCOHOL (SARA 313)

CAS:67-63-0

RTECS #:NT8050000

Fraction by Wt: 1.5%

OSHA PEL:400 PPM

ACGIH TLV:400 PPM;500 STEL

Ingred Name:POLYESTER RESIN; (IRON OXIDE)

Fraction by Wt: 49%

OSHA PEL:N/K

ACGIH TLV:N/K

=====
===== Hazards Identification =====

LD50 LC5

0 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INFLAMMATION OF MUCOUS MEMBRANES AND
RESPIRATORY TRACT, DERMATITIS, BREATHING DIFFICULTY, LOSS OF
APPETITE, NAUSEA, VOMITING, HEADACHE, DIZZINESS, UNCOORDINATION,
NARCOSIS, PARTIAL PARALYSIS.

Explanation of Carcinogenicity:NOT RELEVANT

Effects of Overexposure:SEE HEALTH HAZARDS.

Medical Cond Aggravated

by Exposure:PERSONS W/DISEASE OF THE LIVER,
KIDNEYS, BLOOD OR NERVOUS SYSTEM.

=====
===== First Aid Measures =====

First Aid:EYES:FLUSH W/WATER FOR AT LEAST 15 MINUTES - CONSULT MD.
SKIN:WASH W/SOAP & WATER. INHAL:FRESH AIR, OXYGEN, ARTIFICIAL
RESPIRATION. INGEST:DO NOT INDUCE VOMITING - GASTRIC LAVAGE -
CONSULT MD.

=====
===== Fire Fighting Measures =====

Flash Point Method:OC

Flash Point:50.0F,10.0C

Lower Limits:2

%

Upper Limits:12%

Extinguishing Media:CO*2, CHEMICAL FOAM, DRY CHEMICAL.

Fire Fighting Procedures:USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT . WATER MAY BE INEFFECTIVE EXCEPT FOR COOLING CONTAINERS.

Unusual Fire/Explosion Hazard:DUE TO FLASH POINT - CONTAINERS MAY EXPLODE UNDER HIGH HEAT OR FIRE CONDITIONS.

===== Accidental Release Measures =====

Spill Release Procedures:VENTILATE AREA (AVOID BREATHING VAPORS) - PICK UP W/INERT ABSORBENT MATERIAL - STORE IN SEALED METAL CONTAINERS.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP FROM HEAT OR IGNITION SOURCES.

Other Precautions:PROVIDE GOOD VENTILATION.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:FOR LARGE SPILLS:NIOSH APPROVED SELF CONTAINED BREATHING APPARATUS (SCBA).

Ventilation:MECHANICAL AS REQUIRED TO MEET TLV'S.

Protective

Gloves:RUBBER GLOVES.

Eye Protection:ANSI APPROVED CHEM WORKERS GOGGLES(SUPDAT)

Other Protective Equipment:EYE WASH FOUNTAIN & DELUGE SHOWER WHICH MEET ANSI DESIGN CRITERIA . RUBBER APRON AS REQUIRED.

Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health

EYE PROT:& FULL LENGTH FACESHIELD .

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:230F,110C

Vapor Density:4

Spec Gravity:1

VOC Pounds/Gallon:505

Solubility in

Water: