

HAYNES INTERNATIONAL INC SUB OF CABOT CORP -- H3095-0 ALLOYS, HASTELLOY X ALLOY
N06002 -- 3439-01-031-5253

=====
Product Identification
=====

Product ID:H3095-0 ALLOYS, HASTELLOY X ALLOY N06002
MSDS Date:09/01/1993
FSC:3439
NIIN:01-031-5253
MSDS Number: CFVWS
=== Responsible Party ===
Company Name:HAYNES INTERNATIONAL INC SUB OF CABOT CORP
Address:1020 W PARK AVE
Box:9013
City:KOKOMO
State:IN
ZIP:
46902-9013
Country:US
Info Phone Num:317-456-6625
Emergency Phone Num:800-424-9300(CHEMTREC)/317-456-6894
Preparer's Name:SAFETY DEPT
CAGE:80357

==== Contractor Identification ====

Company Name:HAYNES INTERNATIONAL INC SUB OF CABOT CORP
Address:1020 W PARK AVE
Box:9013
City:KOKOMO
State:IN
ZIP:46904-9013
Country:US
Phone:318-263-2002;765-456-6614
CAGE:80357

=====
Composition/Information on Ingredients
=====

Ingred Name:BORON (% IS MAX AMT)
CAS:7440-42-8
RTECS #:ED7350000
Fracti

on by Wt: 0.008%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:10 MG B2O3/M3
ACGIH TLV:10 MG B2O3/M3

Ingred Name:COBALT (SARA 313)
CAS:7440-48-4
RTECS #:GF8750000
Fraction by Wt: 1.5%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:0.1 MG/M3
ACGIH TLV:0.02 MG/M3; A3; 9596

Ingred Name:CHROMIUM (SARA 313) (CERCLA)
CAS:7440-47-3
RTECS #:GB4200000
Fraction by Wt: 22%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:1 MG/M3
ACGIH TLV:0.5 MG/M3; 9596
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:IRON
CAS:7439-89
-6
RTECS #:NO4565500
Fraction by Wt: 18%
Other REC Limits:NONE RECOMMENDED

Ingred Name:MANGANESE (SARA 313)
CAS:7439-96-5
RTECS #:OO9275000
Fraction by Wt: 1% MAX
Other REC Limits:NONE RECOMMENDED
OSHA PEL:C, 5 MG/M3 (FUME)
ACGIH TLV:0.2 MG/M3; 9596

Ingred Name:MOLYBDENUM
CAS:7439-98-7
RTECS #:QA4680000
Fraction by Wt: 9%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:10 PPM.
ACGIH TLV:10 PPM.

Ingred Name:NICKEL (SARA 313) (CERCLA)
CAS:7440-02-0
RTECS #:QR5950000
Fraction by Wt: 47%
Other REC Lim

its:NONE RECOMMENDED
OSHA PEL:1 MG/M3
ACGIH TLV:1 MG/M3; 9596

Ingred Name:SILICON
CAS:7440-21-3
RTECS #:VW0400000
Fraction by Wt: 1% MAX
Other REC Limits:NONE RECOMMENDED
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9596

Ingred Name:TUNGSTEN,AS W,SOLUBLE COMPOUNDS.
CAS:7440-33-7
RTECS #:YO7175000
Fraction by Wt: 0.6%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:NOE ESTABLISHED
ACGIH TLV:1 MG/M3/3 STEL; 9596

===== Hazards Identification =====

LD50 LC50 Mix
ture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES
Health Hazards Acute and Chronic:INHAL:METAL DUST/FUME/POWDER MAY
RESULT FROM MELT/DROSS HNDLG/CAST/WELD/THERM
CUT/FRINK/CRUSH/SIMILAR OPERATIONS WHICH GENERATE AIRBORNE METAL
PARTICULATE DURING MATLS USE.INGEST:HAND/CLOTH/FOOD/DRINK CONTACT
W/METAL DUST/FUME/POWDER CAN CAUSE PARTICULATE INGEST DURING HAND
TO MOUTH ACTIVITIES
(DRINK/SMOKE/(SUPPLEMENTA)
Explanation of Carcinogenicity:PER MSDS:CR(VI)/NI CMPDS CARC BY
OSHA/IARC/NTP.WELD FUME/CO CARC BY OSHA/IARC.CHEMS KNOWN TO STATE
OF CALIFORNIA CARC.
Effects of Overexposure:INGREDS METAL DUST/FUME IRRIT SKIN/EYE/MUC
MEMB.CR/CO/CU/NI CONTACT CAUSE ALLERGIC SKIN RX.IRRIT
SKIN/DERM,INJURY TO EYE FRM IRRIT/MECHAN INJURY TO CORNEA/CONJ BY
DUST/PARTIC.EXCESS AL,CO,CU,MN,NI RES P
IRRIT,COUGH,BRON,CHILLS,FUME FEVER,ASTHMA-LIKE SYMPT.RESP
DISEASE,CN

S DEPRESS,GI DISORDER,LUNG CHANGES.

Medical Cond Aggravated by Exposure:ALLERGIC RX/SENS TO METALS
ENCOUNTER SKIN RASH/DERM.IMPAIRED PULM FUNCTION/AIRWAY
DISEASE/CONDITIONS LIKE ASTHMA,EMPHY,CHRONIC BRON,ETC FURTHER
DISABILITY.NERV,CIRC,BLOOD,KID DMG/DISEASE NEED SCREENIG

===== First Aid Measures =====

First Aid:INHAL:BREATH DIFFI MOVE TO FRESH AIR.STOP BREATH PERFORM ART
RESP.GET MED ATTN IMMED.INGGEST:SWALLOW LG QUANT OF WATER,ATTEMPT

TO INDUCE VOMIT IF CONSC.GET MED ATTN IMMED.SKIN:CUT/ABRASION TREAT
BY ST D 1ST AID:CONTAM REMOVE BY WASHING W/SOAP/WATER.IRRIT PERSIST
GET MED ATTN.EYE:FLUSH W/COPIOUS AMTS OF CLEAN WATER.IRRIT PERSIST
GET MED ATTN.CONTACT LENSES SHOULDNT BE WORN WHEN WORK W/METAL
DUST/POWD

===== Fire Fighting Measures =====

Flash Point:NONE

Autoignition Temp:Autoignition Temp Text:NP

Lower Limits:NONE

Upper Limits:NONE

Extinguishing Media:THESE ALLOYS ARE NON

-COMBUSTIBLE.USE EXTINGUISHING

MEDIA APPROPRIATE TO SURROUNDING FIRE.

Fire Fighting Procedures:IF THESE MATLS REDUCED TO POWDER FORM CAUT
MUST BE USED TO PREVENT FIRE/EXPLO.TO EXT METAL POWDER FIRE USE DRY
SAND,DRY GRAPHITE,OTHER CLASS D FIRE EXT POWDER.

Unusual Fire/Explosion Hazard:NO USUSUAL FIRE OR EXPLO HAZARDS ARE
ASSOCIATED WITH THESE MATLS.

===== Accidental Release Measures =====

Spill Release Procedures:SOLID FORM MATL POSE NO SPEC CLEANUP

PROBLEMS.MATL POWDER/DUST FORM CLEANUP SHOULD BE CONDUCTED W/VACUUM
SYS UTILIZING HEPA FILT SYS.CAUT SHOULD BE TAKEN TO MIN AIRBORNE
GENERATION OF POWDER/DUST,AVOID CONTAM OF AIR/WATER.PROPERLY LABEL
COLLECT MATL.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:HNDL ACCORDING TO
SIZE/SHAPE/QUANT.SOLID-USE HOIST,CRANE,ETC.POWDER-SPILL/RELEASE
POT.SOLID NO SPEC STORAGE

PROBLEM.STORE METAL/POWDER IN DRY AREA.

Other Precautions:DONT STORE ADJ TO MINERAL ACIDS.KEEP FINE METAL POWDER AWAY FLAME/IGN.EXPO TO ELEMENTS BEST DETERMINE BY AIR SMPLS FRM WORKER BREATH ZONE/WORK AREA/DEPT.LUNG FUNCT TEST/CHEST X-RAY/ROUTINE PHYS EXAM U SEFUL-DETERMINE EFFEFT OF DUST/FUME EXPO

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH APPROV RESP AS SPEC BY INDUSTR HYG/QUAL SAF PROF.LUNG FUNCTION TESTS RECOMMENDED FOR USERS OF NEG PRESSURE

DEVICES.USE FUME RESP OR AIR SUPPL RESP WHERE LOC EXHAU/VENTI DOESNT KEEP EXPO BEL OSHA LIMITS FOR AIR CONTAMINANTS.

Ventilation:LOC EXHAU VENTI SHOULD BE USED TO CONTROL EXPO TO AIRBORNE DUST & FUME WHENEVER POSSIBLE.

Protective Gloves:GLOVES PREVENT METAL CUT/SKIN ABRASIONS

Eye Protection:SAF GLASSES WHEN RISK OF EYE INJURY PRES

Other Protective Equipment:POT CLOTH(UNIFORMS,DISPO COVERALLS,SAF SHOES,ETC)MAY BE REQUIRED DURING METAL HDNLG OPERATIONS AS APP ROP

TO EXPO CIRCUM.

Work Hygienic Practices:CONTAINS SEC 313 EPCRA CHEMS.HEALTH HAZ INFO GIVEN IN MSDS H-1072 FOR WELDING PRODUCTS ALSO APPLY.

Supplemental Safety and Health

HEALTH:NAIL BITE,ETC).SKIN:CONTACT MAY CAUSE IN SOME SENS PEOPLE ALLERGIC RESPONSE IF ELEMENTS LIKE CR,CO,CU,NI PRESENT.METAL DUST/POWDER CONTACT/ABRASION CAUSE IRRIT,DERM.EYE:PARTICU METAL DANGEROUS TO EYE/SURROUNDING TISSUE.AIRBORNE PARTIC POT PROBLEM AS WELL AS INSERTING FINGER INTO EYE IF HAND/CL OTH CONTAM W/PARTIC

=====
===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:NA

Melt/Freeze Pt:M.P/F.P Text:-2300F,-129

Decomp Temp:Decomp Text:NP

Vapor Pres:NA

Vapor Density:NA

Spec Gravity:0.297=DENSITY

pH:NP

Viscosity:NP

Evaporation Rate & Reference:NA

Solubility in Water:NONE

Appearance and Odor:SOLID-SILVER GRAY COLOR, NO ODOR

Percent Volatiles by Volume:NONE

Corrosion Rate:NP

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

AVOID CONTACT W/MINERAL ACIDS & OXIDIZING AGENTS WHICH MAY GENERATE HYDROGEN GAS; EVOLUTION OF HYDROGEN MAY BE EXPLO HAZ.

Stability Condition to Avoid: NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products: VAR ELEMENTAL METALS/METAL OXIDES MAY BE GENERATED FRM WELD/CUT/GRIND/MELT/DROSS HANDLING OPERATIONS.

===== Disposal Considerations =====

Waste Disposal Methods: WASTE MATERIAL DISPOSE IAW STATE/FED REGS. SPEC LABEL/PKG/STORAGE/TRANSPORT/DISPOSE PROCEDURES CALL ENVIRONMENTAL ENGINEER/CONSULTANT FAMILIAR W/WASTE DISPOSE REGS. SOLID NO SPEC ENVIRONMENTAL PROBLEMS; POWDER/DUST SIGNIFICANT IMPACT ON AIR/WATER QUALITY. CONTROL EMISSIONS/SPILLS/RELEASES.

=====

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.