

JAD CHEMICAL CO. INC. -- MA-110 RTU (SS2110) -- 6850-01-370-5244

=====
Product Identification
=====

Product ID:MA-110 RTU (SS2110)
MSDS Date:05/30/1997
FSC:6850
NIIN:01-370-5244
MSDS Number: CFYGY
=== Responsible Party ===
Company Name:JAD CHEMICAL CO. INC.
Box:6786
City:RANCHO PALDS VERDES
State:CA
ZIP:90734
Country:US
Info Phone Num:310-833-7457
Emergency Phone Num:310-833-7457
Preparer's Name:D
ENNIS E. MCEWAN
CAGE:0KRV1
=== Contractor Identification ===
Company Name:JAD CHEMICAL CO. INC.
Address:34 MIRALESTE PLZ
Box:City:PALOS VERDES PENINSULA
State:CA
ZIP:90274-6586
Country:US
Phone:310-833-7457 /FAX: 310-543-3240
CAGE:0KRV1

=====
Composition/Information on Ingredients
=====

Ingred Name:NONE
Other REC Limits:NONE RECOMMENDED

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carc

inogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:TARGET ORGANS: LUNGS AND RESPIRATORY TRACT. EYES- MAY CAUSE SLIGHT TEMPORARY IRRITATION. SKIN- NO EVIDENCE OF ADVERSE EFFECTS. INHALATION- BELIEVED TO BE MINIMALLY IRRITATING. INGESTION- AMOUNTS IN GESTED INCIDENTAL TO INDUSTRIAL HANDLING ARE NOT LIKELY TO CAUSE INJURY.

Effects of Overexposure:NONE

Medical Cond Aggravated by Exposure:NO MEDICAL CONDITIONS KNOWN.

=====
===== First Aid Measures
=====

First Aid:GET MEDICAL HELP IF SYMPTOMS PERSIST. INHALED:REMOVE TO FRESH AIR. PROVIDE CPR/OXYGEN IF NEEDED. EYES:FLUSH WITH WATER FOR 15 MINUTES, HOLDING EYELIDS OPEN. SKIN:WASH WITH SOAP & WATER. ORAL:DO NOT INDUCE VOMITING. IF CONSCIOUS, RINSE MOUTH WITH WATER. SEEK IMMEDIATE MEDICAL ATTENTION. IF SPONTANEOUS VOMITING OCCURS, KEEP HEAD BELOW HIPS TO PREVENT ASPIRATION OF VOMITUS INTO LUNGS.

=====
===== Fire Fighting Measures =====
=====

Flash Point Method:TCC

Flash Point:>200F,>93C

Autoignition Temp:Autoignition Temp Text:>200F

Lower Limits:NO

Upper Limits:NO

Extinguishing Media:DRY CHEMICAL, FOAM, CARBON DIOXIDE, WATER SPRAY OR FOG.

Fire Fighting Procedures:WEAR GOGGLES AND SELF-CONTAINED BREATHING APPARATUS. USE WATER TO KEEP FIRE-EXPOSED CONTAINERS COOL AND TO FLUSH SPILLS AWAY FROM FIRE.

Unusual Fire/Explosion Hazard:COOL SURROUNDING EQUIPMENT AND STRUCTURES WITH WATER IF INVOLVED IN A LARGE FIRE.

E.

=====
===== Accidental Release Measures =====

Spill Release Procedures:MOP OR SWEEP UP SPILLED MATERIAL AND DISPOSE OF IN DOT-APPROVED WASTE CONTAINERS. FLUSH SPILL AREA TO SEWER WITH WATER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:TRAIN ALL EMPLOYEES ON ALL SPECIAL HANDLING PROCEDURES. AVOID BREATHING VAPORS. KEEP PRODUCT IN A COOL SHADED LOCATION. KEEP CONTAINER CLOSED.

Other Precautions:NO

NE

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE A NIOSH-APPROVED CANISTER-TYPE RESPIRATOR,
IF NEEDED.

Ventilation:USE MECHANICAL VENTILATION, IF NECESSARY. LOCAL EXPLOSION
PROOF EXHAUST VENTILATION MAY BE NECESSARY FOR SOME OPERATIONS

Protective Gloves:IMPERMEABLE GLOVES

Eye Protection:NO CONTACT LENSES. USE SAFETY GLASSES.

Other Protective Equipment:SAFETY SHOWERS, EYE WASH AND PROPER FIRE
EXTINGUISHERS.

Work Hygienic Practices:NON

E

Supplemental Safety and Health

NONE

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:>200F,>93C

Melt/Freeze Pt:M.P/F.P Text:NO

Spec Gravity:1.004

pH: