View NSN Online: https://aerobasegroup.gr/nsn/9150-01-178-1221

SHELL OIL COMPANY -- ALVANIA EP GREASE 00,A 12377-1 -- 9150-01-178-1221

Product ID:ALVANIA EP GREASE 00,A 12377-1

MSDS Date:08/04/1994

FSC:9150

NIIN:01-178-1221

MSDS Number: CGLVG === Responsible Party ===

Company Name: SHELL OIL COMPANY

Address: HEALTH, SAFETY AND ENVIRONMENT

Box:4320

City:HOUSTON

State:TX ZIP:77210 Country:US

Info Phone Num:713-241-4819/4141/2252

FAX -6511

Emergency Phone Num:713-473-9461/800-424-9300(CHEMTREC)

CAGE:54527

=== Contractor Identification === Company Name: COMPTECH CORP Address:15944 DERWOOD RD

Box:City:ROCKVILLE

State:MD ZIP:20855 Country:US

Phone:800-284-5279; 301-519-3401

CAGE:0BR38

Company Name: COOPER POWER TOOLS

Address:670 INDUSTRIAL DRIVE

Box:1410

City:COLUMBIA

State:SC

ZIP:29071-1410

Country:US

Phone:803-359-1200

CAGE:24047

Company Name: SHELL OIL COMPANY

Address:Box:2463 City:HOUSTON

State:TX ZIP:77210 Country:US

Pho

ne:800-231-6950 CAGE:54527

======= Composition/Information on Ingredients ========

Ingred Name: MINERAL OIL, HYDROTREATED (MILD), HEAVY NAPHTHENIC

DISTILLATE, PETROLEUM

CAS:64742-52-5 RTECS #:PY8035000 Fraction by Wt: 80 - 82%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:5 MG/M3 AS OIL MIST ACGIH TLV:5 MG/M3 AS OIL MIST

Ingred Name: SOLVENT REFINED HYDROTREATED RESIDUAL OIL

CAS:64742-57-0 Fraction by Wt: 5 - 8%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:5 MG/M3 AS OIL MIST

ACGIH

TLV:5 MG/M3 AS OIL MIST

Ingred Name: SULFURIZED FATTY MATERIAL

CAS:61790-49-6 Fraction by Wt: 4%

Other REC Limits: NONE RECOMMENDED

Ingred Name:LITHIUM 12-HYDROXYSTEARATE

CAS:7620-77-1

Fraction by Wt: 2 - 3%

Other REC Limits: NONE RECOMMENDED

Ingred Name:ZINC NAPHTHANATE

CAS:12001-85-3 RTECS #:QK9275000 Fraction by Wt: 1 - 2%

Other REC Limits: NONE RECOMMENDED

Ingred Name: OTHER ADDITIVES

Fraction by Wt: 5000 MG/KG(64742-52-5)

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO

Reports of Carcin

ogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:TARGET ORGANS:EYE, SKIN. ACUTE- MILDLY IRRITATING TO EYES. PROLONGED/REPEATED SKIN CONTACT CAUSES DERMATITIS, FOLLICULITIS/OIL ACNE. INJECTION UNDER SKIN CAUSES LOCAL NECROSIS. INHALATION OF VAPORS (G ENERATED AT HIGH TEMPERATURES ONLY) MAYCAUSE IRRITATION. SLIGHTLY TOXIC IF INGESTED. CHRONIC- DERMATITIS.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:IRRITATION, NAUSEA, VOMITING, TISSUE DAMAGE

FEW HOURS AFTER HIGH PRESSURE INJECTION

Medical Cond Aggravated by Exposure:PERSONS WITH PRE-EXISTING SKIN DISORDERS MAY BE MORE SUSCEPTIBLE TO THE EFFECTS OF THIS PRODUCT.

First Aid:CALL A DOCTOR IF SYMPTOMS OCCUR. EYE:FLUSH WITH WATER. HOLD EYELIDS OPEN. SKIN:WIPE EXCESS OFF. WASH SKIN WITH SOAP & WATER OR A WATERLESS HAND CLEANER FOLLOWED BY SOAP & WATER. IF MATERIAL IS INJECTE D UNDER SKIN, GET MEDIC

AL ATTENTION PROMPTLY. DO NOT WAIT

FOR SYMPTOMS TO DEVELOP. INHALED:MOVE TO FRESH AIR. PROVIDE OXYGEN IF NEEDED. ORAL:DO NOT INDUCE VOMITING. GET MEDICAL ADVICE.

========= Fire Fighting Measures ============

Flash Point Method:PMCC

Flash Point:415F,213C

Extinguishing Media:WATER FOG, FOAM, DRY CHEMICAL/CARBON DIOXIDE. DON'T USE DIRECT STREAM OF WATER. PRODUCT WILL FLOAT AND CAN BE REIGNITED.

Fire Fighting Procedures:DO NOT ENTER ANY ENCLOSED OR CONFINED A

WITHOUT PROPER PROTECTIVE EQUIPMENT AND NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard: CONTAINER MAY RUPTURE. COOL CONTAINERS WITH WATER SPRAY.

======== Accidental Release Measures ===========

Spill Release Procedures:SCOOP UP EXCESS GREASE, WIPE UP WITH RAGS, PICK-UP RESIDUE WITH NON-FLAMMABLE ABSORBENT MATERIAL SUCH AS DIATOMACEOUS EARTH, SAND OR VERMICULITE. SWEEP UP AND TRANSFER TO A CONTAINER FOR PROPER DISPO

S AL. CLEAN AREA WITH APPROPRIATE CLEANER.
Neutralizing Agent:NOT RELEVANT
======================================
Handling and Storage Precautions:STORE IN A DRY PLACE AWAY FROM OPEN FLAMES AND STRONG OXIDIZING AGENTS. KEEP CONTAINER CLOSED. Other Precautions:"EMPTY" CONTAINERS RETAIN RESIDUE. ALL PRECAUTIONS SHOULD BE OBSERVED. WASH THOROUGHLY AFTER HANDLING. KEEP OUT OF REACH OF CHILDREN. AVOID REPEATED SKIN CONTACT. DO NOT GET IN EYES. LAUNDE R CONTAMINA TED CLOTHING BEFORE REUSE.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:NONE SHOULD BE NEEDED. Ventilation:USE ADEQUATE VENTILATION TO KEEP OIL MISTS OF THIS MATERIAL BELOW APPLICABLE STANDARD(S). Protective Gloves:NITRILE IF FREQUENT CONTACT EXPECTED Eye Protection:SAFETY GOGGLES/GLASSES RECOMMENDED Other Protective Equipment:EYE BATH, WASHING FACILITIES Work Hygienic Practices:OBSERVE GOOD INDUSTRIAL HYGIENE PRACTICES AND RECO MMENDED PROCEDURES. WASH BEFORE EATING OR DRINKING. Supplemental Safety and Health PREVIOUS NAME: SHELL ALVANIA EP LF GREASE R00
========= Physical/Chemical Properties ==========
HCC:V6 NRC/State Lic Num:NOT RELEVANT Melt/Freeze Pt:M.P/F.P Text:401F,205C Solubility in Water:INSOLUBLE Appearance and Odor:BROWN SMOOTH GREASE - SLIGHT HYDROCARBON ODOR
========== Stability and Reactivity Data ===========
Stability Indicator/Materials to Avoid:YES STRONG OXIDIZIN

G AGENTS

Stability Condition to Avoid:EXTREME HEAT, OPEN FLAMES
Hazardous Decomposition Products:A COMPLEX MIXTURE OF AIRBORNE SOLID,
LIQUID, PARTICULATES & GASES WILL EVOVLE. CARBON MONOXIDE & OTHER
COMPD. MAY FORM.

======= Disposal Considerations ==========

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL STATE AND FEDERAL LAWS. REUSING OR RECYCLING IS RECOMMENDED.

Disclaimer (provided with this information by the compiling agencies): This in

formation is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.