

CAAP COMPANY INC. (REPLACING 60922) -- CAAPCOAT POLYURETHANE CURING AGENT --
8010-00-459-1756

===== Product Identification =====

Product ID:CAAPCOAT POLYURETHANE CURING AGENT

MSDS Date:04/01/1996

FSC:8010

NIIN:00-459-1756

Kit Part:Y

MSDS Number: CGNFG

=== Responsible Party ===

Company Name:CAAP COMPANY INC. (REPLACING 60922)

Address:152 PEPES FARM ROAD

City:MILFORD

State:CT

ZIP:06460

Country:US

I

Info Phone Num:203-877-0375/202-483-7616(COLLECT)

Emergency Phone Num:203-877-0375/800-424-9300(CHEMTREC)

CAGE:LO401

=== Contractor Identification ===

Company Name:CAAP CO INC

Address:152 PEPE'S FARM RD

Box:City:MILFORD

State:CT

ZIP:06460

Country:US

Phone:203-877-0375

CAGE:60922

Company Name:CAAP CO INC

Address:152 PEPES FARM ROAD

Box:City:MILFORD

State:CT

ZIP:06460

Phone:(203) 877-0375

CAGE:6P753

Company Name:CAAP COMPANY INC. (REPLACING 60922)

Address:152 PEPES FARM ROAD

City:MILFORD

State:CT

Z

IP:06460
Country:US
Phone:203-877-0375/202-483-7616(COLLECT)
CAGE:LO401

=====
===== Composition/Information on Ingredients =====

Ingred Name:METHYLISOBUTYLKETONE (HEXONE) (SARA 313) (CERCLA)
CAS:108-10-1
RTECS #:SA9275000
Fraction by Wt: 35%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:50 PPM/75 STEL
ACGIH TLV:50 PPM/75 STEL
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ALIPHATIC AMINE
Fraction by Wt: 65%
Other REC Limits:NONE RECOMMENDED
ACGIH TLV:0.5PPM;5MG/M3WEEL

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYE: BURNING. SKIN: IRRITATION,
DEFATTING, DERMATITIS, SENSITIZATION. INHAL: RESPIRATORY
IRRITATION, NEURO IMPAIRMENT, KIDNEY/LIVER DAMAGE, HEADACHE, DIZZY,
THROAT IRRITATION, LOSS OF APPETITE, NAUSEA .
Effects of Overexposure:CONTACT: CORROSIVE ACCORDING TO D.O.T.
CORROSIVITY
TEST. MAY CAUSE IRRITATION OF SKIN, BURNING OF SKIN OR
EYES.
Medical Cond Aggravated by Exposure:PRE-EXISTING ALLERGIES, EYE, SKIN
AND RESPIRATORY DISORDERS.

=====
===== First Aid Measures =====

First Aid:INHAL: REMOVE TO FRESH AIR. PROVIDE CPR/OXYGEN IF NEEDED.
EYE: FLUSH W/WATER FOR 15 MINUTES, HOLDING EYELIDS OPEN. SKIN:
FLUSH W/WATER FOR 15 MIN, WHILE REMOVING CONTAMINATED CLOTHES.
INGEST: DO NOT INDUCE VOMITING. IN ALL CASES, GET MEDICA

L

ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method:TOC

Flash Point:74.0F,23.3C

Lower Limits:1.2

Upper Limits:8.0

Extinguishing Media:CO2, FOAM, DRY CHEMICAL.

Fire Fighting Procedures:USE FULL PROTECTIVE GEAR W/SCBA & CHEMICAL PROTECTIVE SUIT FOR AMINE/AMMONIA TYPE CORROSIVE VAPORS. KEEP PERSONNEL UPWIND OF THE FIRE.

Unusual Fire/Explosion Hazard:NONE, THE PRODUCT IS A FLAMMABLE LIQUID. PRODUCT BECOMES A CORROSIVE LIQUID UPON THE ADDITION OF WATER.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE IGNITION SOURCES. USE PROTECTIVE EQUIPMENT. CONTAIN SPILL W/ABSORBENT MATERIAL. CLEAN UP ABSORBENT AND CONTAIN SECURELY. SWEEP AND WET MOP AREA W/SOAP AND WATER. VENTILATE AREA.

===== Handling and Storage =====

Handling and Storage Precautions:SMOKE IN SMOKING AREAS ONLY.

===== Exposure Controls/Personal Protection =
=====

Respiratory Protection:FULL FACE PIECE OR A PURIFYING CARTRIDGE RESPIRATOR EQUIPPED FOR ORGANIC VAPORS & MISTS, A SCBA IN PRESSURE DEMAND MODE,OR A POSITIVE PRESSURE AIR-SUPPLIED RESPIRATOR.

Ventilation:EXHAUST VENTILATION IN ACCORDANCE W/ACGIH GUIDELINES AS CONTAINED IN ITS 'INDUSTRIAL VENTILATION' PUBLICATION.

Protective Gloves:SOLVENT RESISTANT GLOVES.

Eye Protection:SOLVENT RESISTANT SAFETY GOGGLES/GLASSES

Other Protective Equipment:EYE WASH STATION, SAFETY SHOWER.

SOLVENT

RESISTANT APRON.

Work Hygienic Practices:WASH WELL W/SOAP & WATER AFTER HANDLING PRODUCT. SMOKE IN SMOKING AREA ONLY.

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:241F,116C

Melt/Freeze Pt:M.P/F.P Text:NA

Vapor Pres:15

Vapor Density:3.5

Spec Gravity:0.83

Evaporation Rate & Reference:1.6 (BUAC)

Solubility in Water:SLIGHT

Appearance and Odor:CLEAR YELLOW LIQUID WITH PUNGENT ODOR

Corrosion Rate:N/KNO

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

STRONG OXIDIZING AGENTS, STRONG ACIDS

Stability Condition to Avoid: KEEP AWAY FROM IGNITION SOURCES AND
TEMPERATURES >100F/38C.

Hazardous Decomposition Products: CARBON MONOXIDE, CARBON DIOXIDE,
NITROGEN OXIDES AND AMMONIA MAY BE RELEASED DURING COMBUSTION.

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE W/
FEDERAL, STATE AND

LOCAL REGULATIONS. INCINERATOR IS PREFERRED; RCRA HAZARDOUS
IGNITABLE WASTE.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice
to verify and
assume responsibility for the suitability of this information to their
particular situation.