

HOME OIL COMPANY, INC -- BOILED LINSEED OIL -- 8010-00-684-8789

=====
Product Identification
=====

Product ID:BOILED LINSEED OIL

MSDS Date:09/10/1997

FSC:8010

NIIN:00-684-8789

MSDS Number: CGXMN

=== Responsible Party ===

Company Name:HOME OIL COMPANY, INC

Address:3511 N OHIO

Box:2609

City:WICHITA

State:KS

ZIP:67201-2609

Country:US

Info Phone Num:316-838-4663

Emergency Phone Num:800-633-8253 (PERS)

CAGE:0A9L8

=== Contractor Identification ===

Company Name:HOC INDUSTRIES, INC

Address:3511 N. OHIO

Box:2609

City:WICHITA

State:KS

ZIP:67219

Country:US

Phone:316-838-4663

CAGE:0A9L8

=====
Composition/Information on Ingredients
=====

Ingred Name:BOILED LINSEED OIL IS NOT A HAZARDOUS MATERIAL ACCORDING TO
29 CFR 1910.1200

CAS:8001-26-1

RTECS #:OI9690000

Other REC Limits:NONE RECOMMENDED

=====
Hazards Identification
=====

Routes of Entry:

Inhalation: YES Skin: YES Ingestion: YES
Reports of Carcinogenicity: NTP: NO IARC: NO OSHA: NO
Health Hazards Acute and Chronic: SKIN: IRRIT, DERMATITIS. INGEST: IRRIT
STOMACH & INTESTINES. ASPIRATED INTO LUNGS RESULTING IN CHEMICAL
PNEUMONITIS.

=====
First Aid Measures
=====

First Aid: EYE: FLUSH W/WATER FOR 15 MINUTES. SKIN: REMOVE CONTAM
CLOTHES & SHOES. WASH W/SOAP & WATER. INHAL: REMOVE TO FRESH AIR.
GET MEDICAL ATTENTION AT ONCE. INGEST:
DONT INDUCE VOMIT. KEEP WARM
& QUIET. GET MEDICAL ATTENTION.

=====
Fire Fighting Measures
=====

Flash Point Method: TCC
Flash Point: 200F, 93C
Extinguishing Media: WATER, CARBON DIOXIDE, FOAM EXTINGUISHERS FOR CLASS
III B LIQUID FIRES.
Fire Fighting Procedures: USE SCBA. SHUT OFF SOURCE. WATER FOG/SPRAY TO
COOL CONTAINERS OR EQUIPMENT. DONT SPRAY WATER DIRECTLY ON FIRE.
PRODUCT WILL FLOAT & REIGNITED ON SURFACE.
Unusual Fire/Explosion Hazard: BOILED
LINSEED OIL WILL OXIDIZE & CAUSE
SPONTANEOUS COMBUSTION. AVOID SPONTANEOUS COMBUSTION OF CONTAM
RAGS/IGNITABLE ABSORBENT MATERIAL, BY IMMERSING IN WATER.

=====
Accidental Release Measures
=====

Spill Release Procedures: ELIMINATE IGNIT SOURCES. VENT AREA. USE
SUPPLIED-AIR MASK FOR LARGE SPILLS OR IN CONFINED AREAS. CONTAIN
SPILL. REMOVE W/INERT ABSORBENT. AVOID ALLOWING PRODUCT TO ENTER
STREAMS OR SEWERS.

=====
Handling and Storage
=====

Handling and Storage Precautions: TRANSPORT, HANDLE, STORE IN ACCORDANCE
W/29 CFR (1910.106) & DOT REGULATIONS. GROUND & ELECTRICALLY
INTERCONNECT CONTAINERS FOR TRANSFER.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection: RESPIRATORY PROTECTION MAY BE REQUIRED IF
MATERIAL IS USED IN POORLY VENTILATED AREAS OR IF MATERIAL IS
SPRAYED OR HEATED.
Ventilation: GENERAL VENTILATION IS RECOMMENDED. LOCAL VENTILATION MA

Y

BE REQUIRED IF MATERIAL IS SPRAYED OR HEATED.

Protective Gloves:NEOPRENE RUBBER

Eye Protection:CHEMICAL GOGGLES

Other Protective Equipment:PROTECTIVE CLOTHES SUCH AS UNIFORMS. EYE WASH STATION AVAILABLE.

Work Hygienic Practices:DONT WEAR CONTACT LENSES. FOLLOW SAFE WORK PRACTICES. WASH HANDS PRIOR TO EATING OR SMOKING.

Supplemental Safety and Health
NK

===== Physical/Chemical Properties =====

Spec Gravity:0.93 @ 77F

pH:NA

Solubility in Water:NEGLIGIBLE

Appearance and Odor:CLEAR, LOW ODOR.

Percent Volatiles by Volume:0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZERS

Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE AND POSSIBLY ACROLEIN.

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE OR PLACE IN RCRA PERMITTED WASTE MANAGEMENT FACILITY IN ACCORDANCE W/LOCAL, STATE & FEDERAL REGULATIONS.

=====

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume res

possibility for the suitability of this information to their particular situation.