

LHB INDUSTRIES -- SO-SURE BLACK 37038 (0054-390)

=====
MSDS Safety Information
=====

FSC: 8010
NIIN: 00-910-8154
MSDS Date: 10/02/1997
MSDS Num: CGXNG
Product ID: SO-SURE BLACK 37038 (0054-390)
MFN: 07
Responsible Party
Cage: 0FTT5
Name: LHB INDUSTRIES
Address: 8833 FLEISCHER PLACE
City: ST. LOUIS MO 63
134
Info Phone Number: 314-522-3141
Emergency Phone Number: 800-424-9300 CHEMTREC/ 314-522-3141
Preparer's Name: ROBIN C. GANNON
Published: Y

=====
Preparer Co. when other than Responsible Party Co.
=====

Cage: 0FTT5
Name: LHB INDUSTRIES
Address: 8833 FLEISCHER PLACE
City: ST. LOUIS MO 63134

=====
Contractor Summary
=====

Cage: 0FTT5
Name: LHB INDUSTRIES
Address: 8833 FLEISCHER PLACE
City: ST. LOUIS MO 63134
Phone: 314-522-3141

=====
Item Description Information
=====

Item Manager: GSA
Item Name: ENAMEL
Specification Number: TT-E-516A
Unit of Issue: PT
UI Container Qty: 0

=====
Ingredients
=====

=====

Cas: 108-88-3
RTECS #: XS5250000
Name: TOLUENE (SARA III)
% Wt: 14.66
Other REC Limits: NONE RECOMMENDED
OSHA PEL: 200 PPM
ACGIH TLV: 100 PPM
EPA Rpt Qty: 1000 LBS
DOT Rpt Qty: 1000 LBS

Cas: 67-64-1
RTECS #: AL3150000
Name: ACETONE (SARA III)
% Wt: 23.09
Other REC Limits: NONE RECOMMENDED
OSHA PEL: 1000 PPM
ACGIH TLV: 750 PPM
EPA Rpt Qty: 5000 LBS
DOT Rpt Qty: 5000 LBS

Cas: 1330-20-7
RTECS #: ZE2100000
Name: XYLENE (SARA III)
%
Wt: 3.78
Other REC Limits: NONE RECOMMENDED
OSHA PEL: 100 PPM
ACGIH TLV: 100 PPM
EPA Rpt Qty: 1000 LBS
DOT Rpt Qty: 1000 LBS

Cas: 100-41-4
RTECS #: DA0700000
Name: ETHYLBENZENE (SARA III)
% Wt: <1.89
Other REC Limits: NONE RECOMMENDED
OSHA PEL: 100 PPM
ACGIH TLV: 100 PPM
EPA Rpt Qty: 1000 LBS
DOT Rpt Qty: 1000 LBS

Cas: 74-98-6
RTECS #: TX2275000
Name: PROPANE
% Wt: 14.90
Other REC Limits: NONE RECOMMENDED
OSHA PEL: 1000 PPM
ACGIH

TLV: 1000 PPM

Cas: 75-28-5
RTECS #: TZ4300000
Name: 2-METHYL PROPANE
% Wt: 3.66
Other REC Limits: NONE RECOMMENDED
OSHA PEL: NOT ESTABLISHED
ACGIH TLV: 800 PPM

Cas: 106-97-8
RTECS #: EJ4200000
Name: N-BUTANE
% Wt: 5.86
Other REC Limits: NONE RECOMMENDED
OSHA PEL: 800 PPM
ACGIH TLV: 800 PPM

Cas: 108-65-6
RTECS #: AI8925000
Name: 2-METHOXY-1-METHYL ETHYL ACETATE
% Wt: 1.89
Other REC Limits: NONE RECOMMENDE
D
OSHA PEL: NOT ESTABLISHED
ACGIH TLV: NOT ESTABLISHED

Cas: 8032-32-4
RTECS #: OI6180000
Name: VM & P NAPHTHA
% Wt: 11.35
Other REC Limits: NONE RECOMMENDED
OSHA PEL: 100 PPM
ACGIH TLV: 100 PPM
=====

Health Hazards Data
=====

Route Of Entry Inds - Inhalation: YES
Skin: YES
Ingestion: YES
Carcinogenicity Inds - NTP: NO
IARC: NO
OSHA: NO
Effects of Exposure: EYE:

IRRIT. SKIN: IRRIT. INHAL: HARMFUL, FATAL, BRAIN/NS
DAMAGE, ANESTHETIC, RESPIRATORY TRACT IRRIT, LIGHT HEADEDNESS, STAGGERING
GAIT, GIDDY, NAUSEA, THROAT IRRIT, HEADACHE, VOMIT. INGEST: HARMFUL.
Medical Cond Aggravated By Exposure: RESPIRATORY AILMENTS
First Aid: EYE: FLUSH W/WATER FOR 15 MINUTES. SKIN: WASH W/SOAP & WATER.
WASH CLOTHES BEFORE REUSE. INHAL: REMOVE TO FRESH AIR. ARTIF RESP IF NEEDED.
INGEST: DONT INDUCE VOMIT. IN ALL CASES, GET MEDICAL ATTENTIO N.

=====
=====
Handling and Disposal

=====
Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION AND VENTILATE AREA.
MOP SPILLS WITH INERT ABSORBENT. AVOID BREATHING VAPORS.
Waste Disposal Methods: IN ACCORDANCE W/FEDERAL, STATE, LOCAL REGULATIONS. DONT
PUNCTURE, INCINERATE OR STORE >120F. EXPOSURE TO HEAT OR PROLONGED
EXPOSURE TO SUN MAY CAUSE CAN TO BURST. DISCARD EMPTY CAN IN TRASH PICK-UP. D
ONT PLACE IN HOM
E TRASH COMPACTOR.
Handling And Storage Precautions: KEEP OUT OF REACH OF CHILDREN. CONTENTS UNDER
PRESSURE. DONT STORE WHERE TEMPERATURE MAY EXCEED 120F.
Other Precautions: USE WITH GOOD VENTILATION. READ ENTIRE LABEL BEFORE USING.
FOLLOW ALL LABEL DIRECTIONS.

=====
Fire and Explosion Hazard Information

=====
Flash Point Text: -156F,-104C
Lower Limits: 1.8
Upper Limits: 9.5
Extinguishing Med
ia: CARBON DIOXIDE, DRY CHEMICAL, FOAM, SAND, WATER SPRAY.
AVOID SPREADING ANY BURNING LIQUID WITH WATER SPRAY.
Fire Fighting Procedures: WATER MAY BE INEFFECTIVE. USE WATER TO COOL
CONTAINERS. USE SCBA. USE SHIELDING TO PROTECT PERSONNEL FROM BURSTING,
RUPTURING OR VENTING OF CONTAINERS.
Unusual Fire/Explosion Hazard: DONT SPRAY NEAR OPEN FLAME. AT ELEVATED
TEMPERATURE (>120F) CONTAINERS MAY VENT, RUPTURE OR BURST. AEROSOL
CONTAINER: DONT EXPOSE TO TEMPERATURE ABOVE 120F.

=====
=====
Control Measures

=====
Respiratory Protection: NONE BELOW TLV. USE NIOSH/MSHA APPROVED MASK ABOVE TLV.
Ventilation: LOCAL EXHAUST PREFERRED. MECHANICAL (GENERAL) ACCEPTABLE AT POINT
OF MIST OR SPRAY RELEASE.
Protective Gloves: REQUIRED
Eye Protection: CHEMICAL SPLASH GOGGLES
Other Protective Equipment: IMPERVIOUS CLOTHES TO PROTECT SKIN. EYE WASH
STATION.
Work Hygienic Practices: USE GOOD PERSON

AL HYGIENE. DONT EAT OR SMOKE WHILE
USING PRODUCT.

=====
Physical/Chemical Properties
=====

B.P. Text: NA
M.P/F.P Text: NA
Decomp Text: NA
Vapor Pres: 60 @ 68F
Vapor Density: >1.5 AIR=1
Spec Gravity: 0.798 AEROSOL
PH: NA
VOC Grams/Liter: 452
Solubility in Water: INSOLUBLE
Appearance and Odor: BLACK PAINT
Corrosion Rate: NA

=====
Reactivity Data
ta

=====
Stability Indicator: YES
Stability Condition To Avoid: EXTREME HEAT
Materials To Avoid: NA
Hazardous Decomposition Products: CARBON MONOXIDE AND POSSIBLE HYDROGEN
CHLORIDE.
Hazardous Polymerization Indicator: NO
Conditions To Avoid Polymerization: NA

=====
Toxicological Information
=====

=====
Ecological Information
=====

=====
MSDS Transport Information
=====

=====
Regulatory Information
=====

=====
Other Information
=====

Other

Information: VOC = 452 G/L

=====
Transportation Information
=====

Responsible Party Cage: 0FTT5
Trans ID NO: 91463
Product ID: SO-SURE BLACK 37038 (0054-390)
MSDS Prepared Date: 10/02/1997
Review Date: 03/24/1998
MFN: 7
Multiple KIT Number: 0
Review IND: Y
Unit Of Issue: PT
Container QTY: 0
=====

=====
Detail DOT Information
=====

=====
DOT PSN Code: DTJ
Symbols: D
DOT Proper Shipping Name: CONSUMER COMMODITY
Hazard Class: ORM-D
Label: NONE
Non Bulk Pack: 156,306
Bulk Pack: NONE
Max Qty Pass: 30KGGROSS
Max Qty Cargo: 30KGGROSS
Vessel Stow Req: A
=====

=====
Detail IMO Information
=====

IMO PSN Code: AKH
IMO Proper Shipping Name: AEROSOLS/AEROSOL PRODUCT ?
IMDG Page Number: SEE 9022
UN Number: 1950
UN Haza
rd Class: 9?
IMO Packaging Group: -
Subsidiary Risk Label: -
EMS Number: 2-13
=====

=====
Detail IATA Information
=====

IATA PSN Code: ALS
IATA UN ID Num: 1950
IATA Proper Shipping Name: AEROSOLS, FLAMMABLE
IATA PSN Modifier: (EACH NOT EXCEEDING 1 L CAPACITY)
IATA UN Class: 2.1
IATA Label: FLAMMABLE GAS
Packing Note Passenger: 203
Max Quant Pass: 75KG
Max Quant Cargo: 150KG
Packaging Note Cargo: 203
=====
==

=====
Detail AFI Information
=====

AFI PSN Code: ALR
AFI Symbols: *
AFI Proper Shipping Name: AEROSOLS, FLAMMABLE, N.O.S.
AFI PSN Modifier: (EACH NOT EXCEEDING 1L CAPACITY)
AFI Hazard Class: 2.1
AFI UN ID NUM: UN1950
Special Provisions: P4
Back Pack Reference: A6.3
=====

HAZCOM Label
=====

Product I
D: SO-SURE BLACK 37038 (0054-390)
Cage: 0FTT5
Company Name: LHB INDUSTRIES
Street: 8833 FLEISCHER PLACE
City: ST. LOUIS MO
Zipcode: 63134
Health Emergency Phone: 800-424-9300 CHEMTREC/ 314-522-3141
Label Required IND: Y
Date Of Label Review: 10/12/1999
Status Code: A
Origination Code: G
Hazard And Precautions: EYE: IRRIT. SKIN: IRRIT. INHAL: HARMFUL, FATAL,
BRAIN/NS DAMAGE, ANESTHETIC, RESPIRATORY TRACT IRRIT, LIGHT HEADEDNESS,
STAGGERING GAIT, GIDDY, NAUSEA, THROAT IRRIT, HEADACHE, VOMIT. I
NGEST:
HARMFUL.
=====

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.