

LHB INDUSTRIES -- ECO SURE BLUE #15102 (0674-152)

=====
MSDS Safety Information
=====

FSC: 8010
NIIN: 01-331-6119
MSDS Date: 05/28/1995
MSDS Num: CGXQP
Product ID: ECO SURE BLUE #15102 (0674-152)
MFN: 03
Responsible Party
Cage: 0FTT5
Name: LHB INDUSTRIES
Address: 8833 FLEISCHER PLACE
City: ST. LOUIS MO 6
3134
Info Phone Number: 314-522-3141
Emergency Phone Number: 800-424-9300 CHEMTREC/ 314-522-3141
Preparer's Name: GREGORY M. MCGOWAN
Published: Y

=====
Preparer Co. when other than Responsible Party Co.
=====

Cage: 0FTT5
Name: LHB INDUSTRIES
Address: 8833 FLEISCHER PLACE
City: ST. LOUIS MO 63134

=====
Contractor Summary
=====

Cage: 0FTT5
Name: LHB INDUSTRIES
Address: 8833 FLEISCHER PLACE
City: ST. LOUIS MO 63134
Phone: 314-522-3141

=====
Item Description Information
=====

Item Manager: GSA
Item Name: ENAMEL
Specification Number: A-A-2787
Type/Grade/Class: TYPE I
Unit of Issue: PT
UI Container Qty: 0

=====
Ingredients
=====

=====
Cas: 1330-20-7
RTECS #: ZE2100000
Name: XYLENE (SARA 313) (CERCLA)
% Wt: <20.72
Other REC Limits: NONE RECOMMENDED
OSHA PEL: 100 PPM
ACGIH TLV: 100 PPM
EPA Rpt Qty: 1000 LBS
DOT Rpt Qty: 1000 LBS

Cas: 74-98-6
RTECS #: TX2275000
Name: PROPANE
% Wt: 14.48
Other REC Limits: NONE RECOMMENDED
OSHA PEL: 1000 PPM
ACGIH TLV: 1000 PPM

Cas: 115-10-6
RTECS #: PM4780000
Name: DIMETHYL ETHER
% Wt: 8.05
Other R
EC Limits: NONE RECOMMENDED
OSHA PEL: NOT ESTABLISHED
ACGIH TLV: NOT ESTABLISHED

Cas: 110-12-3
RTECS #: MP3850000
Name: 5-METHYL 2-HEXANONE
% Wt: 5.97
Other REC Limits: NONE RECOMMENDED
OSHA PEL: 50 PPM
ACGIH TLV: 50 PPM

Cas: 64742-95-6
Name: AROMATIC 100
% Wt: 5.97
Other REC Limits: NONE RECOMMENDED
OSHA PEL: NOT ESTABLISHED
ACGIH TLV: 50 PPM

Cas: 64742-95-6
Name: AROMATIC 150
% Wt: <2.99
Other REC L

imits: NONE RECOMMENDED
OSHA PEL: NOT ESTABLISHED
ACGIH TLV: 5 PPM

Cas: 107-87-9
RTECS #: SA7875000
Name: 2-PENTANONE
% Wt: <2.99
Other REC Limits: NONE RECOMMENDED
OSHA PEL: 200 PPM
ACGIH TLV: 200 PPM

Cas: 108-10-1
RTECS #: SA9275000
Name: 4-METHYL-2-PENTANONE (SARA 313) (CERCLA)
% Wt: <2.99
Other REC Limits: NONE RECOMMENDED
OSHA PEL: 100 PPM
ACGIH TLV: 50 PPM
EPA Rpt Qty: 5000 LBS
DOT Rpt Qty: 5000 LBS

Cas: 95-63-6
RTECS #: DC3325000
Name: 1,2,4-TRIMETHYLBENZENE (SARA 313)
% Wt: <2.99
Other REC Limits: NONE RECOMMENDED
OSHA PEL: NOT ESTABLISHED
ACGIH TLV: 25 PPM

Cas: 71-36-3
RTECS #: EO1400000
Name: N-BUTANOL (SARA 313) (CERCLA)
% Wt: <2.99
Other REC Limits: NONE RECOMMENDED
OSHA PEL: 50 PPM
ACGIH TLV: 100 PPM
EPA Rpt Qty: 5000 LBS
DOT Rpt Qty: 5000 LBS
=====

Health Hazards Data
=====

=====
Route Of Entry Inds - Inhalation: YES

Skin: YES

Ingestion: YES

Carcinogenicity Inds - NTP: NO

IARC: NO

OSHA: NO

Effects of Exposure: EYE: IRRIT. SKIN: IRRIT. INHAL: HARMFUL, FATAL, BRAIN/NS
DAMAGE, ANESTHETIC, IRRIT TO RESPIRATORY TRACT, LIGHTHEADED, STAGGERING GAIT,
GIDDY, NAUSEA, THROAT IRRIT, VOMITING, HEADACHE. INGEST: HARMFUL.

Explanation Of Carcinogenicity: NO

Medical Cond Aggravated By Exposure: RESPIRATORY AILMENTS

First Aid: EYE: FLUSH W/WATER FOR

15 MINUTES. SKIN: WASH W/SOAP & WATER.

WASH CLOTHES BEFORE REUSE. INHAL: REMOVE TO FRESH AIR. ARTIF RESP IF NEEDED.

INGEST: DONT INDUCE VOMIT. IN ALL CASES, GET MED AID.

=====
Handling and Disposal

=====
Spill Release Procedures: REMOVE IGNITS. VENT AREA. MOP SPILLS W/INERT
ABSORBENT. AVOID BREATHING VAPORS.

Waste Disposal Methods: IN ACCORDANCE W/FEDERAL, STATE & LOCAL REGULATIONS.

DONT PUNCTURE, INCINERATE OR STORE >120F. EXPOSURE TO HEAT OR PROLONGED
EXPOSURE TO SUN MAY CAUSE CAN TO BURST. DISCARD EMPTY CAN IN TRASH PICK-UP.
DONT PLACE IN HOME TRASH COMPACTOR.

Handling And Storage Precautions: KEEP OUT OF REACH OF CHILDREN. CAUTION:

CONTENTS UNDER PRESSURE: DONT STORE WHERE TEMPS EXCEED 120F.

Other Precautions: USE W/GOOD VENTILATION. READ ENTIRE LABEL BEFORE USING.

FOLLOW ALL LABEL DIRECTIONS.

=====
Fire and Explosion Hazard Information

=====
Flash Point Text: -156F,-104C

Autoignition Temp Text: 662F

Lower Limits: 2.2

Upper Limits: 18.0

Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL, FOAM, SAND, WATER SPRAY.

AVOID SPREADING ANY BURNING LIQUID W/WATER SPRAY.

Fire Fighting Procedures: WATER MAY BE INEFFECTIVE. USE WATER TO COOL

CONTAINERS. USE SCBA. USE SHIELDING TO PROTECT PERSONNEL AGAINST BURSTING,
RUPTURING, VENTING OF CONTAINERS.

Unus

ual Fire/Explosion Hazard: DONT SPRAY NEAR OPEN FLAME. AT TEMPS >120F
CONTAINERS MAY VENT, RUPTURE, BURST. AEROSOL CONTAINERS: DO NOT EXPOSE TO
TEMPS >120F.

=====
Control Measures
=====

Respiratory Protection: USE NIOSH/MSHA APPROVED MASK ABOVE TLV.
Ventilation: LOCAL EXHAUST PREFERRED. MECHANICAL (GENERAL) ACCEPTABLE AT POINT
OF MIST OR SPRAY RELEASE.
Protective Gloves: RECOMMENDED
Eye Protection: CHEMICAL SPLASH GOGGLES
Other Protective Equipment: IMPROVIOUS CLOTHES TO PROTECT SKIN, EYEWASH STATION.
Work Hygienic Practices: DONT EAT, DRINK OR SMOKE WHILE USING THIS PRODUCT.

=====
Physical/Chemical Properties
=====

B.P. Text: NA
M.P/F.P Text: NA
Decomp Text: NA
Vapor Pres: 70 @ 68F
Vapor Density: >1.522
Spec Gravity: 0.890 (AEROSOL)
PH: NA
VOC Grams/Liter: 576
Viscosity: N
A
Solubility in Water: INSOLUBLE
Appearance and Odor: BLUE PAINT
Corrosion Rate: NA

=====
Reactivity Data
=====

Stability Indicator: YES
Stability Condition To Avoid: EXTREME HEAT
Materials To Avoid: NA
Hazardous Decomposition Products: CARBON MONOXIDE
Hazardous Polymerization Indicator: NO
Conditions To Avoid Polymerization: NA

=====
Toxicologica
=====

I Information

Ecological Information

MSDS Transport Information

Regulatory Information

Other Information

Other Information: VOC = 576 G/L

Transportation Information

Responsible Party Cage: 0FTT5
Trans ID NO: 126078
Product ID: ECO SURE BLUE #15102 (0674-152)
MSDS Prepared Date: 05/28/1995
Review Date: 04/29/1998
MFN: 3
Multiple KIT Number: 0
Review IND: Y
Unit Of Issue: PT
Co
ntainer QTY: 0

Detail DOT Information

DOT PSN Code: DTJ
Symbols: D
DOT Proper Shipping Name: CONSUMER COMMODITY
Hazard Class: ORM-D
Label: NONE
Non Bulk Pack: 156,306
Bulk Pack: NONE
Max Qty Pass: 30KGGROSS
Max Qty Cargo: 30KGGROSS
Vessel Stow Req: A

Detail IMO Information

IMO PSN Code: AKH
IMO Proper Shipping Name: AEROSOLS/AEROSOL PRODUCT ?
IMDG Page Number: SEE 9022
UN Number: 1950
UN Hazard Class: 9?
IMO Packaging Group: -
Subsidiary Risk Label: -
EMS Number: 2-13

=====
Detail IATA Information
=====

IATA PSN Code: ALS
IATA UN ID Num: 1950
IATA Proper Shipping Name: AEROSOLS, FLAMMABLE
IATA PSN Modifier: (EACH NOT EXCEEDING 1 L CAPACITY)
IATA UN Class: 2.1
IATA
Label: FLAMMABLE GAS
Packing Note Passenger: 203
Max Quant Pass: 75KG
Max Quant Cargo: 150KG
Packaging Note Cargo: 203

=====
Detail AFI Information
=====

AFI PSN Code: ALR
AFI Symbols: *
AFI Proper Shipping Name: AEROSOLS, FLAMMABLE, N.O.S.
AFI PSN Modifier: (EACH NOT EXCEEDING 1L CAPACITY)
AFI Hazard Class: 2.1
AFI UN ID NUM: UN1950
Special Provisions: P4
Back Pack Reference: A6.3

=====
HAZCOM Label
=====

Product ID: ECO SURE BLUE #15102 (0674-152)
Cage: 0FTT5
Company Name: LHB INDUSTRIES
Street: 8833 FLEISCHER PLACE
City: ST. LOUIS MO
Zipcode: 63134
Health Emergency Phone: 800-424-9300 CHEMTREC/ 314-522-3141
Label Required IND: Y
Date Of Label Review: 10/12/1999
Status Code: A
Origination Code: G
Hazard And Precautions: EYE: IRRIT. SKIN: IRRIT. INHAL: HARMFUL, FATAL,
BRAIN/NS DAMAGE,

ANESTHETIC, IRRIT TO RESPIRATORY TRACT, LIGHTHEADED,
STAGGERING GAIT, GIDDY, NAUSEA, THROAT IRRIT, VOMITING, HEADACHE. INGEST:
HARMFUL.

=====
Disclaimer (provided with this information by the compiling agencies): This
information is formulated for use by elements of the Department of Defense.
The United States of America in no manner whatsoever expressly or implied
warrants, states, or intends said information to have any application,
use or
viability by or to any person or persons outside the Department of Defense
nor any person or persons contracting with any instrumentality of the United
States of America and disclaims all liability for such use. Any person
utilizing this instruction who is not a military or civilian employee of the
United States of America should seek competent professional advice to verify
and assume responsibility for the suitability of this information to their
particular situation regard
less of similarity to a corresponding Department
of Defense or other government situation.