View NSN Online: https://aerobasegroup.gr/nsn/6135-01-315-9214

EAGLE-PINCHER INDUSTRIES,INC -- KEEPER II/LITHIUM/THIONYL CHLORIDE BATTERY 6135-01-315-9214

Product ID:KEEPER II/LITHIUM/THIONYL CHLORIDE BATTERY MSDS Date:10/01/1992 FSC:6135 NIIN:01-315-9214 MSDS Number: CHHTW === Responsible Party === Company Name: EAGLE-PINCHER INDUSTRIES, INC Address:BETHEL RD Box:130 City:SENECA State:MO ZIP:64865 Country:US Info Phone Num :417-776-2256 Emergency Phone Num:417-776-2256/800-424-9300(CHEMTREC) CAGE:81855 === Contractor Identification === Company Name: EAGLE-PICHER INDUSTRIES, INC. Address: C AND PORTER STS Box:47 City: JOPLIN State:MO ZIP:64801 Country:US Phone:417-623-8000 CAGE:81855

Ingred Name:LITHIUM METAL CAS:7439-93-2 RTECS #:OJ5540000 Other REC Limits:NONE RECOMMENDED

Ingred Name:THIONYL CHLORIDE (SOCL2) CAS:7719-09-7 RTECS #:XM5150000 Other REC Limits:NONE RECOMMENDED OSHA PEL:C 1 PPM ACGIH TLV:C 1 PPM; 9596

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER. Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:THIONYL CHLORIDE WILL BURN AND IRRITATE EYES AND SKIN, IRRITATE UPPER RESPIRATORY SYSTEM. CONTINUOUS INHALATION OF FUMES MAY CAUSE LUNG DAMAGE. Explanation of Carcinogenicity:NONE Effects of Overexposure:SYMPTOMS OF OVEREXPOSURE TO THIONYL CHLORIDE FUMES: EYE AND SKIN IRRITATION, PUNGENT ODOR, AND RESPIRATORY IRRITATION. Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

First Aid:IF FREE THIONYL CHLORIDE IS PRESENT, EVACUTE AREA AND PROVIDE VENTILATION, WASH EXPOSED AREAS WITH SODA ASH OR SODIUM BECARBONATE SOLUTION. GET MEDICAL ATTENTION.

=====

Extinguishing Media:DO NOT USE WATER. USE DRY CHEMICAL, SODA ASH, SAND. Fire Fighting Procedures:USE SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE EQUIPMENT.

Unusual Fire/Explosion Hazard:DO NOT RECHARGE, DISASSEMBLE, HEAT ABOVE 125F, INCINERATE OR EXPOSE CONTENTS TO WATER, VENT, RUPTURE OR EXPLOSION MAY RESULT AND CAUSE SEVERE BURNS.

Spill Re

lease Procedures: AVOID CONTACT IF VENT, RUPTURE, OR EXPLOSION HAS OCCURED. OTHERWISE PROTECT FROM HEAT, SHORT CIRCUIT OF TERMINALS, AN ACCUMULATION OF SHORTED BATTERIES, WHICH MAY CAUSE DANGEROUS ELEVATED TEMPERATURES.

Neutralizing Agent:NEUTRALIZE THIONYL CHLORIDE WITH SODA ASH OR SODIUM BICARBONATE SOLUTION.

Handling and Storage Precautions:DO NOT SHORT CIRCUIT, HEAT ABOVE 125C (257F), RECHARGE, DISASSEM

BLE, INCINERATE, OR EXPOSE TO WATER. Other Precautions:NONE SPECIFIED BY MANUFACTURER.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:SELF-CONTAINED BREATHING APPARATUS IF EXPOSURE EXCEEDS RECOMMENDED LIMITS.
Protective Gloves:NEOPRENE IF NEEDED.
Eye Protection:RECOMMENDED.
Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.
Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.
Supplemental Safety and Health
NONE

HCC:N1

Appearance and Odor:3.6 VOLT BATTERY, RECTANGULAR W/ROUNDED CORNERS, 2.2 IN. X 3.54 IN.X 2.13 IN.HIGH

Stability Indicator/Materials to Avoid:YES WATER, HUMID AIR, ALKALIES, AND TEMPERATURE ABOVE 140C (284F). Stability Condition to Avoid:VENT, RUPTURE OR EXPLOSION WILL RELEASE THIONYL CHLORIDE (SOCL2)

Hazardous Decomposition Products: THIONYL CHLORIDE IN PRESENCE OF WAT ER

OR HUMID AIR FORMS HYDROCHLORIC ACID AND SULFUR OXIDE. Conditions to Avoid Polymerization:WILL NOT OCCUR.

Waste Disposal Methods:DISPOSE OF WASTE IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expr essly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.