

DEL PAINT CORP. -- TT-E-2784 ENAMEL BLUE #15526 -- 8010-01-435-2120

===== Product Identification =====

Product ID:TT-E-2784 ENAMEL BLUE #15526

MSDS Date:06/14/1995

FSC:8010

NIIN:01-435-2120

MSDS Number: CHKMH

=== Responsible Party ===

Company Name:DEL PAINT CORP.

Address:3105 E. RENO

City:OKLAHOMA CITY

State:OK

ZIP:73117

Country:US

Info Phone Num:405-672-1431/FAX 405-672-0804

Emergency Phone Num:8

00-424-9300 24 HRS

Preparer's Name:ONEY FLEMING

CAGE:JO954

=== Contractor Identification ===

Company Name:DEL PAINT CORP.

Address:3105 E. RENO

City:OKLAHOMA CITY

State:OK

ZIP:73117

Country:US

Phone:405-672-1431/FAX 405-672-0804

CAGE:JO954

Company Name:DEL PAINT MFG

Address:3105 EAST RENO

Box:City:OKLAHOMA CITY

State:OK

ZIP:73117

Country:US

Phone:405-672-1431

CAGE:39934

===== Composition/Information on Ingredients =====

Ingred Name:PROPYLENE GLYCOL

CAS:57-55-6

RTECS #:TY200000

0
Fraction by Wt: 6.25%
Other REC Limits:NONE RECOMMENDED

Ingred Name:2,2,4-TRIMETHYL-3,3,-PENTANEDIOL MONOISOBUTYRATE
CAS:25265-77-4
RTECS #:UF6000000
Fraction by Wt: 4.86%
Other REC Limits:NONE RECOMMENDED

Ingred Name:2-N-OCTYL-1-ISOTHAZOLIN-3-ONE
CAS:26530-20-2
Fraction by Wt: .18%
Other REC Limits:NONE RECOMMENDED

Ingred Name:NON-HAZARDOUS INGREDIENTS
Fraction by Wt: 88.33%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:NOT RELEVANT
ACGIH TLV:NOT RELEVANT

Ingred Name:DIMETHYLAMINOETHANOL LOW
VOC
CAS:108-01-0
RTECS #:KK6125000
Fraction by Wt: .38%
Other REC Limits:NONE RECOMMENDED

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYE: SLIGHT IRRITATION. SKIN: SLIGHT
IRRITATION. INHAL: HEADACHE, NAUSEA, IRRIT TO NOSE/THROAT/LUNGS.
Medical Cond Aggravated by Exposure:PRE-EXISTING DISEASES.

=====
===== First Aid Measures =====

First Aid:EYE: FLUSH W/WATER 15 MINUTES, GET MED AID. SKIN: WASH
THOROUGHLY W/SOAP & WATER. INGEST: GIVE 2 GLASSES OF WATER TO
DRINK, GET MED AID.

=====
===== Fire Fighting Measures =====

Flash Point Method:SCC
Extinguishing Media:FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG.
Fire Fighting Procedures:SCBA, NIOSH APPROVED PRESSURE DEMAND, FULL
PROTECTIVE GEAR.
Unusual Fire/Explosion Hazard:CAN SPLATTER ABOVE 10

0C. POLYMER FILM CAN
BURN.

===== Accidental Release Measures =====

Spill Release Procedures:KEEP PEOPLE AWAY. FLOOR MAY BE SLIPPERY. USE CARE. CONTAIN SPILL W/INERT ABSORBENT. TRANSFER LIQUID/SOLID DIKING MATERIAL TO SEPARATE SUITABLE CONTAINERS FOR RECOVERY/DISPOSAL.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP FROM FREEZING.
Other Precautions:DONT TAKE INTERNALLY. KEEP AWAY FROM CHILDREN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:MECHANICAL FILTER RESPIRATOR
Ventilation:NORMAL, SUCH AS FAN
Protective Gloves:RUBBER
Eye Protection:SAFETY GLASSES OR GOGGLES
Other Protective Equipment:EYEWASH STATION
Supplemental Safety and Health
NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:212 TO 644F
Melt/Freeze Pt:M.P/F.P Text:32.0F,0.0C
Decomp Temp:Decomp Text:351F,177C
Vapor Pres:NONE
Vapor Densi
ty:>AIR
Spec Gravity:1.01
pH:9.0
Viscosity:77-95 KU
Evaporation Rate & Reference:SLOWER THAN ETHER
Solubility in Water:SLIGHT
Appearance and Odor:BLUE LIQUID/SLIGHT ODOR.
Percent Volatiles by Volume:60.6
Corrosion Rate:NA

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
NK
Hazardous Decomposition Products:ACRYLIC MONOMERS

===== Disposal Considerations =====

Waste Disposal Methods:KEEP SPILLS/CLE

ANING RUNOFF OUT OF SEWERS/OPEN

BODIES OF WATER. CONSULT FEDERAL, STATE AND LOCAL REGULATIONS.

===== Other Information =====

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person uti
lizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.