CIBA-GEIGY CORP -- RP 6401-1 RESIN -- 9330-01-225-0175 ============ Product Identification ========================= Product ID:RP 6401-1 RESIN MSDS Date:06/21/1995 FSC:9330 NIIN:01-225-0175 Kit Part:Y MSDS Number: CHQMM === Responsible Party === Company Name: CIBA-GEIGY CORP Address:4917 DAWN AVE City: EAST LANSING State:MI ZIP:48823 Country:US Info Phone Num:517-351-5900 Emergency Phone Num:800-888-8372 CAGE:02684 === Contractor Identification === Company Name: CIBA SPECIALTY CHEMICALS C **ORPORATION** Address:4917 DAWN AVE Box:City:EAST LANSING State:MI ZIP:48823-5691 Country:US Phone:517-351-5900 CAGE:02684 ======= Composition/Information on Ingredients ======== Ingred Name: METHYLENE BISPHENYL ISOCYANATE (MDI) (SARA 313) CAS:101-68-8 RTECS #:NQ9350000 Other REC Limits: NONE RECOMMENDED OSHA PEL:C 0.02 PPM ACGIH TLV:0.005 PPM; 9596 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingred Name: HYDROGENATED TERPHENYLS

CAS:61788-32-7

RTECS #:WZ6535000

Other REC Limits: NONE RECOMMENDED

OSHA PEL:0.5 PPM ACGIH TLV:0.5 PPM; 9596

Ingred Name:1,1'-METHYLENE BIS(ISOCYANATOBENZENE)

CAS:25686-28-6

Other REC Limits: NONE RECOMMENDED

Ingred Name:BENZENE, 1,1'-METHYLENEBIS(ISOCYANATO-

CAS:26447-40-5

Other REC Limits: NONE RECOMMENDED

========= Hazards Identification ============================

LD50 LC50 Mixture: NOT GIVEN FOR PRODUCT AS A WHOLE

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Ch

ronic:SKIN CONTACT MAY CAUSE IRRITATION,

ALLERGIC SKIN REACTION. EYE CONTACT MAY CAUSE IRRITATION. HEATED PRODUCT MAY PRODUCE INHALABLE VAPORS WHICH MAY CAUSE RESPIRATORY TRACT IRRITATION, RESPIRATORY SENSI TIZATION.

Explanation of Carcinogenicity:THIS COMPOUND CONTAINS NO INGREDIENTS AT CONCENTRATIONS OF 0.1% OR GREATER THAT ARE CARCINOGENS OR SUSPECT CARCINOGENS.

Effects of Overexposure:EYE IRRITATION, SKIN IRRITATION, BREATHLESSNESS, CHEST DISCOMFORT, REDUCED PULMONARY FUNCTION.

ALLERGIC SKIN & RESPIRATORY REACTIONS, SPASMS OF THE BRONCHIAL TUBES, DIFFICULTY BREATHING.

Medical Cond Aggravated by Exposure:PERSONS WITH ASTHMATIC-TYPE CONDITIONS, CHRONIC BRONCHITIS, OTHER CHRONIC RESPIRATORY DISEASES, EYE CONDITIONS OR RECURRENT SKIN ECZEMA OR SENSITIZATION SHOULD BE EXCLUDED FROM WORKING WITH ISOCYANATE

First Aid:EYES: FLUSH WITH WATER FOR 15 MINUTES WHILE HOLDING EYELIDS

OPEN. GET MEDICAL ATTENTION. SKIN: REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP AND WATER. IF IRRITATION PERSIST, GET MEDICAL ATTENTION. INH ALATION: REMOVE TO FRESH AIR. RESTORE BREATHING. GET MEDICAL ATTENTION. INGESTION: IF CONSCIOUS, GIVE PLENTY OF WATER TO DRINK. DO NOT INDUCE VOMITING. CALL A PHYSICIAN.

Flash Point Method:PMCC Flash Point:>230F,>110C Lower Limits:NOT GIVEN Upper Limits:NOT GIVEN Ext inguishing Media:FOAM, CARBON DIOXIDE, DRY CHEMICAL, WATER.

Fire Fighting Procedures:FIRE FIGHTERS SHOULD WEAR SELF CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE GEAR. COOL TANKS AND CONTAINERS EXPOSED TO FIRE WITH WATER.

Unusual Fire/Explosion Hazard:DECOMPOSITION AND COMBUSTION PRODUCTS MAY BE TOXIC. AVOID WATER CONTAMINATION IN CLOSED CONTAINERS OR CONFINED SPACES. CARBON DIOXIDE EVOLVED.

======== Accidental Release Measures ============

Spill Release P

rocedures:ABSORB WITH ABSORBENT MATERIAL AND PLACE IN OPEN TOP CONTAINER. UNDER FOOD VENTILATION DECONTAMINATE ABSORBANT AND SPILL AREA WITH A MIXTURE OF 90% WATER, 8% AMMONIA & 2% DETERGENT. LEAVE VENTILATED F OR 24 HOURS BEFORE DISPOSAL. AVOID CONTACT.

Neutralizing Agent:90% WATER, 8% AMMONIA, 2% DETERGENT

========== Handling and Storage =============

Handling and Storage Precautions:HARMFUL IF INHALED. CAUSES SKIN AND EYE IRRITATION. CAUSES ALLERGIC

SKIN AND RESPIRATORY REACTION.

AVOID CONTACT WITH EYES, SKIN AND CLOTHING.

Other Precautions:AVOID BREATHING VAPOR OR MIST. AVOID PROLONGED OR REPEATED CONTACT WITH SKIN. KEEP CONTAINER CLOSED. USE WITH ADEQUATE VENTILATION. WASH THOROUGHLY AFTER HANDLING. NUISANCE DUST MAY BE GENERATED WHEN SANDING OR SAWING CURED MATERIAL.

===== Exposure Controls/Personal Protection ========

Respiratory Protection:IF A PERSON IS CONCERNED WITH EXPOSURE TO ISOCYANATES, AN

ORGANIC RESPIRATOR CAN PROVIDE PROTECTION AT LESS
THAN THE TLV. IT IS NOT A REQUIREMENT AT AN EXPOSURE LEVEL LESS
THAN THE TLV. GREATER THAN T LV WEAR AIR SUPPLIED RESPIRATOR.

Ventilation: EXHAUST VENTILATION SUFFICIENT TO KEEP AIRBORNE CONCENTRATIONS BELOW RESPECTIVE TLV'S.

Protective Gloves: IMPERVIOUS SYNTHETIC

Eye Protection: SPLASH-PROOF CHEMICAL GOGGLES

Other Protective Equipment: CHEMICAL RESISTANT CLOTHING AS NECESSARY TO PREVENT SKIN CONTACT. AN EMERGENCY EYEWASH AND SHOWER

SHOULD BE AVAILABLE. Work Hygienic Practices:WASH HANDS THOROUGHLY WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING OR USING TOILET FACILITIES. Supplemental Safety and Health REMOVE AND WASH CONTAMINATED CLOTHING BEFORE REUSE.
======== Physical/Chemical Properties =========
HCC:T4 Boiling Pt:B.P. Text:NOT GIVEN Melt/Freeze Pt:M.P/F.P Text:NOT GIVEN Decomp Temp:Decomp Text:NOT GIVEN Vapor Pres:0.11 Vapor Density:> 1 Spec Gravity:1.17 - 1.21 Viscosity:NOT GIVEN E vaporation Rate & Deference:NOT GIVEN Solubility in Water:REACTS WITH WATER Appearance and Odor:CLEAR AMBER LIQUID, ODOR NOT SPECIFIED Percent Volatiles by Volume:NIL
======== Stability and Reactivity Data =========
Stability Indicator/Materials to Avoid:YES WATER, ALCOHOLS, STRONG OXIDIZING AGENTS, STRONG BASED, METAL-ORGANIC COMPOUNDS. Stability Condition to Avoid:AVOID PROLONGED HEATING OVER 160F OR STORING VELOW 75F. AVOID WATER CONTAMINATION. Hazardous Decom position Products:CARBON MONOXIDE, CARBON DIOXIDE, OXIDES OF NITROGEN, BENZENE, TOLUENE, HYDROGEN CYANIDE. Conditions to Avoid Polymerization:CONTAMINATION WITH MOISTURE AND OTHER PRODUCTS THAT REACT WITH ISOCYANATES.
======= Disposal Considerations ==========

Waste Disposal Methods: CONSULT QUALIFIED LOCAL OR CORPORATE PERSONNEL FOR METHOD THAT WILL COMPLY WITH LOCAL, STATE AND FEDERAL HEALTH AND ENVIRONMENTAL REGULATIONS.

Disclaimer (provided with th

is information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.