

S I A ADHESIVES INC -- A-1273-B-2, 3010660 -- 8040-00-940-7997

=====
Product Identification
=====

Product ID:A-1273-B-2, 3010660

MSDS Date:04/06/1995

FSC:8040

NIIN:00-940-7997

Status Code:A

Kit Part:Y

MSDS Number: CHXQM

=== Responsible Party ===

Company Name:S I A ADHESIVES INC

Address:123 WEST BARTGES ST

City:AKRON

State:OH

ZIP:44311

Country:US

Info Phone Num:330-374-2786

Emergency Phone Num:330

-374-5143;800-424-9300(CHEMTREC)

Preparer's Name:CLIFFORD PEARSON

CAGE:MO326

=== Contractor Identification ===

Company Name:S I A ADHESIVES INC

Address:123 WEST BARTGES ST

Box:City:AKRON

State:OH

ZIP:44311

Country:US

Phone:330-374-2786

CAGE:MO326

Company Name:SIA ADHESIVES INC

Address:123 W BARTGES ST

Box:City:AKRON

State:OH

ZIP:44311-1081

Country:US

Phone:330-374-2786 / 330-374-2900

CAGE:1HS43

=====
Composition/Information on Ingredients
=====

Ingred Name:NO INGREDIENT FOR T

HIS FORMULATION_INGREDIENT

===== ===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: SKIN: PROLONGED OR REPEATED
EXPOSURE MAY CAUSE MODERATE IRRITATION. MAY CAUSE ALLERGIC REACTION
AND SENSITIZATION IN SOME INDIVIDUALS. EYE: MODERATE TO SEVERE
IRRITATION. CHRONIC: EXPOSURE M
AY CAUSE SOME PEOPLE TO DEVELOP
SKIN RASH,ALLERGIC REACTION AND/OR SKIN SENSITIZATION.
Explanation of Carcinogenicity:NOT RELEVANT.
Effects of Overexposure:SEE HEALTH HAZARDS.
Medical Cond Aggravated by Exposure:ALLERGIC REACTION AND/OR SKIN
SENSITIZATION.

===== ===== First Aid Measures =====

First Aid:SKIN: REMOVE CONTAMINATED CLOTHING; WASH AREA WITH PLENTY OF
SOAP AND WATER; SEE A PHYSICIAN IF IRRITATION DEVELOPS. EYE: FLUSH
WITH WATER FOR AT
LEAST 15 MINUTES. SEE A PHYSICIAN IF IRRITATION
DEVELO PS. INGESTION: INDUCE VOMITING AND CONSULT A PHYSICIAN.
INHALATION: REMOVE TO FRESH AIR. GET MEDICAL ATTENTION IF
NECESSARY.

===== ===== Fire Fighting Measures =====

Flash Point Method:TOC
Flash Point:365F,185C
Upper Limits:6%
Extinguishing Media:CARBON DIOXIDE, FOAM, DRY CHEMICAL.
Fire Fighting Procedures:USE NIOSH APPROVED SCBA & FULL PROTECTIVE
EQUIPMENT . DO NOT ENTER CONFINED SPACE WITHOUT
PROPER PROTECTIVE
EQUIPMENT.
Unusual Fire/Explosion Hazard:NONE KNOWN.

===== ===== Accidental Release Measures =====

Spill Release Procedures:AVOID SKIN AND EYE CONTACT, SCRAPE UP AND
PLACE IN CONTAINER.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== ===== Handling and Storage =====

Handling and Storage Precautions:AVOID PROLONGED SKIN & EYE CONTACT,
FOR INDUSTRIAL USE ONLY, KEEP OUT OF THE REACH OF CHILDREN. STORE

IN A COOL DRY PLACE, AWAY FROM SOURCES OF HEAT.

Other Precautions:NONE SPECIFIED BY MANUFACTURER.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NORMALLY NEEDED. NIOSH APPROVED RESPIRATOR APPROPRIATE FOR EXPOSURE OF CONCERN .

Ventilation:LOCAL EXHAUST MAY BE NEEDED IF MATERIAL IS HEATED.

Protective Gloves:IMPERVIOUS GLOVES.

Eye Protection:ANSI APPROVED CHEM WORKERS GOGGS .

Other Protective Equipment:EYE WASH FOUNTAIN & DELUGE SHOWER WHICH MEET

ANSI DESIGN CRITERIA . CLEAN LONG SLEEVE, LONG LEG CLOTHING.

Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health

VAPOR DENSITY: NON VOLATILE.

=====
===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:NONE

Melt/Freeze Pt:M.P/F.P Text:1.42

Vapor Pres:SEE ING 2

Vapor Density:SUPDAT

Spec Gravity:1.42497

Evaporation Rate & Reference:N-BUTYL ACETATE

Solubility in Water:1.42497

Appearance and Odor:LIGHT BROWN VISC. PASTE W/
AMINE ODOR.

Percent Volatiles by Volume:0.0

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

EPOXY RESINS.

Stability Condition to Avoid:AVOID MIXING WITH LARGE AMOUNTS OF EPOXY RESIN. NO MORE THAN TWO POUNDS.

Hazardous Decomposition Products:CARBON DIOXIDE, CARBON MONOXIDE, AMMONIA, OTHERS POSSIBLE.

=====
===== Disposal Considerations =====

Waste Disposal Methods:THIS MATERIAL IF DISCARDED MAY BE

HAZARDOUS AS

DEFINED BY GOVERNMENT REGULATIONS AND, THEREFORE MAY BE SUBJECT TO STORAGE. TRANSPORTATION AND DISPOSAL REQUIREMENTS. DISCARD IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all

liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.