

FARWEST PAINT MFG CO -- SPAR VARNISH -- 8010-00-160-5852

===== Product Identification =====

Product ID:SPAR VARNISH

MSDS Date:02/01/1998

FSC:8010

NIIN:00-160-5852

MSDS Number: CHXRH

=== Responsible Party ===

Company Name:FARWEST PAINT MFG CO

Address:4522 S 133 ST

Box:68726

City:SEATTLE

State:WA

ZIP:98168-3251

Country:US

Info Phone Num:206-244-8844

Emergency Phone Num:206-244-8844

CAGE:6F266

=== C

Contractor Identification ===

Company Name:FARWEST PAINT MANUFACTURING CO

Address:4522 SOUTH 133RD ST

Box:City:TUKWILA

State:WA

ZIP:98168

Country:US

Phone:206-244-8844

CAGE:6F266

===== Composition/Information on Ingredients =====

Ingred Name:MINERAL SPIRITS

CAS:8052-41-3

RTECS #:WJ8925000

Fraction by Wt: 37.5%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM

ACGIH TLV:100 PPM; 9495

Ingred Name:GLYCOL ETHER EP

CAS:2807-30-9

RTECS #:KM2800000

Fraction by Wt: 4.6%

Other REC Li

mits:NONE RECOMMENDED

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:SKIN: IRRITATION, SENSITIZATION,  
DEFATTING; INHALE: HEADACHE, DIZZINESS, NAUSEA, LOSS OF  
CONSCIOUSNESS, POSSIBLE PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE;  
EYES: IRRITANT  
Effects of Overexposure:ASPIRATION CAN CAUSE CHEMICAL PNEUMONITIS  
Medical Cond Ag  
gravated by Exposure:NONE

=====  
===== First Aid Measures =====

First Aid:SKIN: PROMPTLY WASH WITH SOAP AND WATER; REMOVE AND WASH ANY  
CONTAM CLOTHING BEFORE REUSE. EYES: FLUSH WITH LARGE QUANTITIES OF  
WATER FOR 15 MINUTES; GET MED AID. INGEST: DO NOT INDUCE VOMITING;  
KEE P PERSON WARM AND QUIET; GET MED AID. INHALE: REMOVE TO FRESH  
AIR IMMED; GET MED AID AT ONCE.

=====  
===== Fire Fighting Measures =====

Flash Point  
Method:TCC  
Flash Point:104F,40C  
Autoignition Temp:Autoignition Temp Text:NONE  
Lower Limits:1  
Upper Limits:7  
Extinguishing Media:FOAM, CO2, DRY CHEMICAL, OR WATER FOG, AND ANY  
CLASS B EXTINGUISHING AGENT. WATER MAY BE UNSUITABLE; USE TO COOL  
CONTA  
Fire Fighting Procedures:WEAR SCUBA; EVACUATE AREA, WEAR PROTECTIVE  
CLOTHING  
Unusual Fire/Explosion Hazard:VAPORS MAY FORM AN EXPLOSIVE MIXTURE IN  
AIR AND MAY BE IGNITED BY SPARKS, PILOT LIGHTS, ETC. CLOSED  
CONTAINERS MAY RUPTURE W  
HEN EXPOSED TO EXTREME HEAT.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION; VENTILLATE  
AREA; ABSORB SPILL WITH AN ABSORBENT MATERIAL SUCH AS SAWDUST,  
VERMICULITE, OR SAND AND PLACE MATERIAL INTO CLOSED CONTAINER. IF  
LARGE SPILL: DIKE - PREVENT FROM ENTERING WATER SYSTEMS OR  
SEWERS;PROT EQUIP

=====  
===== Handling and Storage =====

Handling and Storage Precautions:AVOID

ALL UNNECESSARY CONTACT WITH  
THIS MATERIAL; KEEP AWAY FROM IGNITABLES; DO NOT WELD ON FULL OR  
EMPTY CONTAINERS; KEEP CONTAINERS CLOSED ; LABEL

===== Exposure Controls/Personal Protection =====

Respiratory Protection:CANNISTER TYPE RESPIRATOR IS REQUIRED  
Ventilation:GENERAL VENTILATION IS REQUIRED FOR NORMAL USE; LOCAL  
VENTILATION MAY BE REQUIRED MAY BE REQUIRED SOMETIMES  
Protective Gloves:CHEM RESIST NITRILE, NEOPRENE, RUBBER  
Eye Protection:FACE SHIELD; CHEM GOGG  
LES  
Other Protective Equipment:PROTECTIVE CLOTHING, EYEWASH STATION, SAFETY  
SHOWER  
Work Hygienic Practices:WASH HANDS BEFORE EATING OR SMOKING  
Supplemental Safety and Health  
NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:282F,139C  
Vapor Pres:6  
Vapor Density:>1 AIR=1  
VOC Pounds/Gallon:388  
Evaporation Rate & Reference: