

FISKE BROS REFINING CO -- LUBRIPLATE NO 930-A, 930-AA, 930-AAA, 930-2 -- 9150-00-953-1694

=====  
Product Identification  
=====

Product ID:LUBRIPLATE NO 930-A, 930-AA, 930-AAA, 930-2

MSDS Date:01/01/2000

FSC:9150

NIIN:00-953-1694

Status Code:A

MSDS Number: CKKQZ

=== Responsible Party ===

Company Name:FISKE BROS REFINING CO

Address:129 LOCKWOOD ST

City:NEWARK

State:NJ

ZIP:07105-4720

Country:US

Info

Phone Num:201-589-9150

Emergency Phone Num:800-255-3924 CHEM-TEL

Preparer's Name:JAMES R. KONTAK

CAGE:73219

=== Contractor Identification ===

Company Name:FISKE BROS REFINING CO

Address:129 LOCKWOOD ST

Box:City:NEWARK

State:NJ

ZIP:07105-4720

Country:US

Phone:201-589-9150

CAGE:73219

Company Name:FISKE BROTHERS REFINING CO

Address:1500 OAKDALE AVE

Box:City:TOLEDO

State:OH

ZIP:43605

Country:US

Phone:419-691-2491

CAGE:9N579

Company Name:INDUSTRIAL CHEMICAL COMMODITIES INC

Address:15944 DERWOOD RD

B

ox:City:ROCKVILLE  
State:MD  
ZIP:20855  
Country:US  
Phone:800-284-5279  
Contract Num:SP0450-00-M-C237  
CAGE:1ELU0

=====  
Composition/Information on Ingredients  
=====

Ingred Name:MANUFACTURER CLAIMS ONLY NON-HAZARDOUS INGREDIENTS W/O  
SPECIFYING ANY INDIVIDUAL INGREDIENT.

Fraction by Wt: 100%

Other REC Limits:NONE RECOMMENDED

Ingred Name:ZINC COMPOUNDS (SARA III, SECTION 313)  
&lt; Wt:8.

=====  
Hazards Identification  
=====

LD50 LC50 Mixture:NO DA

TA PROVIDED BY RESPONSIBLE PARTY.

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:PROLONGED OR REPEATED SKIN CONTACT MAY  
CAUSE SKIN IRRITATION. PRODUCT CONTACTING THE EYES MAY CAUSE EYE  
IRRITATION. HUMAN HEALTH RISKS VARY FROM PERSON TO PERSON. AS A  
PRECAUTION, EXPOSURE TO LIQUIDS, VAPORS, MISTS AND FUMES SHOULD BE  
MINIMIZED. THIS PRODUCT HAS A LOW ORDER OF ACUTE ORAL TOXICITY,  
BUT MINUTE AMOUNTS ASPIRATED INTO THE LUNGS DURING INGEST  
ION MAY

CAUSE MILD TO SEVERE PULMONARY I NJURY.

Explanation of Carcinogenicity:NO DATA PROVIDED BY RESPONSIBLE PARTY.

Effects of Overexposure:SKIN/EYE IRRITATION.

Medical Cond Aggravated by Exposure:NO DATA PROVIDED BY RESPONSIBLE  
PARTY.

=====  
First Aid Measures  
=====

First Aid:EYES: FLUSH WITH WATER FOR 15 MINUTES OR UNTIL IRRITATION  
SUBSIDES. IF IRRITATION PERSISTS, CONSULT A PHYSICIAN. SKIN: REMOVE  
ANY CONTAMINATED CLOTHING AND WASH WITH

SOAP AND WARM WATER. IF

INJECTED BY HIGH PRESSURE UNDER THE SKIN, REGARDLESS OF ITS SIZE CONTACT PHYSICIAN IMMEDIATELY. DELAY MAY CAUSE LOSS OF AFFECTED PART OF THE BODY. INHALATION: VAPOR PRESSURE IS VERY LOW AND INHALATION AT ROOM TEMPERATURE IS NOT A PROBLEM. IF OVERCOME BY VAPOR FROM HOT PRODUCT, IMMEDIATELY REMOVE FROM EXPOSURE AND CALL PHYSICIAN. INGESTION: CALL A PHYSICIAN IMMEDIATELY. DO NOT INDUCE VOMITING.

=====  
===== Fire Fighting Measures =====  
=====

Flash Point Method:COC

Flash Point:=-204.4C, 400.F

Lower Limits:0.9

Upper Limits:7.0

Extinguishing Media:FOAM, DRY CHEMICAL, CARBON DIOXIDE OR WATER SPRAY (FOG).

Fire Fighting Procedures:COOL EXPOSED CONTAINERS WITH WATER. USE AIR-SUPPLIED BREATHING EQUIPMENT FOR ENCLOSED OR CONFINED SPACES.

Unusual Fire/Explosion Hazard:DO NOT STORE OR MIX WITH STRONG OXIDANTS. EMPTY CONTAINERS RETAIN RESIDUE. DO NOT CUT, DRILL, GRIND, OR WELD, AS THEY MAY EXPLODE.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:SCRAPE UP GREASE, WASH REMAINDER WITH SUITABLE PETROLEUM SOLVENT OR ADD ABSORBENT. KEEP PETROLEUM PRODUCTS OUT OF SEWERS AND WATER COURSES. ADVISE AUTHORITIES IF PRODUCT HAS ENTERED OR MAY ENTER SEWERS AND WATER COURSES.

Neutralizing Agent:NO DATA PROVIDED BY RESPONSIBLE PARTY.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINER CLOSED WHEN NOT IN USE.

DO NOT HANDLE OR STORE NEAR HEAT, SPARKS, FLAME, OR STRONG OXIDANTS.

Other Precautions:REMOVE OIL-SOAKED CLOTHING AND LAUNDRY BEFORE REUSE. CLEANSE SKIN THOROUGHLY AFTER CONTACT.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NORMALLY NOT NEEDED.

Ventilation:USE LOCAL EXHAUST TO CAPTURE FUMES & VAPORS.

Protective Gloves:USE OIL RESISTANT GLOVES IF NEEDED.

Eye Protection:SAFETY GLASSES OR GOGGLES.

Other Protective Equip

ment:USE OIL-RESISTANT APRON IF NEEDED.

Work Hygienic Practices:NO DATA PROVIDED BY RESPONSIBLE PARTY.

Supplemental Safety and Health

NO DATA PROVIDED BY RESPONSIBLE PARTY.

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:=287.8C, 550.F

Melt/Freeze Pt:M.P/F.P Text:SEMI-SOLID

Vapor Pres:5

Spec Gravity:0.94-0.97

Evaporation Rate & Reference: